Electronics Letters

VOLUME 17, 1981

THE INSTITUTION OF ELECTRICAL ENGINEERS

Electronics Letters

THE INSTITUTION OF ELECTRICAL ENGINEERS

ELECTRONICS LETTERS is published fortnightly.* Price £9·00 ($21·60) per issue; annual subscription in UK £92·00, overseas £126·00 ($302·00). Second-class postage paid at New York, NY. All copies for North America are sent by air freight to New York. Airmail direct to subscriber at an additional charge of £25·00. Available also in a concurrent microfiche edition at the same subscription rate as for the printed edition. The subscription for combined paper and microfiche is £113·00 (UK), overseas £168·00 ($403·00)

*Except in December when only one issue is published. There are 25 issues each year

All subscription inquiries and orders should be sent to the Publication Sales Department, IEE, Station House, Nightingale Road, Hitchin, Herts. SG5 1RJ, England. Telephone Hitchin 53331 (s.t.d. 0462 53331), Telex 825962

Contributions should be addressed to the Executive Editor, *Electronics Letters*, Publishing Department, Institution of Electrical Engineers, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England
There is no page charge

All other correspondence, including advertisements, should be sent to: IEE Publishing Department, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England. Telephone Stevenage 3311 (s.t.d. 0438 3311), Telex 261176, Telegrams Voltampere Stevenage, England. The telephone number of the IEE London office is 01–836 2441, Telex 261176

The advantages of rapid publication given by *Electronics Letters* are nullified if subscribers are subject to excessive delays in the receipt of the journal. The Executive Editor would be grateful to learn of any difficulties subscribers may experience

This publication is copyright under the Berne Convention and the International Copyright Convention. All rights reserved. Apart from any copying under the UK Copyright Act 1956, part 1, section 7, whereby a single copy of an article may be supplied, under certain conditions, for the purposes of research or private study, by a library of a class prescribed by the UK Board of Trade Regulations (Statutory Instruments, 1957, no 868), no part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means without the prior permission of the copyright owners. Permission is, however, not required to copy abstracts of papers or articles on condition that a full reference to the source is shown

The IEE appreciates that, on certain occasions, it could be very useful for organisations to be able to make copies of articles and papers. An IEE licensing arrangement exists whereby organisations entering into an agreement are legally entitled to make up to ten copies of an IEE paper or article. Full details may be obtained from the IEE Publishing Department at the above address

The appearance of the code at the bottom of an article in this journal indicates the copyright owner's consent that copies of the article may be made in the USA for personal or internal use, or for the personal or internal use of specific clients. This consent is given on the condition, however, that the copier pay the stated per-copy fee through the Copyright Clearance Center, Inc. for copying beyond that permitted by Sections 107 or 108 or the US Copyright Law. This consent does not extend to other kinds of copying, such as copying for general distribution, for advertising or promotional purposes for creating new collective works or for resale. Payment is also required for copying of articles published before 1978

The IEE is not as a body responsible for the opinions expressed by individual authors

The IEE is a member of the Association of Learned & Professional Society Publishers

Publishing Department:
IEE
PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

Secretary of the IEE:
H.H.W.Losty

Managing Editor:
Bernard Dunkley

Executive Editor:
Kathy Scales

Assistant Editor:
Nick Matthews

Graphics Manager:
Maurice Partridge

Marketing Manager:
Alan Baldwin

EDITORS
P.J.B.Clarricoats *(London)*
E.A.Ash *(London)*

Advertisement Department:
IEE
PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

©1981: The Institution of Electrical Engineers

The Institution of Electrical Engineers, Savoy Place, London WC2R 0BL, England

Typeset in England by:

Santype International Ltd
Netherhampton Road
Salisbury
Wilts. SP2 8PS

Printed in England by:

C.F.Hodgson & Son Ltd
50 Holloway Road
London N7 8JL

Electronics Letters

INDEX VOLUME 17, 1981

Author index

A

Abbasi, S.A., and Brunnschweiler, A. Effect of masking geometry on gain of bipolar transistors 270

Abbasi, S.A., Takleh, O., Brunnschweiler, A., and Smith, J.G. Variation of diffused boron concentration in the neighbourhood of an oxide-masked edge 578

Abdel Gadir, O.M., and Quarmby, D.J. Microprocessor-based real time system for eye motion analysis 196

Abe, Y., Kishino, K., Suematsu, Y., and Arai, S. GaInAsP/InP integrated laser with butt-jointed built-in distributed-Bragg-reflection waveguide 945

Abe, Y., Kobayashi, K., Utaka, K., and Suematsu, Y. see Kobayashi, K.

Abe, Y., Utaka, K., Kobayashi, K., Koyama, F., and Suematsu, Y. see Utaka, K.

Abramovitz, A., and Bar-Ness, Y. TSRMA-A communication protocol for data transmission by radio channels 526

Ackley, D.E. Leaky-mode channel-guide injection lasers 766

Adams, A.R., and Tatham, H.L. Temperature dependence of the Gunn threshold in GaAs 557

Adams, A.R., Hayes, J.R., Tatham, H.L., and Greene, P.D. see Hayes, J.R.

Adams, A.R., Heasman, K.C., Hayes, J.R., and Greene, P.D. see Heasman, K.C.

Adams, M.J., Francois, P.L., and Sasaki, I. see Francois, P.L.

Adler, E.L. Mismatch losses in multiply tapped SAW convolvers 866

Aggarwal, K.K., and Govil, K.K. see Govil, K.K.

Ahluwalia, H.S., and May, E.J.P. Effect of direct current on spuriously generated third harmonics 851

Ainger, F.W., Whatmore, R.W., Shorrocks, N.M., O'Hara, C., and Young, I.M. see Whatmore, R.W.

Akaike, M., Hagihara, E., and Imai, N. see Hagihara, E.

Akers, L.A. Threshold voltage of a narrow-width MOSFET 49

Akiba, S., Williams, G.E., and Haus, H.A. High rate pulse generation from InGaAsP laser in selfoc lens external resonator 527

Akiba, S., Utaka, K., Sakai, K., and Matsushima, Y. see Utaka, K.

Akita, K., Yamaguchi, A., Nakajima, K., and Takanohashi, T. Effect of substrate orientation on electrical properties of LPE-grown InP 921

Akiya, M., Ohwada, K., and Nakashima, S. High-voltage buried-channel MOS fabricated by oxygen implantation into silicon 640

Alard, F., Jeunhomme, L., and Sansonetti, P. Fundamental mode spot-size measurement in single-mode optical fibres 958

Alba-Flores, R., Sanchez-Sinencio, E., and Silva-Martinez, J. see Sanchez-Sinencio, E.

Albrecht, W., Baack, C., Elze, G., Enning, B., Heydt, G., Peters, K., Walf, G., and Wenke, G. 2.24 Gbit/s optical transmission system at 0.85 μm wavelength 664

Almond, D.P., and Gordon-Smith, D. see Gordon-Smith, D.

Ameri, S., Ash, E.A., Neuman, V., and Petts, C.R. Photo-displacement imaging 337

Ameri, S., and Gunton, D.J. Efficient three-wavelength-output SAW multistrip beam compressor for convolver applications 836 e900

Ananasso, F. Nulling performance of null-steering arrays with digital phase-only weights 255

Andersen-Gott, T., Eriksrud, M., and Mickelson, A.R. see Eriksrud, M.

Anderson, A.P., Shaw, D.I., and Bennett, J.C. see Shaw, D.I.

Andersson, T., Tell, R., and Eng, S.T. see Tell, R.

Ando, H., Susa, N., and Kanbe, H. Planar InP avalanche photodiode with Zn-diffused guard ring 292

Ando, Y., and Nishi, I. Self-aligning optical-fibre connector with magnetic-alloy-clad fibres 793

Andreev, A.T., Grundinin, A.B., Dianov, E.M., Prokhorov, A.M., Guryanov, A.N., Devjatykh, G.G., Ignatjev, S.V., and Hopin, V.F. Experimental study of single-mode W-type optical fibre 416

Andritsos, I., Fray, C., and Papiernik, A. see Fray, C.

Ankiewicz, A., and Pask, C. Analysis of multimode optical fibres with profile perturbations 551

Antar, Y.M.M., Hendry, A., Schlesak, J.J., and Olsen, R.L. see Hendry, A.

Aoshima, R., Kanda, Y., and Takada, A. see Kanda, Y.

Arai, A., Koyama, F., Suematsu, Y., and Kishino, K. see Koyama, F.

Arai, K., Shino, T., Yanagawa, S., Yamada, Y., Kamei, K., Chigira, T., and Nakanisi, T. see Shino, T.

Arai, S., Abe, Y., Kishino, K., and Suematsu, Y. see Abe, Y.

Arai, S., Asada, M., Itoh, K., and Suematsu, Y. see Asada, M.

Arai, S., Tanbun-ek, T., Koyama, F., Kishino, K., Yoshizawa, S., Watanabe, T., and Suematsu, Y. see Tanbun-ek, T.

Arambepola, B. DFT processing of variable length sequences 109

Archer, J.A., Petz, F.A., and Weidlich, H.P. GaAs FET distributed amplifier 433

Archer, J.W., and Mattauch, R.J. Low noise single-ended mixer for 230 GHz 180

Arditty, H.J., Kayoun, P., Puech, C., and Papuchon, M. see Kayoun, P.

Arnaud, J., and Desage, A.M. Optimisation of a graded-index fibre over a wavelength range 339

Arnodo, C., Damay-Kavala, F., and Nuzillat, G. see Damay-Kavala, F.

Arthur, J.W., Campbell, P.A., and Grant, P.M. see Campbell, P.A.

Asada, M., Itoh, K., Suematsu, Y., and Arai, S. Cavity length dependence of differential quantum efficiency of GaInAsP/InP lasers 486

Ash, E.A., Ameri, S., Neuman, V., and Petts, C.R. see Ameri, S.

Asher, P.G., Chang, K., Kung, J.K., Hayashibara, G.M., and Ying, R.S. see Chang, K.

Aspin, G.J., White, I.H., Carroll, J.E., and Plumb, R.G. see White, I.H.

Attal, J., Truong-Quang, N., Cambon, G., Saurel, J.M., and Rouzeyre, M. Acoustic microscopy with noncoherent source 116

Attal, J., Saurel, J.M., Lassale, J., Shahab, G., and Cambon, G. see Saurel, J.M.

Attikiouzel, J., and Crebbin, G. see Crebbin, G.

Atzeni, C., Manes, G.F., Tortoli, P., and Gerli, D. see Manes, G.F.

Auchterlonie, L.J., and Mahmid, B. see Mahmid, B.

Aulbach, R., Fritzsche, D., and Kuphal, E. see Fritzsche, D.

Auld, B.A., Ayter, S., Tan, M., and Hauden, D. Filter detection of phase-modulated laser probe signals 661

Ayasli, Y., Vorhaus, J.L., Mozzi, R., and Reynolds, L. Monolithic GaAs travelling-wave amplifier 413

Ayoub, F. Encryption with keyed random permutations 583 e771

Ayter, S., Auld, B.A., Tan, M., and Hauden, D. see Auld, B.A.

Azimi Sadjadi, M.R., and King, R.A. Truncation error in 2-D block mode filtering 217

B

Baack, C., Elze, G., Enning, B., Heydt, G., Walf, G., and Wenke, G. Optical transmission of 16 digitised TV channels over 21 km fibre at a bit rate of 1.12 Gbit/s 517

Baack, C., Albrecht, W., Elze, G., Enning, B., Heydt, G., Peters, K., Walf, G., and Wenke, G. see Albrecht, W.

Bar-Chaim, N., Katz, J., Ury, I., and Yariv, A. Buried heterostructure AlGaAs lasers on semi-insulating substrates 108

Bar-Ness, Y., and Abramovitz, A. see Abramovitz, A.

Barboza, Z., Maclean, T.S.M., and Saini, S.P.S. see Maclean, T.S.M.

Barker, R.W.J., and Hart, B.L. Design technique for low-current generators 271

Barlow, A.J., and Payne, D.N. Polarisation maintenance in circularly birefringent fibres 388

Barlow, A.J., Payne, D.N., Hadley, M.R., and Mansfield, R.J. Production of single-mode fibres with negligible intrinsic birefringence and polarisation mode dispersion 725

Barnett, S.A., Witkowski, L.C., Drummond, T.J., Morkoc, H., Cho, A.Y., and Greene, J.E. see Witkowski, L.C.

Baron, J.L., and Henry, M. see Henry, M.

Barr, W.P., Turner, B., Cooper, D.P., and Taylor, D.J. see Turner, B.

Barrett, N.J., Gill, S.S., Sealy, B.J., Topham, P.J., and Stephens, K.G. see Gill, S.S.

Bateman, A., and McGeehan, J.P. see McGeehan, J.P.

Bayon, J.F., Poignant, H., and Le Mellot, J. see Poignant, H.

Beale, M. Conditions for synchronisation and corresponding user capacities for spread-spectrum multiple-access systems 410 e862

Beales, K.J., France, P.W., and Partington, S. Double crucible optical fibre for data link applications 846

Beard, S.J., and Rees, H.D. Hot electron effects in Schottky barrier mixers at high frequencies 811

Beck, A.H.W. Reduction of shot noise by the influence of space charge 769

Bellavance, D.W., Lam, H.W., Pinizzotto, R.F., and Yuan, H.T. see Lam, H.W.

Beneking, H., and Su, L.M. GaAlAs/GaAs heterojunction microwave bipolar transistor 301

Beneking, H., and Filensky, W. see Filensky, W.

Beneking, H., Klein, H.J., and Kaumanns, R. see Klein, H.J.

Beneking, H., Wei, C.J., and Klein, H.-J. see Wei, C.J.

Beneš, V.E., and Kurshan, R.P. Wide-sense nonblocking network made of square switches 697

Bennett, J.C., and Yamani, A. Depth of field improvements in long wavelength imaging systems 860
Bennett, J.C., Shaw, D.I., and Anderson, A.P. see Shaw, D.I.
Bennett, R.J., and Thoma, K.A. Determination of an initial mesh for computer simulation of H-abrupt devices 747
Benson, T.M., Murotani, T., Houston, P.A., and Robson, P.N. Photoelastic optical directional couplers in epitaxial GaAs layers 237
Berger, H.P., Welter, R., Dill, A., Guekos, G., and Melchior, H. Tradeoffs between noise, distortion and fibre length for multichannel analogue TV transmission over graded-index fibres at 0.83 μm 844
Berka, J.C., and Herpy, M. Novel active *RC* building block with optimal sensitivity 887
Bermudez, L.A., and Podcameni, A. see Podcameni, A.
Berth, M., Venger, C., and Martin, G.M. Selective carrier removal using oxygen implantation in GaAs 873
Bhattacharyya, A.B., Shankarnarayan, L., and Kapur, N. Performance of an area variable MOS varicap weighted programmable CCD transversal filter 467
Bhuyan, L., and Chatterji, B.N. Very low sensitivity recursive digital filter structures 348
Bickers, L. Schmitt trigger circuit with picosecond risetimes 695
Biey, M. Design of twin-T single amplifier building block with prescribed values of capacitors and minimum gain-sensitivity product 249 e358
Birand, M.T., and Gelsthorpe, R.V. Experimental millimetric array using dielectric radiators fed by means of dielectric waveguide 633
Birand, M.T., and Williams, N. Input VSWR of profiled E-plane tapers 220
Birand, M.T., Wright, P., and Williams, N. Mode conversion in profiled *E*-plane tapers and horns 885
Birand, M.T., Inggs, M.R., and Williams, N. see Inggs, M.R.
Bird, T.S. Investigation of crosspolarisation in offset Cassegrain antennas 585
Biscarri, J., and Gago, A. see Gago, A.
Bisherurwa, E.J.K., and Coakley, F.P. New fast discrete sine transform with offset 803
Blondeau, R., Razeghi, M., Hirtz, P., Larivain, J.P., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Board, K., and Darwish, M. Theory of switching in polysilicon-n-p^+ silicon structures 41
Boccon-Gibod, D., and Meignant, D. see Meignant, D.
Boccon-Gibod, D., and Rocchi, M. see Rocchi, M.
Boeck, J., and Schimpe, R. see Schimpe, R.
Böhm, K., Marten, P., Petermann, K., Weidel, E., and Ulrich, R. Low-drift fibre gyro using a superluminescent diode 352
Bomberger, W.D., and Burke, J.J. Interferometric measurement of dispersion of a single-mode optical fibre 495
Bondeau, R., Razeghi, M., Hirtz, J.P., Hirtz, P., Larivain, J.P., De Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Bone, M.C., King, G.D.H., Weiss, B.L., and Weeks, D.W. see King, G.D.H.
Borelli, W.C., Rashvand, H.F., and Farrell, P.G. Convolutional codes for multi-level modems 331
Borgaonkar, S.R., and Rao, S.N. Analysis and design of DC blocks 101
Boutin, N. Active compensation of op-amp inverting amplifier using NIC 978
Bowers, J.E., and Kino, G.S. Adaptive noise cancellation with a SAW storage correlator 460
Braas, M., and Schieblich, C. E-type circulator for fin lines 701
Brambley, D.R., and Smith, D.C. High efficiency InP transferred electron device for high peak power, high mean power pulsed sources in J-band 307
Bremond, G., Nouailhat, A., Guillot, G., and Cockayne, B. Deep level spectroscopy in InP:Fe 55
Brewitt-Taylor, C.R., Gunton, D.J., and Rees, H.D. Planar antennas on a dielectric surface 729
Brezovich, I.A., Young, J.H., and Wang, M.-T. see Young, J.H.
Bridges, E., Rahman, F., and Shafai, L. see Rahman, F.
Brookbanks, D.M., and Eddison, I.G. see Eddison, I.G.
Brookbanks, D.M., Eddison, I.G., Davies, I., and Giles, P.L. see Eddison, I.G.
Brookbanks, D.M., Eddison, I.G., Davies, I., and Howard, A.M. see Eddison, I.G.
Brookbanks, D.M., Gokgor, H.S., Davies, I., and Howard, A.M. see Gokgor, H.S.
Brosson, P., and Thompson, G.H.B. Current dependence of temperature rise in CW operated GaInAsP/InP DH laser diodes 957
Brown, J.L., Delansky, J., Plotkin, E., Roytman, L.M., and Swamy, M.N.S. Stability test for multidimensional digital filters 717
Brozel, M.R., Tuck, B., and Foulkes, E.J. Diffusion of transition elements in GaAs and InP 532
Brugger, U.W., von Grünigen, D., and Moschytz, G.S. see von Grünigen, D.
Brugger, U.W., Von Grünigen, D., Moschytz, G.S., and Vollenweider, W. see Von Grünigen, D.
Brunnschweiler, A., and Abbasi, S.A. see Abbasi, S.A.
Brunnschweiler, A., Abbasi, S.A., Takleh, O., and Smith, J.G. see Abbasi, S.A.
Brussaard, G. Variability of atmospheric noise temperature in 11-14 GHz band due to water vapour and clouds 20
Bura, P. 70 MHz to 6 GHz FET upconvertor 437
Burgelman, M., and Pauwels, H.J. Theoretical advantages of pn^+-type Cu_2S-ZnO solar cell 224
Burke, J.J., and Bomberger, W.D. see Bomberger, W.D.
Burnham, R.D., Scifres, D.R., and Streifer, W. Low-threshold stripe geometry lasers by metalorganic chemical vapour deposition (MO-CVD) 714
Burnham, R.D., Streifer, W., and Scifres, D.R. see Streifer, W.
Burrus, C.A., Lee, T.P., and Dentai, A.G. Short-cavity single-mode 1.3 μm InGaAsP lasers with evaporated high-reflectivity mirrors 954
Burrus, C.A., Lee, T.P., Ogawa, K., and Dentai, A.G. see Lee, T.P.
Burrus, C.A., Lin, C., Liu, P.L., Lee, T.P., Stone, F.T., and Ritger, A.J. see Lin, C.
Burrus, C.A., Ogawa, K., Lee, T.P., Campbell, J.C., and Dentai, A.G. see Ogawa, K.
Buus, J. Equivalent network analysis of dielectric thin-film waveguide with trapezoidal cross-section (Comment and reply) 497

C

Calleja, E., and Piqueras, J. Effect of vacuum annealing cleaning on electrical characteristics of $GaAs_{1-x}P_x$-Mo Schottky diodes 37
Calzavara, M., Di Vita, P., and Rossi, U. Reliability of a new method for measurements of modal power distribution in optical fibres with application to mode scrambler testing 543
Calzolari, P.U., Masetti, G., Turchetti, C., and Severi, M. Integrated NMOS output stage with low output impedance 218
Cambon, G., Attal, J., Truong-Quang, N., Saurel, J.M., and Rouzeyre, M. see Attal, J.
Cambon, G., Saurel, J.M., Lassale, J., Shahab, G., and Attal, J. see Saurel, J.M.
Cameron, K.H., Preston, K.R., and Woollard, K.C. see Preston, K.R.
Campbell, J.C., Ogawa, K., Lee, T.P., Burrus, C.A., and Dentai, A.G. see Ogawa, K.
Campbell, P.A., Grant, P.M., and Arthur, J.W. Extension of time-bandwidth product in SAW spectrum analysers 576
Card, H.C., Thomson, D.J., and Matiowsky, M.A. see Thomson, D.J.
Carel, M., Henaff, J., and Feldmann, M. see Henaff, J.
Carel, M., Henaff, J., Feldmann, M., and Dubois, R. see Henaff, J.
Carome, E.F., and Koo, K.P. see Koo, K.P.
Carroll, J.E., White, I.H., Aspin, G.J., and Plumb, R.G. see White, I.H.
Casares-Giner, V., and Garcia-Lopez, J.A. see Garcia-Lopez, J.A.
Castaner, L., Llaberia, J., Garrido, J., and Vilamajo, E. Numerical simulation of solar cell open circuit voltage decay 745
Cattermole, K.W., and Sundara Murthy, K.M. see Sundara Murthy, K.M.
Caulton, M., Rosen, A., Wu, C.P., Gombar, A., and Stabile, P. see Rosen, A.
Cederbaum, I. Voltage amplification in switched-capacitor networks 194
Chambers, B. Resolution enhancement in time domain reflectometry systems 154
Chand, N., Houston, P.A., and Robson, P.N. Mn as a p-type dopant in $In_{0.53}Ga_{0.47}As$ on InP substrates 726
Chandra, P., Coldren, L.A., and Strege, K.E. Refractive index data from $Ga_xIn_{1-x}As_yP_{1-y}$ films 6
Chandrasekhar, K., Fray, C., and Papiernik, A. see Fray, C.
Chang, G., Teng, T.C., Shiau, Y., De Ornellas, S., Readdie, J., Wong, E., Ko, S., and Skinner, C. see Teng, T.C.
Chang, H.J., Hwang, H.L., Lin, W.J., and Sun, C.Y. see Hwang, H.L.
Chang, K., Kung, J.K., Asher, P.G., Hayashibara, G.M., and Ying, R.S. GaAs read-type impatt diode for 130 GHz CW operation 471
Chao, P.C., and Ku, W.H. Modelling of dual-gate MESFETS with second gate forward biased 574
Chaplart, J., Delescluse, P., Laviron, M., Delagebeaudeuf, D., and Linh, N.T. see Delescluse, P.
Chaplart, J., Laviron, M., Delagebeaudeuf, D., Delescluse, P., and Linh, N.T. see Laviron, M.
Chassay, G., and Saillard, J. see Saillard, J.
Chatterjee, J.S., and Das, N. see Das, N.
Chatterji, B.N., and Bhuyan, L. see Bhuyan, L.
Cheetham, B.M.G., and Hughes, P.M. see Hughes, P.M.
Chen, P.C., Yu, K.L., Koren, U., Chen, T.R., and Yariv, A. see Yu, K.L.
Chen, R.T., Oliver, J.R., Fairman, R.D., and Yu, P.W. see Oliver, J.R.
Chen, T.R., Yu, K.L., Koren, U., Chen, P.C., and Yariv, A. see Yu, K.L.
Chen, W.H., and Lean, E.G. Grating acoustic scanner using bulk acoustic waves 141
Cheng, D.K., and Liang, C.H. Optimum directivity of elliptic loop antennas 736
Chhotaray, R.K., and Mohanty, A.K. Observer design for differential difference systems 19
Chigira, T., Kamei, K., Kawasaki, H., Nakanisi, T., Kawabuchi, K., and Yoshimi, M. see Kamei, K.
Chigira, T., Shino, T., Yanagawa, S., Yamada, Y., Arai, K., Kamei, K., and Nakanisi, T. see Shino, T.
Childs, P.A., Eccleston, W., and Stuart, R.A. Alternative mechanism for substrate minority carrier injection in MOS devices operating in low level avalanche 281
Chin, A.K., Temkin, H., and Digiuseppe, M.A. see Temkin, H.
Chinnock, E.L., Ogawa, K., Gloge, D., Kaiser, P., Nagel, S.R., and Jang, S.J. see Ogawa, K.
Cho, A.Y., Drummond, T.J., Keever, M., Kopp, W., Morkoç, H., Hess, K., and Streetman, B.G. see Drummond, T.J.
Cho, A.Y., Drummond, T.J., Morkoc, H., Su, S.L., and Fischer, R. see Drummond, T.J.
Cho, A.Y., Witkowski, L.C., Drummond, T.J., Barnett, S.A., Morkoc, H., and Greene, J.E. see Witkowski, L.C.

Cho, F.Y., and Williams, D.F. see Williams, D.F.
Choi D.H., and Salama, C.A.T. Low voltage high performance E/D MOS logic 879
Choi, S.S., and Kim, B.Y. see Kim, B.Y.
Choi, Y-I, Oh, S-H, Kwon, Y-S, and Kim, C-K see Oh, S-H
Choyke, W.J., Wrick, V.L., and Tzeng, C.F. see Wrick, V.L.
Chu, P.L., and Peri, D. Application of focusing method of index profiling to transition region of optical fibre preform 64
Chu, P.L., and Peri, D. see Peri, D.
Chua, S.J. Conditions for operation of semiconductor laser with negative light/current characteristic 848
Chubachi, N., and Kushibiki, J. see Kushibiki, J.
Chubachi, N., Kushibiki, J., and Maehara, H. see Kushibiki, J.
Chubachi, N., Kushibiki, J., and Ohkubo, A. see Kushibiki, J.
Chubachi, N., Kushibiki, J., and Sannomiya, T. see Kushibiki, J.
Chung, P.S., and Wilson, M.G.F. Optical mode conversion using chirped gratings 14
Clarricoats, P.J.B. Theoretical comparison of crosspolar performance of dielectric and corrugated feeds 317
Coakley, F.P., and Bisherurwa, E.J.K. see Bisherurwa, E.J.K.
Cockayne, B., Bremond, G., Nouailhat, A., and Guillot, G. see Bremond, G.
Cohen, A., and Kazovsky, L. see Kazovsky, L.
Coldren, L.A., Chandra, P., and Strege, K.E. see Chandra, P.
Coldren, L.A., Furuya, K., Miller, B.I., and Rentschler, J.A. see Furuya, K.
Cole, R.S., Medeiros Filho, F.C., and Jayasuriya, D.A.R. see Medeiros Filho, F.C.
Coleman, J.J., Dapkus, P.D., and Yang, J.J.J. Single-interface enhanced mobility structures by metalorganic chemical vapour deposition 606
Conduit, A.J., Hartog, A.H., Hadley, M.R., Payne, D.N., Gold, M.P., Mansfield, R.J., and Tarbox, E.J. High-resolution measurement of diameter variations in optical fibres by the backscatter method 742
Conduit, A.J., Payne, D.N., Hartog, A.H., and Gold, M.P. Optical fibre diameter variations and their effect on backscatter loss measurements 308
Connor, F.R. New commutated Doppler radar system 533
Conradi, J., Maciejko, R., Straus, J., Few, I., Duck, G., Sinclair, W., Springthorpe, A.J., and Dyment, J.C. Laser based WDM multichannel video transmission system 91
Conrado, L.F., and Podcameni, A. see Podcameni, A.
Conrado, L.F.M., Podcameni, A., and Mosso, M.M. see Podcameni, A.
Constant, E., and Lippens, D. see Lippens, D.
Cooper, C.B., Dietze, W.T., and Ludowise, M.J. see Dietze, W.T.
Cooper, D.P., Turner, B., Barr, W.P., and Taylor, D.J. see Turner, B.
Copeland, M.A., Van Gelder, I.A., and Declerck, G.J. see Van Gelder, I.A.
Copeland, P.R., Davies, W.S., and Lipback, G.W. see Davies, W.S.
Coppa, G., and Di Vita, P. Solution of wave equation in graded-index optical fibres by means of multiparabolic approximation 896
Craig, P.C., and Westphal, L.C. Two-stage stability test for two-dimensional recursive digital filters 919
Crebbin, G., and Attikiouzel, J. Design of two-dimensional recursive digital filters to a specified stability margin 765
Crowley, J.D., Sowers, J.J., Janis, B.A., and Fank, F.B. see Sowers, J.J.
Cuhaci, M., and Lo, G.J.P. High frequency microstrip branch-line coupler design with T-junction discontinuity compensation 87 e334
Culshaw, B., and Wilson, M.G.F. Integrated optic frequency shifter modulator 135
Curtis, L., and Young, W.C. see Young, W.C.
Cuthbert, L.G., Liau, T.F., and Razzak, M.A. see Liau, T.F.
Czarnecki, L.S. Convertor of optimal capacitance for nonsinusoidal systems compensation to DC voltage 426

D

D'Angelo, R., and Verlangieri, P.A. Ohmic contacts on n-GaAs produced by spark alloying 290
D'Assunçao, A.G., Giarola, A.J., and Rogers, D.A. Characteristics of broadside-coupled microstrip lines with iso/anisotropic substrates 264
D'Assunlao, A.G., and Giarola, A.J. Parallel-coupled microstrip lines on pyrolytic boron nitride 947
Da Rocha, V.C. Multilevel double error correcting codes 45
Daikoku, K., and Yamada, K. see Yamada, K.
Damay-Kavala, F., Nuzillat, G., and Arnodo, C. High-speed frequency dividers with quasi-normally-off GaAs MESFETs 968
Dandridge, A., and Miles, R.O. Spectral characteristics of semiconductor laser diodes coupled to optical fibres 273
Dandridge, A., and Tveten, A.B. Electronic phase noise suppression in diode lasers 937
Dandridge, A., Tveten, A.B., and Giallorenzi, T.G. Interferometric current sensors using optical fibres 523
Dandridge, A., Goldberg, L., Miles, R.O., Giallorenzi, T.G., and Weller, J.F. see Goldberg, L.
Dandridge, A., Leslie, D.H., Trusty, G.L., and Giallorenzi, T.G. see Leslie, D.H.
Dapkus, P.D., Coleman, J.J., and Yang, J.J.J. see Coleman, J.J.
Darwish, M., and Board, K. see Board, K.
Das, N., and Chatterjee, J.S. Quarterwave microstrip antenna on a ferrimagnetic substrate 441
Davies, D.E.N., and Withers, M.J. New approach to compact measurements on reflector antennas 960
Davies, I., Eddison, I.G., Giles, P.L., and Brookbanks, D.M. see Eddison, I.G.
Davies, I., Eddison, I.G., Howard, A.M., and Brookbanks, D.M. see Eddison, I.G.
Davies, I., Gokgor, H.S., Howard, A.M., and Brookbanks, D.M. see Gokgor, H.S.
Davies, J.B., Philippou, G.Y., and Gupta, G.S. see Philippou, G.Y.
Davies, W.S., Lipback, G.W., and Copeland, P.R. Bird-proof feed-horn windows for microwave radio system antennas 777
Davison, A.M., Fung, S., Nicholas, R.J., and Stradling, R.A. see Fung, S.
De Albuquerque, A.A., and Lind, L.F. see Lind, L.F.
de Carvalho, J., and Hanson, J.V. Efficient real-time interpolation for D/A conversion 733
De Cremoux, B., Razeghi, M., Hirtz, J.P., Hirtz, P., Larivain, J.P., Bondeau, R., and Duchemin, J.P. see Razeghi, M.
de Cremoux, B., Razeghi, M., Hirtz, P., Larivain, J.P., Blondeau, R., and Duchemin, J.P. see Razeghi, M.
De La Sen, M., and Dormido, S. Nonperiodic sampling and identifiability 922
De Oliveira, A.D., Wilson, M.G.F., and Parriaux, O. Stripe waveguide Y-intersection as efficient coupler for multimode optical communication systems 100
De Crnellas, S., Teng, T.C., Shiau, Y., Readdie, J., Wong, E., Chang, G., Ko, S., and Skinner, C. see Teng, T.C.
De Prunele, G., and Smith, M.S. see Smith, M.S.
de Vincenti, P., Doro, G., and Saitto, A. Reconstruction of bidimensional electromagnetic field by unidimensional sampling technique 324
Declerck, G.J., Van Gelder, I.A., and Copeland, M.A. see Van Gelder, I.A.
Degrauwe, M., Krummenacher, F., and Vittoz, E. see Krummenacher, F.
Delagebeaudeuf, D., Delescluse, P., Laviron, M., Chaplart, J., and Linh, N.T. see Delescluse, P.
Delagebeaudeuf, D., Laviron, M., Delescluse, P., Chaplart, J., and Linh, N.T. see Laviron, M.
Delansky, J., Brown, J.L., Plotkin, E., Roytman, L.M., and Swamy, M.N.S. see Brown, J.L.
Delescluse, P., Laviron, M., Chaplart, J., Delagebeaudeuf, D., and Linh, N.T. Transport properties in GaAs-$Al_xGa_{1-x}As$ heterostructures and MESFET application 342
Delescluse, P., Laviron, M., Delagebeaudeuf, D., Chaplart, J., and Linh, N.T. see Laviron, M.
Den Dulk, R.C., and Huisman, M.P.I. Phase-lock-loop operating ranges measurement 691
Dentai, A.G., Burrus, C.A., and Lee, T.P. see Burrus, C.A.
Dentai, A.G., Lee, T.P., Burrus, C.A., and Ogawa, K. see Lee, T.P.
Dentai, A.G., Ogawa, K., Lee, T.P., Burrus, C.A., and Campbell, J.C. see Ogawa, K.
Denyer, P.B., Reekie, H.M., and Mavor, J. see Reekie, H.M.
Desage, A.M., and Arnaud, J. see Arnaud, J.
Devjatykh, G.G., Andreev, A.T., Grundinin, A.B., Dianov, E.M., Prokhorov, A.M., Guryanov, A.N., Ignatjev, S.V., and Hopin, V.F. see Andreev, A.T.
Devlin, W.J., Walling, R.H., Fiddyment, P.J., Hobbs, R.E., Murrell, D., Spillett, R.E., and Steventon, A.G. Low threshold channelled-substrate buried crescent InGaAsP lasers emitting at 1.54 μm 651
Dewinter, J.C., Kaminow, I.P., Nahory, R.E., and Stulz, L.W. see Kaminow, I.P.
Di Vita, P. Mode power distribution in optical fibres with fluctuation in physical parameters and application to backscattering signal analysis 874
Di Vita, P., Calzavara, M., and Rossi, U. see Calzavara, M.
Di Vita, P., and Coppa, G. see Coppa, G.
Dianov, E.M., Andreev, A.T., Grundinin, A.B., Prokhorov, A.M., Guryanov, A.N., Devjatykh, G.G., Ignatjev, S.V., and Hopin, V.F. see Andreev, A.T.
Dias, M., and Evans, F.J. Algorithms for sampled data signal flow graphs 341
Dietze, W.T., Ludowise, M.J., and Cooper, C.B. Improved mobility in OM-VPE-grown $Ga_{1-x}In_xAs$ 698
Digiuseppe, M.A., Temkin, H., and Chin, A.K. see Temkin, H.
Dill, A., Berger, H.P., Welter, R., Guekos, G., and Melchior, H. see Berger, H.P.
Dintelmann, F. Analysis of 11 GHz slant path fade duration and fade slope 267
Djurdje, P.M. Digital frequency substractor and/or adder based on hybrid PLL 28
Doble, J.E. Interference on microwave digital radio links due to transhorizon propagation 399
Dohsen, M., Kasahara, J., Taira, K., Kato, Y., and Watanabe, N. see Kasahara, J.
Dohsen, M., Kato, Y., Kasahara, J., Taira, K., and Watanabe, N. see Kato, Y.
Donaghy, F.A., Irving, D.H., and Sabine, P.V.H. see Irving, D.H.
Dorda, G., and Schmitt, D. see Schmitt, D.
Dormido, S., and De La Sen, M. see De La Sen, M.
Doro, G., de Vincenti, P., and Saitto, A. see de Vincenti, P.
Downs, T., O'Neill, C.J., and Khan, P.J. see O'Neill, C.J.
Drummond, T., Keever, M., Hess, K., Morkoc, H., and Streetman, B.G. see Keever, M.
Drummond, T.J., Keever, M., Kopp, W., Morkoç, H., Hess, K., Streetman, B.G., and Cho, A.Y. Field dependence of mobility in $Al_{0.2}Ga_{0.8}As/GaAs$ heterojunctions at very low fields 545

Drummond, T.J., Kopp, W., and Morkoç, H. Three period (Al, Ga)As/GaAs heterostructures with extremely high mobilities 442
Drummond, T.J., Morkoc, H., Su, S.L., Fischer, R., and Cho, A.Y. Enhanced mobility in inverted $Al_xGa_{1-x}As/GaAs$ heterojunctions: binary on top of ternary 870
Drummond, T.J., Witkowski, L.C., Barnett, S.A., Morkoc, H., Cho, A.Y., and Greene, J.E. see Witkowski, L.C.
Dubois, R., Henaff, J., Feldmann, M., and Carel, M. see Henaff, J.
Dubost, G. Flat short-circuited strip of one wavelength width and acting at quarter-wave resonance 891
Dubost, G. Short- or open-circuited dipole parallel to perfect reflector plane and embedded in substrate and acting at resonance 914
Duchemin, J.P., Hirtz, J.P., Razeghi, M., Larivain, J.P., and Hersee, S. see Hirtz, J.P.
Duchemin, J.P., Razeghi, M., Hirtz, J.P., Hirtz, P., Larivain, J.P., Bondeau, R., and De Cremoux, B. see Razeghi, M.
Duchemin, J.P., Razeghi, M., Hirtz, P., Larivain, J.P., Blondeau, R., and de Cremoux, B. see Razeghi, M.
Duck, G., Conradi, J., Maciejko, R., Straus, J., Few, I., Sinclair, W., Springthorpe, A.J., and Dyment, J.C. see Conradi, J.
Dutta Roy, S.C., and Kapur, N. see Kapur, N.
Dutta Roy, S.C., and Varanasi, P. see Varanasi, P.
Dvorak, V. Phase-plane analysis of simple Josephson junction model 980
Dyment, J.C., Conradi, J., Maciejko, R., Straus, J., Few, I., Duck, G., Sinclair, W., and Springthorpe, A.J. see Conradi, J.

E

Eastman, L.F., Wang, W.I., and Wood, C.E.C. see Wang, W.I.
Eccleston, W., Childs, P.A., and Stuart, R.A. see Childs, P.A.
Edahiro, T., Hosaka, T., Okamoto, K., Miya, T., and Sasaki, Y. see Hosaka, T.
Edahiro, T., Hosaka, T., Okamoto, K., and Sasaki, Y. see Hosaka, T.
Edahiro, T., Ohmori, Y., and Sasaki, Y. see Ohmori, Y.
Edahiro, T., Ohmori, Y., Sasaki, Y., and Kawachi, M. see Ohmori, Y.
Edahiro, T., Sasaki, Y., Ohmori, Y., and Kawachi, M. see Sasaki, Y.
Edahiro, T., Shibata, N., and Shibata, S. see Shibata, N.
Edahiro, T., Tomaru, S., Yasu, M., and Kawachi, M. see Tomaru, S.
Edahiro, T., Tomaru, T., Kawachi, M., Yasu, M., and Miya, T. see Tomaru, T.
Eddison, I.G., and Brookbanks, D.M. Operating modes of millimetre wave transferred electron oscillators 112
Eddison, I.G., Davies, I., Giles, P.L., and Brookbanks, D.M. Efficient fundamental frequency oscillation from millimetre-wave indium phosphide n^+-n-n^+ transferred electron oscillators 758
Eddison, I.G., Davies, I., Howard, A.M., and Brookbanks, D.M. 60 GHz high-efficiency InP pulsed TEO 948
Elliott, C.T. New detector for thermal imaging systems 312
Eltoukhy, A.A., and Roulston, D.J. Minority-carrier injection into diffused region of small N^+-P junction 619
Eltoukhy, A.A., and Roulston, D.J. Sidewall effects in shallow emitter of small bipolar transistor 845
Elze, G., Albrecht, W., Baack, C., Enning, B., Heydt, G., Peters, K., Walf, G., and Wenke, G. see Albrecht, W.
Elze, G., Baack, C., Enning, B., Heydt, G., Walf, G., and Wenke, G. see Baack, C.
Eng, S.T., Tell, R., and Andersson, T. see Tell, R.
Engelmann, R.W.H. Bandwidth formulas for chromatic limitation in optical fibres 333
Enning, B. Retiming 2.24 Gbit/s and demultiplexing 2.24 to 1.12 Gbit/s in an optical transmission system by means of a single-gate field-effect transistor 548
Enning, B., Albrecht, W., Baack, C., Elze, G., Heydt, G., Peters, K., Walf, G., and Wenke, G. see Albrecht, W.
Enning, B., Baack, C., Elze, G., Heydt, G., Walf, G., and Wenke, G. see Baack, C.
Enomoto, Y., and Yamanaka, K. see Yamanaka, K.
Eriksrud, M., Mickelson, A.R., and Andersen-Gott, T. Backscattering signatures from graded-index fibres with diameter variations 200
Eriksud, M., and Mickelson, A.R. see Mickelson, A.R.
Evans, B.G., and Ganem, H. Simulation of FM/FDM blocks for interference and intermodulation calculations 963
Evans, B.G., Upton, S.A.J., and Holt, A.R. Effect of raindrop shape on crosspolarisation/attenuation relationships 22
Evans, F.J., and Dias, M. see Dias, M.
Evans, P.L., and Jayaram, N. see Jayaram, N.

F

Fabre, J.J., and Leroy, Y. Thermal noise emission of a lossy material for a TEM propagation 376
Fahmy, M.M., and O'Reilly, J. see O'Reilly, J.
Fairman, R.D., Oliver, J.R., Chen, R.T., and Yu, P.W. see Oliver, J.R.
Fan, S-C., and Gregorian, R. see Gregorian, R.
Fanetti, E. Flash technique for GaAs concentrator solar cell measurement 469
Fank, F.B., Sowers, J.J., Janis, B.A., and Crowley, J.D. see Sowers, J.J.
Farrell, P.G., Borelli, W.C., and Rashvand, H.F. see Borelli, W.C.
Faucon, L., and Kennis, P. see Kennis, P.
Feldmann, M., Henaff, J., and Carel, M. see Henaff, J.
Feldmann, M., Henaff, J., Carel, M., and Dubois, R. see Henaff, J.
Fernando, K.V., and Nicholson, H. Degree of controllability due to individual inputs 330
Fernando, K.V., and Nicholson, H. Solution of Lyapunov equation for the state matrix 204
Few, I., Conradi, J., Maciejko, R., Straus, J., Duck, G., Sinclair, W., Springthorpe, A.J., and Dyment, J.C. see Conradi, J.
Fiddyment, P.J., Devlin, W.J., Walling, R.H., Hobbs, R.E., Murrell, D., Spillett, R.E., and Steventon, A.G. see Devlin, W.J.
Fielder, H., Zimmer, G., Hoefflinger, B., Neubert, E., and Vogt, H. see Zimmer, G.
Filanovsky, I.M., and Stromsmoe, K.A. Current-voltage conveyor 129 e316
Filensky, W., and Beneking, H. New technique for determination of static emitter and collector series resistances of bipolar transistors 503
Finnegan, T.F., and Soerensen, O.H. Adjustable microstrip transformer for use with Josephson devices in mm-wave ICs 79
Fischer, R., Drummond, T.J., Morkoc, H., Su, S.L., and Cho, A.Y. see Drummond, T.J.
Fleischer, P.E., Ganesan, A., and Laker, K.R. Parasitic compensated switched capacitor circuits 929
Fleming, J.W., and Raju, V.R. Low-loss single-mode fibres prepared by plasma-enhanced MCVD 867
Fleming, W.P., Lee, C.P., and Welch, B.M. see Lee, C.P.
Flinn, I., Milson, R.F., Murray, R.J., and Redwood, M. see Milson, R.F.
Forrest, J.R., and Seeds, A.J. see Seeds, A.J.
Forrest, S.R., Williams, G.F., Kim, O.K., and Smith, R.G. Excess-noise and receiver sensitivity measurements of $In_{0.53}Ga_{0.47}As/InP$ avalanche photodiodes 917
Forsythe, W., and Marshall, W.G. see Marshall, W.G.
Foulkes, E.J., Brozel, M.R., and Tuck, B. see Brozel, M.R.
France, P.W., Beales, K.J., and Partington, S. see Beales, K.J.
Francois, P.L., Sasaki, I., and Adams, M.J. Three-dimensional fibre preform profiling 876
Fray, C., Andritsos, I., and Papiernik, A. Additional losses and time delay fluctuations of TE_{11} modes in curved circular waveguides-application to feeder antennas 362
Fray, C., Chandrasekhar, K., and Papiernik, A. Reflection analysis of flanged circular waveguide radiating through small aperture into absorbing medium 718
Freude, W. Far-field profiling of multimode optical fibres 385
Fritzsche, D., Kuphal, E., and Aulbach, R. Fast response InP/InGaAsP heterojunction phototransistors 178
Fujii, Y., and Minowa, J. Cylindrical concave diffraction grating utilising thin silicon chip 934
Fujii, Y., Sakaki, H., Misawa, M., and Hidaka, H. see Sakaki, H.
Fujii, Y., Tachikawa, Y., Ohnishi, K., and Nagata, Y. see Tachikawa, Y.
Fujisawa, K., and Yamamoto, Y. see Yamamoto, Y.
Fung, S., Nicholas, R.J., Davison, A.M., and Stradling, R.A. Chromium contamination in VPE InP from photoconductivity spectra 188
Furukawa, S., Matsumura, H., and Kanamori, M. see Matsumura, H.
Furuta, O., and Yamada, M. Effective canting angle of distorted raindrops along earth-space propagation path 170
Furutsuka, T., Tsuji, T., Katano, F., Higashisaka, A., and Kurumada, K. Ion-implanted E/D-type GaAs IC technology 944
Furutsuka, T., Katano, F., and Higashisaka, A. see Katano, F.
Furuya, K., Coldren, L.A., Miller, B.I., and Rentschler, J.A. Crystallographic facets chemically etched in GaInAsP/InP for integrated optics 582

G

Gago, A., and Biscarri, J. Low-cost multiprocessor system 924
Ganem, H., and Evans, B.G. see Evans, B.G.
Ganesan, A., Fleischer, P.E., and Laker, K.R. see Fleischer, P.E.
Gannon, J.R., and Rosiewicz, A. see Rosiewicz, A.
Garcia-Lopez, J.A., and Casares-Giner, V. Modified Lin's empirical formula for calculation rain attenuation on a terrestrial path 34
Garlichs, G. Polarisation behaviour fluctuations of a single-mode fibre 894
Garrido, J., Castaner, L., Llaberia, J., and Vilamajo, E. see Castaner, L.
Gaw, C.A., and Reynolds, C.L. Transmission cathodoluminescence as a screening technique for rake lines in (Al, Ga)As DH laser material 285
Gelsthorpe, R.V., and Birand, M.T. see Birand, M.T.
Gen-ei, K., Ito, H., Onodera, N., and Inaba, H. see Ito, H.
Gerli, D., Manes, G.F., Tortoli, P., and Atzeni, C. see Manes, G.F.
Gharavi, H. Differential encoding of composite SECAM colour TV signals 122
Giallorenzi, T.G., Dandridge, A., and Tveten, A.B. see Dandridge, A.
Giallorenzi, T.G., Goldberg, L., Dandridge, A., Miles, R.O., and Weller, J.F. see Goldberg, L.
Giallorenzi, T.G., Leslie, D.H., Trusty, G.L., and Dandridge, A. see Leslie, D.H.
Giarola, A.J., D'Assunçao, A.G., and Rogers, D.A. see D'Assunçao, A.G.
Giarola, A.J., and D'Assunlao, A.G. see D'Assunlao, A.G.
Giles, P.L., Eddison, I.G., Davies, I., and Brookbanks, D.M. see Eddison, I.G.

Gill, A., and Shannon, J.M. see Shannon, J.M.
Gill, S.S., Sealy, B.J., Topham, P.J., Barrett, N.J., and Stephens, K.G. Annealing of Si_3N_4-capped ion-implanted InP 623
Gillingham, P. Strays-insensitive switched capacitor biquads with reduced number of capacitors 171 e246
Glass, N.E., and Maradudin, A.A. Shear surface elastic waves on large amplitude gratings 773
Gloanec, M., Jarry, J., and Nuzillat, G. GaAs digital integrated circuits for very high-speed frequency division 763
Gloge, D., Ogawa, K., Chinnock, E.L., Kaiser, P., Nagel, S.R., and Jang, S.J. see Ogawa, K.
Gobet, C.A. Spectral distribution of a sampled 1st-order lowpass filtered white noise 720
Gokgor, H.S., Davies, I., Howard, A.M., and Brookbanks, D.M. High-efficiency millimetre-wave silicon impatt oscillators 744
Gold, M.P., and Hartog, A.H. Measurement of backscatter factor in single-mode fibres 965
Gold, M.P., Conduit, A.J., Hartog, A.H., Hadley, M.R., Payne, D.N., Mansfield, R.J., and Tarbox, E.J. see Conduit, A.J.
Gold, M.P., Conduit, A.J., Payne, D.N., and Hartog, A.H. see Conduit, A.J.
Goldberg, L., Dandridge, A., Miles, R.O., Giallorenzi, T.G., and Weller, J.F. Noise characteristics in line-narrowed semiconductor lasers with optical feedback 677
Goldberg, L., Taylor, H.F., and Weller, J.F. Time-dependent thermal effects in current-modulated semiconductor lasers 497
Gombar, A., Rosen, A., Wu, C.P., Caulton, M., and Stabile, P. see Rosen, A.
Gomi, J., Yoneyama, T., and Nishida, S. Tube-controlled slab waveguide for millimetre and submillimetre waves 125
Goodwin, G.C., and Hoang, D.B. see Hoang, D.B.
Gordon-Smith, D., and Almond, D.P. Anomalous nonlinearity of quartz crystal filters 207
Goto, H., Sekine, H., Yamada, T., and Suzuki, N. CCD linear image sensor with buried overflow drain structure 904
Goto, M., and Kuwahara, H. see Kuwahara, H.
Govil, K.K., and Aggarwal, K.K. New method for maximum power consideration in solar cells with and without resistive losses 5
Graffeuil, J. Low-frequency noise spectrum of GaAs FETs 387
Grant, P.M., Campbell, P.A., and Arthur, J.W. see Campbell, P.A.
Greene, J.E., Witkowski, L.C., Drummond, T.J., Barnett, S.A., Morkoc, H., and Cho, A.Y. see Witkowski, L.C.
Greene, P.D., Hayes, J.R., Tatham, H.L., and Adams, A.R. see Hayes, J.R.
Greene, P.D., Heasman, K.C., Hayes, J.R., and Adams, A.R. see Heasman, K.C.
Greene, P.D., Turley, S.E.H., Henshall, G.D., Knight, V.P., Moule, D.M., and Wheeler, S.A. see Turley, S.E.H.
Gregorian, R., and Fan, S-C. Ladder-simulation switched-capacitor filters with inductor loops 786
Grekhov, I.V., Kardo-Sysoev, A.F., Kostina, L.S., and Shenderey, S.V. High-power subnanosecond switch 422
Grimbleby, J.B. Algorithm for finding the common spanning trees of two graphs 470
Grimbleby, J.B. Symbolic analysis of circuits containing active elements 754
Groubert, E., Peransin, J.M., and Mesbah, M. see Peransin, J.M.
Grundinin, A.B., Andreev, A.T., Dianov, E.M., Prokhorov, A.M., Guryanov, A.N., Devjatykh, G.G., Ignatjev, S.V., and Hopin, V.F. see Andreev, A.T.
Guekos, G., Berger, H.P., Welter, R., Dill, A., and Melchior, H. see Berger, H.P.
Guena, J., Loriou, B., and Sautereau, J.F. see Loriou, B.
Guillot, G., Bremond, G., Nouailhat, A., and Cockayne, B. see Bremond, G.
Gulyaev, Yu.V., Mansfeld, G.D., and Orlova, G.A. Acoustionjection transistor - A new type of electrically controlled transducer 396
Gunshor, R.L., Melloch, M.R., and Pierret, R.F. see Melloch, M.R.
Gunton, D.J., and Ameri, S. see Ameri, S.
Gunton, D.J., Brewitt-Taylor, C.R., and Rees, H.D. see Brewitt-Taylor, C.R.
Guo, Y.C., and Smith, M.S. Phase weighting for linear antenna arrays 121
Gupta, G.S., Philippou, G.Y., and Davies, J.B. see Philippou, G.Y.
Guruprasada Rau, V. Minimum trajectory sensitivity of a linear system 563
Guryanov, A.N., Andreev, A.T., Grundinin, A.B., Dianov, E.M., Prokhorov, A.M., Devjatykh, G.G., Ignatjev, S.V., and Hopin, V.F. see Andreev, A.T.

H

Haddon, J., Moulsley, T.J., Lo, P., and Vilar, E. see Moulsley, T.J.
Hadley, M.R., Barlow, A.J., Payne, D.N., and Mansfield, R.J. see Barlow, A.J.
Hadley, M.R., Conduit, A.J., Hartog, A.H., Payne, D.N., Gold, M.P., Mansfield, R.J., and Tarbox, E.J. see Conduit, A.J.
Hagihara, E., Akaike, M., and Imai, N. Radiation suppressed high-Q dielectric resonators for MIC applications 213
Halgren, R.C., and Peterson, I.R. Simple phase-locked loop with large pull-in range to noise bandwidth ratio 448
Hamdy, S.M.A., and Parker, E.A. see Parker, E.A.
Hamdy, S.M.A., Parker, E.A., and Langley, R.J. see Parker, E.A.
Hang, C.C., and Tang, H.S. see Tang, H.S.
Hansen, R.C. Effect of field amplitude taper on measured antenna gain and sidelobes 260
Hansen, V. Dipoles of finite length above stratified planar structures 982
Hanson, J.V., and de Carvalho, J. see de Carvalho, J.
Hara, E.H., Machida, S., Ikeda, M., Kanbe, H., and Kimura, T. Optoelectronic matrix switch using heterojunction switching photodiodes 150
Hara, E.H., MacDonald, R.I., and Hum, R.H. see MacDonald, R.I.
Harada, K., Jeong, M.U., Shirafuji, J., Inuishi, Y., Yakushiji, H., and Oka, H. see Jeong, M.U.
Harris, D.J., and Mak, S. Groove-guide microwave detector for 100 GHz operation 516
Harris, D.J., and Teo, T.M. Extinction cross-section measurements on single falling water drops at 100 GHz 7
Harrison, A.P., Irven, J., and Smith, C.R. see Irven, J.
Hart, B.L. Offset voltage, CMRR and PSRR of a long-tailed pair: an integrated approach 537
Hart, B.L., and Barker, R.W.J. see Barker, R.W.J.
Hartog, A.H., Conduit, A.J., Hadley, M.R., Payne, D.N., Gold, M.P., Mansfield, R.J., and Tarbox, E.J. see Conduit, A.J.
Hartog, A.H., Conduit, A.J., Payne, D.N., and Gold, M.P. see Conduit, A.J.
Hartog, A.H., and Gold, M.P. see Gold, M.P.
Haruna, M., and Koyama, J. Thermo-optic effect in $LiNbO_3$ for light deflection and switching 842
Hasegawa, H., and Seki, S. see Seki, S.
Hashimoto, K.Y., Yamaguchi, M., and Kogo, H. see Yamaguchi, M.
Hashimoto, M. Cutoff frequencies of vector wave modes in cladded inhomogeneous optical fibre (Comment) 17
Hashimoto, M. Hybrid modes of graded-index optical fibres 659 e987
Hashizume, N., Yamada, H., Kojima, T., Matsumoto, K., and Tomizawa, K. Low-power gigabit logic by GaAs SSFL 553
Hashizume, N., Yamada, H., and Tomizawa, K. Schottky-barrier coupled Schottky-barrier gate GaAs FET logic 51
Hashizume, N., Tomizawa, K., Matsumoto, K., and Suzuki, F. see Tomizawa, K.
Hatch, C.B., Westbrook, L.D., and Nelson, A.W. see Westbrook, L.D.
Hatori, K., Shibata, K., Yanagisawa, H., and Torimura, Y. see Shibata, K.
Hauden, D., Auld, B.A., Ayter, S., and Tan, M. see Auld, B.A.
Haus, H.A., Akiba, S., and Williams, G.E. see Akiba, S.
Hauser, J.R., Takeda, Y., and Littlejohn, M.A. see Takeda, Y.
Hawkins, R.J. New technique for determination of static emitter and collector series resistances of bipolar transistors (Comment) 735
Hawrylo, F.Z. LPE growth of 1.3 μm InGaAsP CW lasers on (110) InP substrates 282
Hayashibara, G.M., Chang, K., Kung, J.K., Asher, P.G., and Ying, R.S. see Chang, K.
Haydl, W.H. Harmonic operation of GaAs millimetre wave transferred electron oscillators 825
Hayes, J.R., Tatham, H.L., Adams, A.R., and Greene, P.D. Pressure dependence of hole mobility in $In_{1-x}Ga_xAs_yP_{1-y}$ and its relation to alloy scattering 230
Hayes, J.R., Heasman, K.C., Adams, A.R., and Greene, P.D. see Heasman, K.C.
Healey, P. Multichannel photon-counting backscatter measurements on monomode fibre 751
Healey, P. Optical orthogonal pulse compression codes by hopping 970
Healey, P. OTDR in monomode fibres at 1.3 μm using a semiconductor laser 62
Heasman, K.C., Hayes, J.R., Adams, A.R., and Greene, P.D. Temperature dependence of the transferred electron threshold current in $In_{1-x}Ga_xAs_yP_{1-y}$ 756
Heckmann, S. Modal noise in single-mode fibres operated slightly above cutoff 499
Helszajn, J., and Lyon, R.W. Approximate determination of effective radius and effective dielectric constant of microstrip disc resonators 46
Henaff, J., Feldmann, M., and Carel, M. Voltage-controlled SAW filter on berlinite 86
Henaff, J., Feldmann, M., Carel, M., and Dubois, R. New SSBW mode in GaAs 427
Hendry, A., Antar, Y.M.M., Schlesak, J.J., and Olsen, R.L. Melting layer attenuation at 28.6 GHz from simultaneous comstar beacon and polarisation diversity radar data 190
Henry, M., and Baron, J.L. 4 GBIT/s pseudo-noise generator using GaAs MESFETs 928
Henshall, G.D., Turley, S.E.H., Greene, P.D., Knight, V.P., Moule, D.M., and Wheeler, S.A. see Turley, S.E.H.
Herbst, D., Hosticka, B.J., Höfflinger, B., Kleine, U., Nientiedt, W., and Schweer, R. Integrated CMOS SC filter with 170 kHz cutoff frequency 205
Herbst, D., Hosticka, B.J., and Hoefflinger, B. see Hosticka, B.J.
Herbst, D., Kleine, U., Hoefflinger, B., Hosticka, B.J., and Schweer, R. see Kleine, U.
Herbst, D., and Pandel, J. see Pandel, J.
Herpy, M., and Berka, J.C. see Berka, J.C.
Herranze, J., and Verdú, S. see Verdú, S.
Herrmann, H., and Voshchenkov, A.M. see Voshchenkov, A.M.
Hersee, S., Hirtz, J.P., Razeghi, M., Larivain, J.P., and Duchemin, J.P. see Hirtz, J.P.
Hess, K., Drummond, T.J., Keever, M., Kopp, W., Morkoç, H., Streetman, B.G., and Cho, A.Y. see Drummond, T.J.
Hess, K., Keever, M., Drummond, T., Morkoc, H., and Streetman, B.G. see Keever, M.
Heydt, G., Albrecht, W., Baack, C., Elze, G., Enning, B., Peters, K., Walf, G., and Wenke, G. see Albrecht, W.

Heydt, G., Baack, C., Elze, G., Enning, B., Walf, G., and Wenke, G. see Baack, C.
Hidaka, H., Sakaki, H., Fujii, Y., and Misawa, M. see Sakaki, H.
Higashimoto, M., Ishihara, K., Uchida, N., Ishida, Y., and Sugawara, Y. see Ishihara, K.
Higashisaka, A., Furutsuka, T., Tsuji, T., Katano, F., and Kurumada, K. see Furutsuka, T.
Higashisaka, A., Katano, F., and Furutsuka, T. see Katano, F.
Higashisaka, A., and Yamamoto, R. see Yamamoto, R.
Higuchi, H., Oomura, E., Hirano, R., Namizaki, H., Murotani, T., and Susaki, W. see Oomura, E.
Hill, D.R. New technique to improve antenna measurements in the presence of site reflections 257 e334
Hirano, R., Oomura, E., Higuchi, H., Namizaki, H., Murotani, T., and Susaki, W. see Oomura, E.
Hirata, Y. SSB-FDM using complementary comb filters 614
Hirayama, M., Ino, M., and Ohmori, M. see Ino, M.
Hirayama, M., Takada, T., and Yokoyama, K. see Takada, T.
Hirtz, J.P., Razeghi, M., Larivain, J.P., Hersee, S., and Duchemin, J.P. Low threshold GaInAsP/InP lasers with good temperature dependence grown by low pressure MOVPE 113
Hirtz, J.P., Razeghi, M., Hirtz, P., Larivain, J.P., Bondeau, R., De Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Hirtz, P., Razeghi, M., Hirtz, J.P., Larivain, J.P., Bondeau, R., De Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Hirtz, P., Razeghi, M., Larivain, J.P., Blondeau, R., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Hoang, D.B., and Goodwin, G.C. Lower bound on one shot error probability 261
Hobbs, R.E., Devlin, W.J., Walling, R.H., Fiddyment, P.J., Murrell, D., Spillett, R.E., and Steventon, A.G. see Devlin, W.J.
Hodges, M.R.L. Effect of threshold offsets in zero-crossing speech detector 682
Hodgkiss, W. Extraction of decision level for envelope-detected amplitude-shift keying 881
Hoefflinger, B., Hosticka, B.J., and Herbst, D. see Hosticka, B.J.
Hoefflinger, B., Kleine, U., Herbst, D., Hosticka, B.J., and Schweer, R. see Kleine, U.
Hoefflinger, B., Zimmer, G., Fielder, H., Neubert, E., and Vogt, H. see Zimmer, G.
Höfflinger, B., Herbst, D., Hosticka, B.J., Kleine, U., Nientiedt, W., and Schweer, R. see Herbst, D.
Holbeche, J., and King, R.A. see King, R.A.
Holmes, F.E., and Jamal, H. see Jamal, H.
Holt, A.R., Evans, B.G., and Upton, S.A.J. see Evans, B.G.
Honda, T., Yamazaki, H., and Miyazawa, S. see Yamazaki, H.
Honjo, K., Sugiura, T., and Itoh, H. Ultrabroadband GaAs monolithic amplifier 927
Hopin, V.F., Andreev, A.T., Grundinin, A.B., Dianov, E.M., Prokhorov, A.M., Guryanov, A.N., Devjatykh, G.G., and Ignatjev, S.V. see Andreev, A.T.
Horiguchi, M., Kawachi, M., Tomaru, S., Yasu, M., Sakaguchi, S., and Kimura, T. see Kawachi, M.
Horiguchi, M., Shibata, S., Jinguji, K., Mitachi, S., Kanamori, T., and Manabe, T. see Shibata, S.
Horiguchi, T., Nakazawa, M., Tokuda, M., and Uchida, N. see Nakazawa, M.
Horn, P. Positive impedance convertor suitable for high-frequency application 474
Hornung, S., and Reeve, M.H. Single-mode optical fibre microbending loss in a loose tube coating 774
Hosaka, T., Okamoto, K., Miya, T., Sasaki, Y., and Edahiro, T. Low-loss single polarisation fibres with asymmetrical strain birefringence 530
Hosaka, T., Okamoto, K., Sasaki, Y., and Edahiro, T. Single mode fibres with asymmetrical refractive index pits on both sides of core 191
Hosny, E.A., and Sobhy, M.I. see Sobhy, M.I.
Hosticka, B.J., Hoefflinger, B., and Herbst, D. Performance of integrated dynamic MOS amplifiers 298
Hosticka, B.J., Herbst, D., Höfflinger, B., Kleine, U., Nientiedt, W., and Schweer, R. see Herbst, D.
Hosticka, B.J., Kleine, U., Herbst, D., Hoefflinger, B., and Schweer, R. see Kleine, U.
Houston, P.A., Benson, T.M., Murotani, T., and Robson, P.N. see Benson, T.M.
Houston, P.A., Chand, N., and Robson, P.N. see Chand, N.
Howard, A.M., Eddison, I.G., Davies, I., and Brookbanks, D.M. see Eddison, I.G.
Howard, A.M., Gokgor, H.S., Davies, I., and Brookbanks, D.M. see Gokgor, H.S.
Huertas, J.L., and Rodriguez-Vazquez, A. see Rodriguez-Vazquez, A.
Hughes, P.M., and Cheetham, B.M.G. Analysis of noise, sensitivity and dynamic range in digital filters using multiplier extraction approach 286
Huijsing, J.H., and Veelenturf, C.J. Monolithic class AB operational mirrored amplifier 119
Huisman, M.P.I., and Den Dulk, R.C. see Den Dulk, R.C.
Hum, R.H., MacDonald, R.I., and Hara, E.H. see MacDonald, R.I.
Hung-Chia, H., and Zi-Hua, W. Analytical approach to prediction of dispersion properties of step-index single mode optical fibres 202
Hussey, C.D., and Pask, C. Single-mode fibres in a few moments 644
Hutchby, J.A., Takeda, Y., Littlejohn, M.A., and Trew, R.J. see Takeda, Y.
Hwang, H.L., Lin, W.J., Chang, H.J., and Sun, C.Y. Preparation of $CuInS_2$ on GaP grown by LPE 245

I

Iga, K., Moriki, K., Uchida, M., Wakao, K., and Kunikane, T. see Moriki, K.
Iga, K., Oikawa, M., and Sanada, T. see Oikawa, M.
Ignatjev, S.V., Andreev, A.T., Grundinin, A.B., Dianov, E.M., Prokhorov, A.M., Guryanov, A.N., Devjatykh, G.G., and Hopin, V.F. see Andreev, A.T.
Ikeda, M. Laser diode switch 899
Ikeda, M., Hara, E.H., Machida, S., Kanbe, H., and Kimura, T. see Hara, E.H.
Ikeda, M., and Murakami, Y. see Murakami, Y.
Ikeda, M., Uesugi, N., and Sasaki, Y. see Uesugi, N.
Ikuno, H. Asymptotic eigenvalues of vector wave equation for guided modes in graded-index fibre 8
Ikuno, H., and Yata, A. see Yata, A.
Ilumoka, A., and Spence, R. Economic choice of component tolerances 979
Imai, H., Ishikawa, H., Tanahashi, T., and Takusagawa, M. InGaAsP/InP separated multiclad layer stripe geometry lasers emitting at 1.5 μm 17
Imai, H., Ishikawa, H., Tanahashi, T., Nishitani, Y., and Takusagawa, M. see Ishikawa, H.
Imai, N., Hagihara, E., and Akaike, M. see Hagihara, E.
Imoto, K., and Sumi, M. Modified VAD method for optical-fibre fabrication 525
Inaba, H., Ito, H., Onodera, N., and Gen-ei, K. see Ito, H.
Inada, K., Tanaka, M., Kobayashi, T., Sugawara, Y., Tanaka, C., Katsuyama, Y., and Ishida, Y. see Tanaka, M.
Inggs, M.R., Birand, M.T., and Williams, N. Experimental 30 GHz printed array with low loss insular guide feeder 146
Inggs, M.R., and Williams, N. Experimental evaluation of bend radiation losses in millimetric dielectric waveguide 75
Ino, M., Hirayama, M., and Ohmori, M. Analysis for optimum threshold voltage and load current of E-D-type GaAs DCFL circuits 522
Inoue, T., and Ueno, F. New switched capacitor ladder filter with reduced number of amplifiers 209
Inuishi, M., and Wessels, B.W. Deep hole traps in VPE p-type InP 685
Inuishi, Y., Jeong, M.U., Shirafuji, J., Yakushiji, H., Harada, K., and Oka, H. see Jeong, M.U.
Irish, R.T. Performance of Ruthroff transformer with reactive loads 913
Irven, J. Long wavelength performance of $SiO_2/GeO_2/P_2O_5$ core fibres with different P_2O_5 levels 2
Irven, J., Harrison, A.P., and Smith, C.R. Long wavelength performance of optical fibres co-doped with fluorine 3
Irving, D.H., Donaghy, F.A., and Sabine, P.V.H. Fibre light acceptance for modified near field technique 250
Isailović, J. Binary data transmission through TV channels by equivalent luminance signal 233
Isailović, J. Realisation of a decoder for two MFM codes 117
Ishibashi, T. InP MESFET with $In_{0.53}Ga_{0.47}As/InP$ heterostructure contacts 215
Ishida, Y., Ishihara, K., Uchida, N., Sugawara, Y., and Higashimoto, M. see Ishihara, K.
Ishida, Y., Mitsunaga, Y., and Katsuyama, Y. see Mitsunaga, Y.
Ishida, Y., Tanaka, M., Kobayashi, T., Sugawara, Y., Inada, K., Tanaka, C., and Katsuyama, Y. see Tanaka, M.
Ishihara, K., Uchida, N., Ishida, Y., Sugawara, Y., and Higashimoto, M. Low loss high-density optical cable with nylon-extruded fibre units 69
Ishihara, K., Miyajima, Y., Kakii, T., Toda, Y., and Tanaka, S. see Miyajima, Y.
Ishii, Y., and Kawasaki, Y. Self-aligned normally-off GaAs MESFET using Sn-doped SiO_2 glass 834
Ishikawa, H., Imai, H., Tanahashi, T., Nishitani, Y., and Takusagawa, M. V-grooved substrate buried heterostructure InGaAsP/InP laser 465
Ishikawa, H., Imai, H., Tanahashi, T., and Takusagawa, M. see Imai, H.
Ito, H., Onodera, N., Gen-ei, K., and Inaba, H. Self-Q-switched picosecond optical pulse generation with tandem-type AlGaAs TJS laser 15
Ito, K., Umeda, Y., Sugiyama, Y., Nakajima, K., Oshima, K., and Nunoshita, M. Bidirectional fibre optic loop-structured network 84
Itoh, H., Honjo, K., and Sugiura, T. see Honjo, K.
Itoh, K., Asada, M., Suematsu, Y., and Arai, S. see Asada, M.
Iwane, G., and Kawaguchi, H. see Kawaguchi, H.

J

Ja, Y.H. Observation of higher-order diffraction components in degenerate four-wave mixing experiments in $Bi_{12}GeO_{20}$ crystals 488
Jaarinen, J., Lehto, A., Jokinen, M., Tiusanen, T., and Luukkala, M. see Lehto, A.
Jaarinen, J., Lehto, A., Tiusanen, T., Jokinen, M., and Luukkala, M. see Lehto, A.
Jack, M.A., McKee, D., Milne, A.D., and Warden, M. Discrimination of pulsed and CW signals using SAW power cepstrum analysis 39
Jacovitti, G. Parameter estimation of an SSR amplitude comparison monopulse extractor 632
Jager, D., and Wedding, B. see Wedding, B.
Jamal, H., and Holmes, F.E. MOS switched capacitor integrator eliminating operational amplifiers 925

Jang, S.J., Ogawa, K., Chinnock, E.L., Gloge, D., Kaiser, P., and Nagel, S.R. see Ogawa, K.
Janis, B.A., Sowers, J.J., Crowley, J.D., and Fank, F.B. see Sowers, J.J.
Jansen, R.H., Kirschning, M., and Koster, N.H.L. see Kirschning, M.
Jarry, J., Gloanec, M., and Nuzillat, G. see Gloanec, M.
Jayaram, N., and Evans, P.L. Distributed mailbox arrangement which facilitates task communication in a multimicroprocessor system 648 e862
Jayasuriya, D.A.R., Medeiros Filho, F.C., and Cole, R.S. see Medeiros Filho, F.C.
Jeong, M.U., Shirafuji, J., Inuishi, Y., Yakushiji, H., Harada, K., and Oka, H. Effect of illumination and gate bias on flat-band voltage in plasma CVD Si-N on n-Si MIS structure 444 e862
Jeunhomme, L. Single-mode-fibre design for 4 μm band operation 560
Jeunhomme, L., Poignant, H., and Monerie, M. Material dispersion evaluation in a fluoride glass 808
Jeunhomme, L., Alard, F., and Sansonetti, P. see Alard, F.
Jinguji, K., Shibata, S., Horiguchi, M., Mitachi, S., Kanamori, T., and Manabe, T. see Shibata, S.
John, S., and Parthasarathy, R. see Parthasarathy, R.
Jokinen, M., Lehto, A., Jaarinen, J., Tiusanen, T., and Luukkala, M. see Lehto, A.
Justesen, J. Fast calculation of impulse responses without multiplications 700

K

Kaiser, P., Ogawa, K., Chinnock, E.L., Gloge, D., Nagel, S.R., and Jang, S.J. see Ogawa, K.
Kajfez, D. Even mode analysis of symmetric coupled microstrip 183
Kajfez, D., Ratkovic, Z., and Smith, C.E. Power dissipation on edges of coupled microstrip 984
Kakii, T., Miyajima, Y., Ishihara, K., Toda, Y., and Tanaka, S. see Miyajima, Y.
Kamei, K., Kawasaki, H., Chigira, T., Nakanisi, T., Kawabuchi, K., and Yoshimi, M. Extremely low-noise MESFETs fabricated by metal-organic chemical vapour deposition 450
Kamei, K., Shino, T., Yanagawa, S., Yamada, Y., Arai, K., Chigira, T., and Nakanisi, T. see Shino, T.
Kaminow, I.P., Nahory, R.E., Stulz, L.W., and Dewinter, J.C. Performance of an improved InGaAsP ridge waveguide laser at 1.3 μm 318
Kamiya, T., Seki, K., and Yanai, H. see Seki, K.
Kanamori, M., Matsumura, H., and Furukawa, S. see Matsumura, H.
Kanamori, T., Mitachi, S., and Miyashita, T. see Mitachi, S.
Kanamori, T., Shibata, S., Horiguchi, M., Jinguji, K., Mitachi, S., and Manabe, T. see Shibata, S.
Kanbe, H., Ando, H., and Susa, N. see Ando, H.
Kanbe, H., Hara, E.H., Machida, S., Ikeda, M., and Kimura, T. see Hara, E.H.
Kanda, Y., Aoshima, R., and Takada, A. Blood compatibility of components and materials in silicon integrated circuits 558
Kaneda, T., Shirai, T., Osaka, F., Yamasaki, S., and Nakajima, K. see Shirai, T.
Kapur, N., and Dutta Roy, S.C. Method for reducing coefficient sensitivity in lowpass CCD transversal filters 435
Kapur, N., Bhattacharyya, A.B., and Shankarnarayan, L. see Bhattacharyya, A.B.
Kardo-Sysoev, A.F., Grekhov, I.V., Kostina, L.S., and Shenderey, S.V. see Grekhov, I.V.
Karim, A.A.A., Nagarajan, R., and Mirza, K.B. Discrete time MRAS with reduced implementation complexity 809
Kasahara, J., Taira, K., Kato, Y., Dohsen, M., and Watanabe, N. Fully ion-implanted GaAs ICs using normally-off JFETs 621
Kasahara, J., Kato, Y., Dohsen, M., Taira, K., and Watanabe, N. see Kato, Y.
Kasai, T., Terui, H., and Kobayashi, M. see Terui, H.
Kashyap, S.C. Dielectric properties of blood plasma 713
Katano, F., Furutsuka, T., and Higashisaka, A. High speed normally-off GaAs MESFET integrated circuit 236
Katano, F., Furutsuka, T., Tsuji, T., Higashisaka, A., and Kurumada, K. see Furutsuka, T.
Katayama, Y., Kurokawa, T., Yoshizawa, T., and Nara, S. see Kurokawa, T.
Katić, O., and Popovich, M.V. see Popovich, M.V.
Kato, Y., Dohsen, M., Kasahara, J., Taira, K., and Watanabe, N. Planar normally-off GaAs JFET for high speed logic circuits 951
Kato, Y., Kasahara, J., Taira, K., Dohsen, M., and Watanabe, N. see Kasahara, J.
Katsuyama, T., Matsumura, H., and Suganuma, T. Low-loss single-polarisation fibres 473
Katsuyama, Y., Mitsunaga, Y., and Ishida, Y. see Mitsunaga, Y.
Katsuyama, Y., Shibata, N., Tateda, M., and Seikai, S. see Shibata, N.
Katsuyama, Y., Tanaka, M., Kobayashi, T., Sugawara, Y., Inada, K., Tanaka, C., and Ishida, Y. see Tanaka, M.
Katz, J., Bar-Chaim, N., Ury, I., and Yariv, A. see Bar-Chaim, N.
Kaumanns, R., Klein, H.J., and Beneking, H. see Klein, H.J.
Kawabuchi, K., Kamei, K., Kawasaki, H., Chigira, T., Nakanisi, T., and Yoshimi, M. see Kamei, K.
Kawachi, M., Tomaru, S., Yasu, M., Horiguchi, M., Sakaguchi, S., and Kimura, T. 100 km single mode VAD fibres 57
Kawachi, M., Ohmori, Y., Sasaki, Y., and Edahiro, T. see Ohmori, Y.
Kawachi, M., Sasaki, Y., Ohmori, Y., and Edahiro, T. see Sasaki, Y.
Kawachi, M., Tomaru, S., Yasu, M., and Edahiro, T. see Tomaru, S.
Kawachi, M., Tomaru, T., Yasu, M., Miya, T., and Edahiro, T. see Tomaru, T.
Kawaguchi, H. Bistable operation of semiconductor lasers by optical injection 741
Kawaguchi, H., and Iwane, G. Bistable operation in semiconductor lasers with inhomogeneous excitation 167
Kawanishi, S., Kikuchi, K., and Okoshi, T. see Kikuchi, K.
Kawano, K., and Tomimuro, H. Slot ring resonator and dispersion measurement on slot lines 916
Kawasaki, H., Kamei, K., Chigira, T., Nakanisi, T., Kawabuchi, K., and Yoshimi, M. see Kamei, K.
Kawasaki, Y., and Ishii, Y. see Ishii, Y.
Kayoun, P., Puech, C., Papuchon, M., and Arditty, H.J. Improved coupling between laser diode and single-mode fibre tipped with a chemically etched self-centred diffracting element 400
Kayran, A.H., and King, R.A. Stability test for two-dimensional recursive digital filters using inner determinants 67
Kazovsky, L., and Cohen, A. Estimation of parameter drift rate for detection and prediction of faults 306
Keever, M., Drummond, T., Hess, K., Morkoc, H., and Streetman, B.G. Time dependence of current at high electric fields in $Al_xGa_{1-x}As$-GaAs heterojunction layers 93
Keever, M., Drummond, T.J., Kopp, W., Morkoç, H., Hess, K., Streetman, B.G., and Cho, A.Y. see Drummond, T.J.
Kennis, P., and Faucon, L. Rigorous analysis of planar MIS transmission lines 454
Kersten, R.T., Von Helmolt, C.H., and Schlaak, H.F. see Von Helmolt, C.H.
Khan, P.J., O'Neill, C.J., and Downs, T. see O'Neill, C.J.
Khilla, A.-M. Simple design of X-junction microstrip circulators 681
Kikuchi, K., Okoshi, T., and Kawanishi, S. Achievement of 1 MHz frequency stability of semiconductor lasers by double-loop AFC scheme 515
Kim, B.Y., and Choi, S.S. Backscattering measurement of bending-induced birefringence in single mode fibres 193
Kim, C-K, Oh, S-H, Choi, Y-I, and Kwon, Y-S see Oh, S-H
Kim, J., and Shim, Y. see Shim, Y.
Kim, O.K., Forrest, S.R., Williams, G.F., and Smith, R.G. see Forrest, S.R.
Kimura, M. Microheater and microbolometer using microbridge of SiO_2 film on silicon 80
Kimura, T., Hara, E.H., Machida, S., Ikeda, M., and Kanbe, H. see Hara, E.H.
Kimura, T., Kawachi, M., Tomaru, S., Yasu, M., Horiguchi, M., and Sakaguchi, S. see Kawachi, M.
Kimura, T., Kobayashi, S., and Yamamoto, Y. see Kobayashi, S.
Kimura, T., Machida, S., and Sakai, J. see Machida, S.
Kimura, T., Sakaguchi, S., and Nakahara, M. see Sakaguchi, S.
Kimura, T., Yamada, J.I., and Machida, S. see Yamada, J.I.
King, G.D.H., Bone, M.C., Weiss, B.L., and Weeks, D.W. Ion implanted optical waveguides in $LiNbO_3$ 897
King, R.A., and Holbeche, J. Impact of entropic coding on the time delays associated with time-encoded speech (TES) systems 394
King, R.A., and Azimi Sadjadi, M.R. see Azimi Sadjadi, M.R.
King, R.A., and Kayran, A.H. see Kayran, A.H.
King, R.A., and Pal, S.K. see Pal, S.K.
King, R.J., and Park, K.S. Synthesis of surface reactances using grounded pin bed structure 52
Kino, G.S., and Bowers, J.E. see Bowers, J.E.
Kinoshita, J., and Uematsu, Y. Improvement in surface morphology of InGaAsP-InP wafers by dummy layer technique 223
Kirschning, M., Jansen, R.H., and Koster, N.H.L. Accurate model for open end effect of microstrip lines 123
Kishino, K., Abe, Y., Suematsu, Y., and Arai, S. see Abe, Y.
Kishino, K., Koyama, F., Arai, A., and Suematsu, Y. see Koyama, F.
Kishino, K., Tanbun-ek, T., Arai, S., Koyama, F., Yoshizawa, S., Watanabe, T., and Suematsu, Y. see Tanbun-ek, T.
Kitayama, K., Seikai, S., and Uchida, N. Polarisation-maintaining single-mode fibre with azimuthally inhomogeneous index profile 419
Kitazawa, I., Nomura, Y., Morimitsu, T., and Washio, M. see Nomura, Y.
Klein, H.J., Kaumanns, R., and Beneking, H. High-speed $Ga_{0.47}In_{0.53}As$ photoconductive detector for picosecond light pulses 421
Klein, H.-J., Wei, C.J., and Beneking, H. see Wei, C.J.
Kleine, U., Herbst, D., Hoefflinger, B., Hosticka, B.J., and Schweer, R. Real-time programmable unit-element SC filter for LPC synthesis 600
Kleine, U., Herbst, D., Hosticka, B.J., Höfflinger, B., Nientiedt, W., and Schweer, R. see Herbst, D.
Knight, V.P., Turley, S.E.H., Henshall, G.D., Greene, P.D., Moule, D.M., and Wheeler, S.A. see Turley, S.E.H.
Knott, J.E., and Reif, R. see Reif, R.
Ko, S., Teng, T.C., Shiau, Y., De Ornellas, S., Readdie, J., Wong, E., Chang, G., and Skinner, C. see Teng, T.C.
Kobayashi, K., Utaka, K., Abe, Y., and Suematsu, Y. CW operation of 1.5 - 1.6 μm wavelength GaInAsP/InP buried-heterostructure integrated twin-guide laser with distributed Bragg reflector 366
Kobayashi, K., Utaka, K., Koyama, F., Abe, Y., and Suematsu, Y. see Utaka, K.
Kobayashi, M., Terui, H., and Kasai, T. see Terui, H.

Kobayashi, S., Yamamoto, Y., and Kimura, T. Modulation frequency characteristics of directly optical frequency modulated AlGaAs semiconductor laser 350
Kobayashi, S., Yamamoto, Y., and Kimura, T. Optical FM signal amplification and FM noise reduction in an injection locked AlGaAs semiconductor laser 849
Kobayashi, T., and Okamura, M. see Okamura, M.
Kobayashi, T., Tanaka, M., Sugawara, Y., Inada, K., Tanaka, C., Katsuyama, Y., and Ishida, Y. see Tanaka, M.
Kogo, H., Yamaguchi, M., and Hashimoto, K.Y. see Yamaguchi, M.
Kojima, T., Hashizume, N., Yamada, H., Matsumoto, K., and Tomizawa, K. see Hashizume, N.
Koo, K.P., and Carome, E.F. Frequency mixing in fibre-optic interferometer systems 380
Koo, K.P., and Tran, D.C. see Tran, D.C.
Koopman, J.C., Van De Grijp, A., Meuleman, L.J., Nicia, A.J.A., Roza, E., and Van Heuven, J.H.C. see Van De Grijp, A.
Kopp, W., Drummond, T.J., Keever, M., Morkoç, H., Hess, K., Streetman, B.G., and Cho, A.Y. see Drummond, T.J.
Kopp, W., Drummond, T.J., and Morkoç, H. see Drummond, T.J.
Koren, U., Yu, K.L., Chen, T.R., Chen, P.C., and Yariv, A. see Yu, K.L.
Korolkiewicz, E., and Kulesza, B.L.J. Influence of diode capacitance on performance of balanced microwave mixers 144
Koshiba, M., Morita, H., and Suzuki, M. Finite-element analysis of discontinuity problem of SH modes in an elastic plate waveguide 480
Koshiba, M., Okada, M., and Suzuki, M. Finite-element analysis of topographic waveguides for acoustic surface waves using approximate analytical solutions 856
Koshiba, M., Okada, M., and Suzuki, M. Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method 609
Koshiba, M., and Suzuki, M. Equivalent network analysis of dielectric thin-film waveguide with trapezoidal cross-section 283
Koster, N.H.L., Kirschning, M., and Jansen, R.H. see Kirschning, M.
Kostina, L.S., Grekhov, I.V., Kardo-Sysoev, A.F., and Shenderey, S.V. see Grekhov, I.V.
Kowatsch, M., Lafferl, J., Ungersbäck, F., and Seifert, F.J. Encoding of analogue signals using surface-acoustic-wave chirp filters 475
Koyama, F., Arai, A., Suematsu, Y., and Kishino, K. Dynamic spectral width of rapidly modulated 1.58 μm GAINAsP/InP buried-heterostructure distributed-Bragg-reflector integrated-twin-guide lasers 938
Koyama, F., Tanbun-ek, T., Arai, S., Kishino, K., Yoshizawa, S., Watanabe, T., and Suematsu, Y. see Tanbun-ek, T.
Koyama, F., Utaka, K., Kobayashi, K., Abe, Y., and Suematsu, Y. see Utaka, K.
Koyama, J., and Haruna, M. see Haruna, M.
Krause, J.T., Kurkjian, C.R., and Paek, U.C. Strength of fusion splices for fibre lightguides 232
Krause, J.T., Kurkjian, C.R., and Paek, U.C. Tensile strengths > 4 GPa for lightguide fusion splices 812
Kriezis, E.E., and Tsibukis, T.D. see Tsibukis, T.D.
Krucker, K. Rapid interference suppression using Kalman filter approach 65
Krummenacher, F. High voltage gain CMOS OTA for micropower SC filters 160
Krummenacher, F., Vittoz, E., and Degrauwe, M. Class AB CMOS amplifier for micropower SC filters 433
Ku, W.H., and Chao, P.C. see Chao, P.C.
Kuijk, L.A.M., and van den Bosch, P.P.J. see van den Bosch, P.P.J.
Kulesza, B.L.J., and Korolkiewicz, E. see Korolkiewicz, E.
Kung, J.K., Chang, K., Asher, P.G., Hayashibara, G.M., and Ying, R.S. see Chang, K.
Kunikane, T., Moriki, K., Iga, K., Uchida, M., and Wakao, K. see Moriki, K.
Kuphal, E., Fritzsche, D., and Aulbach, R. see Fritzsche, D.
Kurkjian, C.R., Krause, J.T., and Paek, U.C. see Krause, J.T.
Kurokawa, T., Yoshizawa, T., Nara, S., and Katayama, Y. Precision moulded fibre connector using an electroformed cavity 667
Kurshan, R.P., and Beneš, V.E. see Beneš, V.E.
Kurumada, K., Furutsuka, T., Tsuji, T., Katano, F., and Higashisaka, A. see Furutsuka, T.
Kushibiki, J., and Chubachi, N. Double-layer acoustic antireflection coating for sapphire/water interface 59
Kushibiki, J., Maehara, H., and Chubachi, N. Acoustic properties of evaporated chalcogenide glass films 322 e482
Kushibiki, J., Ohkubo, A., and Chubachi, N. Anisotropy detection in sapphire by acoustic microscope using line-focus beam 534
Kushibiki, J., Ohkubo, A., and Chubachi, N. Linearly focused acoustic beams for acoustic microscopy 520
Kushibiki, J., Sannomiya, T., and Chubachi, N. Broad bandwidth concave transducer for scanning acoustic microscope 42
Kuwahara, H., and Goto, M. Generation of harmonic distortion at fibre connectors 626
Kwon, Y-S, Oh, S-H, Choi, Y-I, and Kim, C-K see Oh, S-H

L

Labarre, T., and Lind, L.F. see Lind, L.F.
Ladbrooke, P.H. Power limiting due to impact ionisation in GaAs MESFETS 338
Lafferl, J., Kowatsch, M., Ungersbäck, F., and Seifert, F.J. see Kowatsch, M.
Laine, D.C., and Yassin, G. see Yassin, G.
Laker, K.R., Fleischer, P.E., and Ganesan, A. see Fleischer, P.E.
Lam, H.W., Pinizzotto, R.F., Yuan, H.T., and Bellavance, D.W. Characteristics of MOSFETS fabricated in silicon-on-insulator material formed by high-dose oxygen ion implantation 356
Lamouler, P., and Monerie, M. see Monerie, M.
Langley, R.J., Parker, E.A., and Hamdy, S.M.A. see Parker, E.A.
Larivain, J.P., Hirtz, J.P., Razeghi, M., Hersee, S., and Duchemin, J.P. see Hirtz, J.P.
Larivain, J.P., Razeghi, M., Hirtz, J.P., Hirtz, P., Bondeau, R., De Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Larivain, J.P., Razeghi, M., Hirtz, P., Blondeau, R., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Lassale, J., Saurel, J.M., Shahab, G., Cambon, G., and Attal, J. see Saurel, J.M.
Lastman, G.J., and Sinha, N.K. see Sinha, N.K.
Laviron, M., Delagebeaudeuf, D., Delescluse, P., Chaplart, J., and Linh, N.T. Low-noise two-dimensional electron gas FET 536
Laviron, M., Delescluse, P., Chaplart, J., Delagebeaudeuf, D., and Linh, N.T. see Delescluse, P.
Lazarus, M.J., Pantoja, F.R., Novak, S., and Somekh, M.G. Wideband tunable mm-wave Gunn oscillator design 739
Lazarus, M.J., Pantoja, F.R., and Somekh, M.G. New moving target simulators for Doppler radar 48
Lazarus, M.J., Somekh, M.G., Novak, S., and Pantoja, F.R. Directional harmonics in Doppler effect 94
Le Mellot, J., Poignant, H., and Bayon, J.F. see Poignant, H.
Lean, E.G., and Chen, W.H. see Chen, W.H.
Lee, C.P., Welch, B.M., and Fleming, W.P. Reliability of AuGe/Pt and AuGe/Ni ohmic contacts on GaAs 407
Lee, C.P., and Lee, S.J. see Lee, S.J.
Lee, J-H. Electron scattering profiles in SOS films measured by temperature-dependent Hall effect 566
Lee, S.J., and Lee, C.P. Temperature effect on low threshold voltage ion-implanted GaAs MESFETs 760
Lee, T.P., Burrus, C.A., Ogawa, K., and Dentai, A.G. Very-high speed back-illuminated InGaAs/InP PIN punch-through photodiodes 431
Lee, T.P., Burrus, C.A., and Dentai, A.G. see Burrus, C.A.
Lee, T.P., Lin, C., Liu, P.L., Burrus, C.A., Stone, F.T., and Ritger, A.J. see Lin, C.
Lee, T.P., Ogawa, K., Burrus, C.A., Campbell, J.C., and Dentai, A.G. see Ogawa, K.
Lehto, A., Jaarinen, J., Tiusanen, T., Jokinen, M., and Luukkala, M. Magnitude and phase in thermal wave imaging 364
Lehto, A., Jokinen, M., Jaarinen, J., Tiusanen, T., and Luukkala, M. Alternating beam method (ABM) in photothermal microscopy (PTM) and photoacoustic microscopy (PAM) 540
Leistner, D. Efficient P-type Si impatt diodes for V-band frequencies 635
Lengyel, G., Meissner, P., Patzak, E., and Zschauer, K.H. Calculation of lateral current spreading and series resistance effects in oxide stripe geometry GaAs-GaAlAs DH lasers 174
Leroy, M. Original improvements of TLM method 684
Leroy, Y., and Fabre, J.J. see Fabre, J.J.
Leroy, Y., Mamouni, A., and Van de Velde, J.C. see Mamouni, A.
Leslie, D.H., Trusty, G.L., Dandridge, A., and Giallorenzi, T.G. Fibre-optic spectrophone 581
Lewis, M.F. High frequency acoustic plate mode device employing interdigital transducers 819
Liang, C.H., and Cheng, D.K. see Cheng, D.K.
Liau, T.F., Razzak, M.A., and Cuthbert, L.G. Phase constraints on FIR digital filters 910
Lidgey, F.J., and Saluja, K.K. see Saluja, K.K.
Lin, C., Liu, P.L., Lee, T.P., Burrus, C.A., Stone, F.T., and Ritger, A.J. Measuring high-bandwidth fibres in the 1.3 μm region with picosecond InGaAsP injection lasers and ultrafast InGaAs detectors 438
Lin, C., and Marcuse, D. Optimum optical pulse width for high bandwidth single-mode fibre transmission 54
Lin, W.J., Hwang, H.L., Chang, H.J., and Sun, C.Y. see Hwang, H.L.
Lind, L.F., and De Albuquerque, A.A. Efficient calculation of multimode CPFSK spectra 456
Lind, L.F., and de Albuquerque, A.A. Spectral calculation of partial response multi-h phase codes 711
Lind, L.F., and Labarre, T. Realisable 100% raised cosine filters 197
Linh, N.T., Delescluse, P., Laviron, M., Chaplart, J., and Delagebeaudeuf, D. see Delescluse, P.
Linh, N.T., Laviron, M., Delagebeaudeuf, D., Delescluse, P., and Chaplart, J. see Laviron, M.
Lipback, G.W., Davies, W.S., and Copeland, P.R. see Davies, W.S.
Lippens, D., and Constant, E. Effect of energy relaxation on injected current pulse in high-frequency impatt diodes 878
Littlejohn, M.A., Takeda, Y., and Hauser, J.R. see Takeda, Y.
Littlejohn, M.A., Takeda, Y., Hutchby, J.A., and Trew, R.J. see Takeda, Y.
Liu, P.L., Lin, C., Lee, T.P., Burrus, C.A., Stone, F.T., and Ritger, A.J. see Lin, C.
Llaberia, J., Castaner, L., Garrido, J., and Vilamajo, E. see Castaner, L.
Lo, G.J.P., and Cuhaci, M. see Cuhaci, M.

Lo, P., Moulsley, T.J., Haddon, J., and Vilar, E. see Moulsley, T.J.
Lo, Y.T., and Richards, W.F. Perturbation approach to design of circularly polarised microstrip antennas 383
Loriou, B., Guena, J., and Sautereau, J.F. Optically frequency modulated GaAs MESFET oscillator 901
Ludowise, M.J., Dietze, W.T., and Cooper, C.B. see Dietze, W.T.
Lutz, P. Sensitivities of impedance scaled SC filters 24
Luukkala, M., Lehto, A., Jaarinen, J., Tiusanen, T., and Jokinen, M. see Lehto, A.
Luukkala, M., Lehto, A., Jokinen, M., Jaarinen, J., and Tiusanen, T. see Lehto, A.
Lyle, J.H., and Pitt, C.W. Vortex shedding fluid flowmeter using optical fibre sensor 244
Lyon, R.W., and Helszajn, J. see Helszajn, J.

M

McCormack, J.S. Remote optical measurement of temperature using luminescent materials 630
Macdonald, B.M., and Saunders, A.G. Coupling of an optical fibre to a substrate entry photodiode 832
MacDonald, R.I., Hara, E.H., and Hum, R.H. Fast photoconductive optoelectronic broadband switch with low control voltage 611
McGeehan, J.P., and Bateman, A. Subjective performance of amplitude companding in SSB mobile radio systems 859
Machida, S., Sakai, J., and Kimura, T. Polarisation conservation in single-mode fibres 494
Machida, S., Hara, E.H., Ikeda, M., Kanbe, H., and Kimura, T. see Hara, E.H.
Machida, S., Yamada, J.I., and Kimura, T. see Yamada, J.I.
Maciejko, R., Conradi, J., Straus, J., Few, I., Duck, G., Sinclair, W., Springthorpe, A.J., and Dyment, J.C. see Conradi, J.
McKee, D., Jack, M.A., Milne, A.D., and Warden, M. see Jack, M.A.
Maclean, T.S.M., and Saini, S.P.S. Efficiency and signal/noise ratio of short linear dipoles 492
Maclean, T.S.M., Saini, S.P.S., and Barboza, Z. Cross-spectral densities of array elements for folded dipole and loop antennas 749
McMahon, D.H., Nelson, A.R., and van de Vaart, H. see Nelson, A.R.
Maehara, H., Kushibiki, J., and Chubachi, N. see Kushibiki, J.
Mahmid, B., and Auchterlonie, L.J. Measurement of mutual scattering between spheres by use of microwave open resonator 977
Mak, S., and Harris, D.J. see Harris, D.J.
Makarios, A., and Tozer, T.C. False-lock avoidance scheme for Costas loops 490
Malkomes, M., and Quitmann, A. Microstrip circular-segment antenna 198
Mamihira, Y., Mochizuki, K., and Wakabayashi, H. see Mochizuki, K.
Mamouni, A., Van de Velde, J.C., and Leroy, Y. New correlation radiometer for microwave thermography 554
Manabe, T., Mitachi, S., and Shibata, S. see Mitachi, S.
Manabe, T., Shibata, S., Horiguchi, M., Jinguji, K., Mitachi, S., and Kanamori, T. see Shibata, S.
Manes, G.F., Tortoli, P., Gerli, D., and Atzeni, C. Analogue buffer memory for high speed rate conversion 58
Manning, J.S., and Olshansky, R. Carrier-induced index change in AlGaAs double-heterostructure lasers 506
Mansfeld, G.D., Gulyaev, Yu.V., and Orlova, G.A. see Gulyaev, Yu.V.
Mansfield, R.J., Barlow, A.J., Payne, D.N., and Hadley, M.R. see Barlow, A.J.
Mansfield, R.J., Conduit, A.J., Hartog, A.H., Hadley, M.R., Payre, D.N., Gold, M.P., and Tarbox, E.J. see Conduit, A.J.
Maradudin, A.A., and Glass, N.E. see Glass, N.E.
Marcuse, D., and Lin, C. see Lin, C.
Marshall, J., and Taylor, F. Computer-aided design of the Gray-Markel filter 662
Marshall, W.G., and Forsythe, W. Self-checking multiprocessor module for train control applications 408
Marten, P., Böhm, K., Petermann, K., Weidel, E., and Ulrich, R. see Böhm, K.
Martin, G.M., Berth, M., and Venger, C. see Berth, M.
Martinelli, G. Reverse ladder linear predictor 985
Masetti, G., Calzolari, P.U., Turchetti, C., and Severi, M. see Calzolari, P.U.
Materka, A., and Mizushina, S. Waveguide cavity FET oscillator 902
Matiowsky, M.A., Thomson, D.J., and Card, H.C. see Thomson, D.J.
Matricciani, E. Duration of rain-induced fades of signal from Sirio at 11.6 GHz 29
Matricciani, E. Rate of change of signal attenuation from Sirio at 11.6 GHz 139
Matson, J.L., and Winch, R.G. see Winch, R.G.
Matsui, T., and Nunoshita, M. Optical tee coupler for data bus system with single multimode fibres 304
Matsumoto, K., Hashizume, N., Yamada, H., Kojima, T., and Tomizawa, K. see Hashizume, N.
Matsumoto, K., Tomizawa, K., Hashizume, N., and Suzuki, F. see Tomizawa, K.
Matsumoto, M., Miyauchi, M., Toda, Y., Matsuno, K., and Tokumuru, Y. see Miyauchi, M.
Matsumura, H., Kanamori, M., and Furukawa, S. Characteristics of field-effect transistor using fluorinated amorphous-silicon (a-Si:F) 457
Matsumura, H., Katsuyama, T., and Suganuma, T. see Katsuyama, T.
Matsumura, M., Tsutsui, K., and Naruke, Y. Submicrometre lift-off line with T-shaped cross-sectional form 429
Matsuno, K., Miyauchi, M., Matsumoto, M., Toda, Y., and Tokumuru, Y. see Miyauchi, M.
Matsuoka, T., Takahei, K., Noguchi, Y., and Nagai, H. 1.5 μm region InP/GaInAsP buried heterostructure lasers on semi-insulating substrates 12
Matsushima, Y., Noda, Y., and Sakai, K. see Noda, Y.
Matsushima, Y., Utaka, K., Akiba, S., and Sakai, K. see Utaka, K.
Mattauch, R.J., and Archer, J.W. see Archer, J.W.
Mattauch, R.J., and Setzer, C.S. see Setzer, C.S.
Mauri, M., and Paraboni, A. Attenuation statistics at 11.6 GHz from satellite SIRIO after three years' activity in Italy 440
Mavor, J., and Rafat, H.A. see Rafat, H.A.
Mavor, J., Reekie, H.M., and Denyer, P.B. see Reekie, H.M.
Mawira, A. Microwave thermal emission of rain 162
May, E.J.P., and Mehdi, H.H. Low-noise state-space realisation of bandpass active filter 615
May, E.J.P., and Ahluwalia, H.S. see Ahluwalia, H.S.
Mazurczyk, V.J. Sensitivity of single mode buried heterostructure lasers to reflected power at 274 Mbit/s 143
Mazzone, A.M., and Rees, H.D. Transferred-electron oscillators at very high frequencies 539
Medeiros Filho, F.C., Jayasuriya, D.A.R., and Cole, R.S. Probability distribution of amplitude scintillations on a line-of-sight link at 36 GHz and 55 GHz 393
Medeiros Filho, F.C., Jayasuriya, D.A.R., and Cole, R.S. Spectral density of amplitude scintillations on a 55 GHz line of sight link 25
Mehdi, H.H., and May, E.J.P. see May, E.J.P.
Meierer, R., and Tsironis, C. see Tsironis, C.
Meignant, D., and Boccon-Gibod, D. Schottky drain microwave GaAs field effect transistors 107
Meissner, P., Lengyel, G., Patzak, E., and Zschauer, K.H. see Lengyel, G.
Melchior, H., Berger, H.P., Welter, R., Dill, A., and Guekos, G. see Berger, H.P.
Melloch, M.R., Gunshor, R.L., and Pierret, R.F. High frequency ZnO-SiO_2-Si surface acoustic wave convolvers 827
Mesbah, M., Peransin, J.M., and Groubert, E. see Peransin, J.M.
Meuleman, L.J., Van De Grijp, A., Koopman, J.C., Nicia, A.J.A., Roza, E., and Van Heuven, J.H.C. see Van De Grijp, A.
Mgombelo, H.R. Effect of length of each transmission line in Roy transformer on wideband matching 402
Mian, G.A., and Nainer, A.P. Computation of impulse response autocorrelation sequence of an AR model 347
Mickelson, A.R., and Eriksud, M. Role of modal distribution in determining power backscattered from fibres with diameter perturbations 658
Mickelson, A.R., Eriksrud, M., and Andersen-Gott, T. see Eriksrud, M.
Mikoshiba, N., and Sasaki, H. see Sasaki, H.
Miles, R.O., and Dandridge, A. see Dandridge, A.
Miles, R.O., Goldberg, L., Dandridge, A., Giallorenzi, T.G., and Weller, J.F. see Goldberg, L.
Millar, C.A. Direct method of determining equivalent-step-index profiles for monomode fibres 458
Miller, B.I., Furuya, K., Coldren, L.A., and Rentschler, J.A. see Furuya, K.
Milne, A.D., Jack, M.A., McKee, D., and Warden, M. see Jack, M.A.
Milson, R.F., Murray, R.J., Flinn, I., and Redwood, M. Ultra low bulk orientations of lithium niobate for SAW TV filters 89
Minakata, M., Yamada, S., and Noda, J. see Yamada, S.
Minowa, J., and Fujii, Y. see Fujii, Y.
Mirza, K.B., Karim, A.A.A., and Nagarajan, R. see Karim, A.A.A.
Misawa, M., Sakaki, H., Fujii, Y., and Hidaka, H. see Sakaki, H.
Mišić, V.B. Sensitivity evaluation for multiple feedback active filters 240
Mitachi, S., Miyashita, T., and Kanamori, T. Fluoride-glass-cladded optical fibres for mid-infra-red ray transmission 591, 672
Mitachi, S., Shibata, S., and Manabe, T. Teflon FEP-clad fluoride glass fibre 128
Mitachi, S., Shibata, S., Horiguchi, M., Jinguji, K., Kanamori, T., and Manabe, T. see Shibata, S.
Mitsunaga, Y., Katsuyama, Y., and Ishida, Y. Reliability assurance for long-length optical fibre based on proof testing 567
Miya, T., Hosaka, T., Okamoto, K., Sasaki, Y., and Edahiro, T. see Hosaka, T.
Miya, T., Tomaru, T., Kawachi, M., Yasu, M., and Edahiro, T. see Tomaru, T.
Miyajima, Y., Ishihara, K., Kakii, T., Toda, Y., and Tanaka, S. Long-length fibre containing high-strength splices 670
Miyashita, T., Mitachi, S., and Kanamori, T. see Mitachi, S.
Miyauchi, M., Matsumoto, M., Toda, Y., Matsuno, K., and Tokumuru, Y. New reinforcement for arc-fusion spliced fibre 907
Miyazawa, S., Yamazaki, H., and Honda, T. see Yamazaki, H.
Mizushina, S., and Materka, A. see Materka, A.
Mladenović, D.A., and Popović, R.S. see Popović, R.S.
Mochizuki, K., Mamihira, Y., and Wakabayashi, H. Dispersion measurements in single-mode fibres using sum-frequency mixing as a picosecond optical shutter 646
Mochizuki, K., Namihira, Y., and Wakabayashi, H. Polarisation mode dispersion measurements in long single mode fibres 153
Mochizuki, K., Namihira, Y., and Tatekura, K. see Namihira, Y.

Modone, E., and Roba, G. OH reduction in preforms by isotope exchange 815
Moeller, R.P., and Villarruel, C.A. see Villarruel, C.A.
Mohanty, A.K., and Chhotaray, R.K. see Chhotaray, R.K.
Monerie, M., and Lamouler, P. Birefringence measurement in twisted single-mode fibres 252 e334
Monerie, M., Jeunhomme, L., and Poignant, H. see Jeunhomme, L.
Morgan, D.P. General analysis of bilinear SAW convolvers 265
Morgan, G.B. Microstrip impatt-diode oscillator for 100 GHz 570
Morgan, G.B., and Obe, G.O. MIC impatt diode oscillator stabilised by temperature compensated dielectric resonator 72
Moriki, K., Iga, K., Uchida, M., Wakao, K., and Kunikane, T. 1.3 μm-wavelength mode controlled GaInAsP/InP etched laser 559
Morimitsu, T., Nomura, Y., Kitazawa, I., and Washio, M. see Nomura, Y.
Morishige, Y., Nakazawa, M., Tokuda, M., and Washio, K. see Nakazawa, M.
Morita, H., Koshiba, M., and Suzuki, M. see Koshiba, M.
Morkoç, H., Drummond, T.J., Keever, M., Kopp, W., Hess, K., Streetman, B.G., and Cho, A.Y. see Drummond, T.J.
Morkoç, H., Drummond, T.J., and Kopp, W. see Drummond, T.J.
Morkoc, H., Drummond, T.J., Su, S.L., Fischer, R., and Cho, A.Y. see Drummond, T.J.
Morkoc, H., Keever, M., Drummond, T., Hess, K., and Streetman, B.G. see Keever, M.
Morkoc, H., Witkowski, L.C., Drummond, T.J., Barnett, S.A., Cho, A.Y., and Greene, J.E. see Witkowski, L.C.
Moschytz, G.S. Simplified analysis of switched capacitor networks 975
Moschytz, G.S., von Grünigen, D., and Brugger, U.W. see von Grünigen, D.
Moschytz, G.S., Von Grünigen, D., Brugger, U.W., and Vollenweider, W. see Von Grünigen, D.
Mossman, P. Ceramic components for optical-fibre systems 451
Mosso, M.M., Podcameni, A., and Conrado, L.F.M. see Podcameni, A.
Motley, A.J. SSB versus FM at VHF for mobile radio telephony 852
Moule, D.M., Turley, S.E.H., Henshall, G.D., Greene, P.D., Knight, V.P., and Wheeler, S.A. see Turley, S.E.H.
Moulsley, T.J., Haddon, J., Lo, P., and Vilar, E. Measurement and modelling of the probability density function of amplitude scintillations of an X-band satellite down-link 625
Mozzi, R., Ayasli, Y., Vorhaus, J.L., and Reynolds, L. see Ayasli, Y.
Mukai, T., and Yamamoto, Y. Noise characteristics of semiconductor laser amplifiers 31
Mukai, T., Yamamoto, Y., and Saito, S. see Yamamoto, Y.
Mulawka, J.J. Switched capacitor analogue delays comprising unity gain buffer 276
Mulawka, J.J. Synthesis of single-amplifier switched-capacitor networks 510
Müller, G., and Temes, G.C. A pauper's algorithm for switched-capacitor circuit analysis 942
Murakami, Y., and Ikeda, M. Single-mode optical Y-branching circuit using deposited silica guides (DS guides) 411
Murata, H., and Nagasawa, S. see Nagasawa, S.
Murata, H., Satake, T., and Nagasawa, S. see Satake, T.
Murotani, T., Benson, T.M., Houston, P.A., and Robson, P.N. see Benson, T.M.
Murotani, T., Oomura, E., Higuchi, H., Hirano, R., Namizaki, H., and Susaki, W. see Oomura, E.
Murray, R.J., Milson, R.F., Flinn, I., and Redwood, M. see Milson, R.F.
Murrell, D., Devlin, W.J., Walling, R.H., Fiddyment, P.J., Hobbs, R.E., Spillett, R.E., and Steventon, A.G. see Devlin, W.J.

N

Nagai, H., Matsuoka, T., Takahei, K., and Noguchi, Y. see Matsuoka, T.
Nagai, H., Nakano, Y., Takahei, K., Noguchi, Y., Nawata, K., and Tokunaga, M. see Nakano, Y.
Nagai, H., Tokunaga, M., Nakano, Y., Takahei, K., Noguchi, Y., and Nawata, K. see Tokunaga, M.
Nagaraj, K., and Satyam, M. Multistage monostable multivibrator using load-coupled regenerative feedback 159
Nagaraj, K., and Satyam, M. Novel CMOS Schmitt trigger 693
Nagarajan, R., Karim, A.A.A., and Mirza, K.B. see Karim, A.A.A.
Nagasawa, S., and Murata, H. Optical fibre connectors using a fused and drawn multi-class-rod arrangement 268
Nagasawa, S., Satake, T., and Murata, H. see Satake, T.
Nagata, Y., Tachikawa, Y., Ohnishi, K., and Fujii, Y. see Tachikawa, Y.
Nagel, S.R., Ogawa, K., Chinnock, E.L., Gloge, D., Kaiser, P., and Jang, S.J. see Ogawa, K.
Nahory, R.E., Kaminow, I.P., Stulz, L.W., and Dewinter, J.C. see Kaminow, I.P.
Nainer, A.P., and Mian, G.A. see Mian, G.A.
Nakahara, M., Sakaguchi, S., and Kimura, T. see Sakaguchi, S.
Nakajima, K., Akita, K., Yamaguchi, A., and Takanohashi, T. see Akita, K.
Nakajima, K., Ito, K., Umeda, Y., Sugiyama, Y., Oshima, K., and Nunoshita, M. see Ito, K.
Nakajima, K., Shirai, T., Osaka, F., Yamasaki, S., and Kaneda, T. see Shirai, T.
Nakamura, K., Sasaki, H., and Shimizu, H. ZnO/SiO_2-diaphragm composite resonator on a silicon wafer 507
Nakanisi, T., Kamei, K., Kawasaki, H., Chigira, T., Kawabuchi, K., and Yoshimi, M. see Kamei, K.
Nakanisi, T., Shino, T., Yanagawa, S., Yamada, Y., Arai, K., Kamei, K., and Chigira, T. see Shino, T.
Nakano, H., and Yamauchi, J. see Yamauchi, J.
Nakano, Y., Takahei, K., Noguchi, Y., Nagai, H., Nawata, K., and Tokunaga, M. InGaAsP/InP BH lasers on p-type InP substrates 645
Nakano, Y., Takahei, K., Noguchi, Y., Suzuki, Y., Nagai, H., and Nawata, K. High power output InGaAsP/InP buried heterostructure lasers 782
Nakano, Y., Tokunaga, M., Takahei, K., Noguchi, Y., Nagai, H., and Nawata, K. see Tokunaga, M.
Nakashima, S., Akiya, M., and Ohwada, K. see Akiya, M.
Nakazawa, M., Horiguchi, T., Tokuda, M., and Uchida, N. Polarisation beat length measurement in a single-mode optical fibre by backward Rayleigh scattering 513
Nakazawa, M., Tokuda, M., Washio, K., and Morishige, Y. Marked extension of diagnosis length in optical time domain reflectometry using 1.32 μm YAG laser 783
Namihira, Y., Mochizuki, K., and Tatekura, K. Effects of thermal stress on group delay in jacketed single mode fibres 813
Namihira, Y., Mochizuki, K., and Wakabayashi, H. see Mochizuki, K.
Namizaki, H., Oomura, E., Higuchi, H., Hirano, R., Murotani, T., and Susaki, W. see Oomura, E.
Nara, S., Kurokawa, T., Yoshizawa, T., and Katayama, Y. see Kurokawa, T.
Naruke, Y., Matsumura, M., and Tsutsui, K. see Matsumura, M.
Nassau, K. Materials dispersion zero in glass mixtures 768
Nawata, K., Nakano, Y., Takahei, K., Noguchi, Y., Nagai, H., and Tokunaga, M. see Nakano, Y.
Nawata, K., Tokunaga, M., Nakano, Y., Takahei, K., Noguchi, Y., and Nagai, H. see Tokunaga, M.
Nedungadi, A. Accurate submicroampere controlled current source 320
Nelson, A.R., McMahon, D.H., and van de Vaart, H. Multiplexing system for fibre optic sensors using pulse compression techniques 263
Nelson, A.W., Westbrook, L.D., and Hatch, C.B. see Westbrook, L.D.
Nelson, S.R., and Tserng, H.Q. see Tserng, H.Q.
Neubert, E., Zimmer, G., Fielder, H., Hoeflinger, B., and Vogt, H. see Zimmer, G.
Neuman, V., Pitt, C.W., and Walpita, L.M. Guided-wave holographic grating beam expander - fabrication and performance 165
Neuman, V., Ameri, S., Ash, E.A., and Petts, C.R. see Ameri, S.
Neumann, E.-G. Reducing radiation loss of tilts in dielectric optical waveguides 369
Ng, W-H Use of error patterns in coded communication systems 241
Nicholas, R.J., Fung, S., Davison, A.M., and Stradling, R.A. see Fung, S.
Nicholson, H., and Fernando, K.V. see Fernando, K.V.
Nicia, A.J.A., Van De Grijp, A., Koopman, J.C., Meuleman, L.J., Roza, E., and Van Heuven, J.H.C. see Van De Grijp, A.
Nientiedt, W., Herbst, D., Hosticka, B.J., Höfflinger, B., Kleine, U., and Schweer, R. see Herbst, D.
Nikias, C.L., and Scott, P.D. see Scott, P.D.
Nilsson, O., Saito, S., and Yamamoto, Y. Oscillation frequency, linewidth reduction and frequency modulation characteristics for a diode laser with external grating feedback 589
Nishi, I., and Ando, Y. see Ando, Y.
Nishida, S., Gomi, J., and Yoneyama, T. see Gomi, J.
Nishida, S., and Yoneyama, T. see Yoneyama, T.
Nishida, S., Yoneyama, T., and Shimokoriyama, M. see Yoneyama, T.
Nishitani, Y., Ishikawa, H., Imai, H., Tanahashi, T., and Takusagawa, M. see Ishikawa, H.
Noda, J., Yamada, S., and Minakata, M. see Yamada, S.
Noda, Y., Sakai, K., and Matsushima, Y. High temperature CW operation of 1.5 μm InGaAsP/InP buffer-layer loaded planoconvex waveguide lasers 226
Noguchi, Y., Matsuoka, T., Takahei, K., and Nagai, H. see Matsuoka, T.
Noguchi, Y., Nakano, Y., Takahei, K., Nagai, H., Nawata, K., and Tokunaga, M. see Nakano, Y.
Noguchi, Y., Nakano, Y., Takahei, K., Suzuki, Y., Nagai, H., and Nawata, K. see Nakano, Y.
Noguchi, Y., Tokunaga, M., Nakano, Y., Takahei, K., Nagai, H., and Nawata, K. see Tokunaga, M.
Nomura, Y., Morimitsu, T., Kitazawa, I., and Washio, M. 1.3 μm, 400 Mbit/s undersea optical repeater sea trial 889
Nosu, K., and Watanabe, R. see Watanabe, R.
Nouailhat, A., Bremond, G., Guillot, G., and Cockayne, B. see Bremond, G.
Novak, S., Lazarus, M.J., Pantoja, F.R., and Somekh, M.G. see Lazarus, M.J.
Novak, S., Lazarus, M.J., Somekh, M.G., and Pantoja, F.R. see Lazarus, M.J.
Nunoshita, M., Ito, K., Umeda, Y., Sugiyama, Y., Nakajima, K., and Oshima, K. see Ito, K.
Nunoshita, M., and Matsui, T. see Matsui, T.
Nuzillat, G., Damay-Kavala, F., and Arnodo, C. see Damay-Kavala, F.
Nuzillat, G., Gloanec, M., and Jarry, J. see Gloanec, M.

O

O'Hara, C., Whatmore, R.W., Shorrocks, N.M., Ainger, F.W., and Young, I.M. see Whatmore, R.W.

O'Neill, C.J., Downs, T., and Khan, P.J. Formulation of electric-field integral equation without use of differential operator 598
O'Reilly, J., and Fahmy, M.M. Simple derivation of discrete minimal-order optimal estimator 908
O'Reilly, J.J. Equivalent-time signal acquisition and processing 911
Obe, G.O., and Morgan, G.B. see Morgan, G.B.
Ogawa, K., Chinnock, E.L., Gloge, D., Kaiser, P., Nagel, S.R., and Jang, S.J. System experiments using 1.3 μm LEDs 71
Ogawa, K., Lee, T.P., Burrus, C.A., Campbell, J.C., and Dentai, A.G. Wavelength division multiplexing experiment employing dual-wavelength LEDs and photodetectors 857
Ogawa, K., Lee, T.P., Burrus, C.A., and Dentai, A.G. see Lee, T.P.
Oh, S-H, Choi, Y-I, Kwon, Y-S, and Kim, C-K Etched profiles of SiO_2 layer 227
Ohkubo, A., Kushibiki, J., and Chubachi, N. see Kushibiki, J.
Ohmori, M., Ino, M., and Hirayama, M. see Ino, M.
Ohmori, Y., and Sasaki, Y. Characteristics of phase-matched sum-frequency light in optical fibres 678
Ohmori, Y., and Sasaki, Y. Sum-frequency light generation in optical fibres pumped by a Q-switched laser 781
Ohmori, Y., Sasaki, Y., and Edahiro, T. Fibre-length dependence of critical power for stimulated Raman scattering 593
Ohmori, Y., Sasaki, Y., Kawachi, M., and Edahiro, T. Single-pass Raman generation pumped by a mode-locked laser 594
Ohmori, Y., Sasaki, Y., Kawachi, M., and Edahiro, T. see Sasaki, Y.
Ohnishi, K., Tachikawa, Y., Fujii, Y., and Nagata, Y. see Tachikawa, Y.
Ohwada, K., Akiya, M., and Nakashima, S. see Akiya, M.
Oikawa, M., Iga, K., and Sanada, T. Distributed-index planar microlens array prepared from deep electromigration 452
Oka, H., Jeong, M.U., Shirafuji, J., Inuishi, Y., Yakushiji, H., and Harada, K. see Jeong, M.U.
Okada, M., Koshiba, M., and Suzuki, M. see Koshiba, M.
Okamoto, K., Hosaka, T., Miya, T., Sasaki, Y., and Edahiro, T. see Hosaka, T.
Okamoto, K., Hosaka, T., Sasaki, Y., and Edahiro, T. see Hosaka, T.
Okamura, M., and Kobayashi, T. Current drifting behaviour in InP MISFET with thermally oxidised InP/InP interface 941
Okoshi, T., Kikuchi, K., and Kawanishi, S. see Kikuchi, K.
Oliver, J.R., Fairman, R.D., Chen, R.T., and Yu, P.W. Undoped semi-insulating LEC GaAs: a model and a mechanism 839
Olsen, R.L., Hendry, A., Antar, Y.M.M., and Schlesak, J.J. see Hendry, A.
Olshansky, R., and Manning, J.S. see Manning, J.S.
Onodera, N., Ito, H., Gen-ei, K., and Inaba, H. see Ito, H.
Oomura, E., Higuchi, H., Hirano, R., Namizaki, H., Murotani, T., and Susaki, W. Transverse mode control in InGaAsP/InP buried crescent diode lasers 83
Opuchlik, J.M. Three-layer low frequency hybrid electrothermal filter 329
Orlova, G.A., Gulyaev, Yu.V., and Mansfeld, G.D. see Gulyaev, Yu.V.
Osaka, F., Shirai, T., Yamasaki, S., Nakajima, K., and Kaneda, T. see Shirai, T.
Oshima, K., Ito, K., Umeda, Y., Sugiyama, Y., Nakajima, K., and Nunoshita, M. see Ito, K.

P

Padmanabhan, K., and Somayajulu Sarma, G.S. Pseudoactive bridge for separation of R and C in a practical capacitive/conductive transducer 705
Paek, U.C., Krause, J.T., and Kurkjian, C.R. see Krause, J.T.
Pal, K. New inductance and capacitor floatation schemes using current conveyors 807 e936
Pal, K. Novel floating inductance using current conveyors 638
Pal, S.K., and King, R.A. Histogram equalisation with S and π functions in detecting X-ray edges 302
Palomera-Garcia, R. Voltage transfer function shift theorem (Comment) 721
Pandel, J., and Herbst, D. VIS-SC filters for higher clock frequency applications 504
Pantoja, F.R., Lazarus, M.J., Novak, S., and Somekh, M.G. see Lazarus, M.J.
Pantoja, F.R., Lazarus, M.J., and Somekh, M.G. see Lazarus, M.J.
Pantoja, F.R., Lazarus, M.J., Somekh, M.G., and Novak, S. see Lazarus, M.J.
Papachristou, C.A. Method for direct multiway branching in microprogram control 709
Papamichael, M., and Wilson, G. see Wilson, G.
Papiernik, A., Fray, C., and Andritsos, I. see Fray, C.
Papiernik, A., Fray, C., and Chandrasekhar, K. see Fray, C.
Papuchon, M., Kayoun, P., Puech, C., and Arditty, H.J. see Kayoun, P.
Paraboni, A., and Mauri, M. see Mauri, M.
Park, K.S., and King, R.J. see King, R.J.
Park, R.M., and Stanley, C.R. Characterisation of a deep electron trap in molecular-beam epitaxial InP 669
Parker, E.A., and Hamdy, S.M.A. Rings as elements for frequency selective surfaces 612
Parker, E.A., Hamdy, S.M.A., and Langley, R.J. Arrays of concentric rings as frequency selective surfaces 880
Parriaux, O., De Oliveira, A.D., and Wilson, M.G.F. see De Oliveira, A.D.
Parthasarathy, R., and John, S. Cauer continued fraction methods for model reduction 792
Partington, S., Beales, K.J., and France, P.W. see Beales, K.J.
Pask, C., and Ankiewicz, A. see Ankiewicz, A.
Pask, C., and Hussey, C.D. see Hussey, C.D.
Pask, C., and Sammut, R.A. see Sammut, R.A.
Patzak, E., Lengyel, G., Meissner, P., and Zschauer, K.H. see Lengyel, G.
Pauwels, H.J., and Burgelman, M. see Burgelman, M.
Payne, D.N., and Barlow, A.J. see Barlow, A.J.
Payne, D.N., Barlow, A.J., Hadley, M.R., and Mansfield, R.J. see Barlow, A.J.
Payne, D.N., Conduit, A.J., Hartog, A.H., and Gold, M.P. see Conduit, A.J.
Payne, D.N., Conduit, A.J., Hartog, A.H., Hadley, M.R., Gold, M.P., Mansfield, R.J., and Tarbox, E.J. see Conduit, A.J.
Payne, D.N., and Sasaki, I. see Sasaki, I.
Payne, R. Modal distribution of backscattered light in a step-index multimode fibre 568
Peaker, A.R., and Rockett, P.I. see Rockett, P.I.
Pearsall, T.P. Alloy scattering effects and calculated mobility in n-type $Ga_{0.47}$ $In_{0.53}$ As 169
Pearsall, T.P., and Takeda, Y. see Takeda, Y.
Pei, S-C., and Wu, J-L. Fast biased polynomial transforms for two-dimensional convolutions 547
Pengelly, R.S. Application of feedback techniques to the realisation of hybrid and monolithic broadband low-noise-and-power GaAs FET amplifiers 798
Peransin, J.M., Mesbah, M., and Groubert, E. Effects of heat treatment on noise spectrum in Au-InP Schottky barriers 757
Peri, D., and Chu, P.L. Measurement of refractive-index profile of optical-fibre preform by means of spatial filtering 371
Peri, D., and Chu, P.L. see Chu, P.L.
Petermann, K., Böhm, K., Marten, P., Weidel, E., and Ulrich, R. see Böhm, K.
Peters, K., Albrecht, W., Baack, C., Elze, G., Enning, B., Heydt, G., Walf, G., and Wenke, G. see Albrecht, W.
Peterson, I.R., and Halgren, R.C. see Halgren, R.C.
Petts, C.R., Ameri, S., Ash, E.A., and Neuman, V. see Ameri, S.
Petz, F.A., Archer, J.A., and Weidlich, H.P. see Archer, J.A.
Philippou, G.Y., Gupta, G.S., and Davies, J.B. Finite-element analysis of angularly dependent modes in a general RF periodic cavity 588
Pic, E., and Saguet, P. see Saguet, P.
Pierret, R.F., Melloch, M.R., and Gunshor, R.L. see Melloch, M.R.
Pinizzotto, R.F., Lam, H.W., Yuan, H.T., and Bellavance, D.W. see Lam, H.W.
Piqueras, J., and Calleja, E. see Calleja, E.
Pitt, C.W., and Lyle, J.H. see Lyle, J.H.
Pitt, C.W., Neuman, V., and Walpita, L.M. see Neuman, V.
Pleibel, W., Wagner, R.E., and Stolen, R.H. see Wagner, R.E.
Plotkin, E., Brown, J.L., Delansky, J., Roytman, L.M., and Swamy, M.N.S. see Brown, J.L.
Plumb, R.G., White, I.H., Aspin, G.J., and Carroll, J.E. see White, I.H.
Podcameni, A., and Bermudez, L.A. Stabilised FET oscillator with input dielectric resonator: large signal design 44
Podcameni, A., and Conrado, L.F. Broadbanding the quarter-wave transformer using two parallel stubs 372
Podcameni, A., Conrado, L.F.M., and Mosso, M.M. Unloaded quality factor measurement for MIC dielectric resonator applications 656
Poignant, H. Dispersive and scattering properties of a ZrF_4 based glass 973
Poignant, H., Le Mellot, J., and Bayon, J.F. Fluoride glasses for infra-red optical fibres 295
Poignant, H., Jeunhomme, L., and Monerie, M. see Jeunhomme, L.
Popović, R.S., and Mladenović, D.A. Low breakdown voltage Schottky diode as voltage regulator 214
Popovich, M.V., and Katić, O. New inverting integrator with improved high-frequency response 641
Porter, B. Design of error-actuated controllers for unknown multivariable plants 106
Potter, P.G. Reduction of crosstalk interference in local digital transmission 423
Prabhu, V.K. Cochannel interference immunity of high capacity QAM 680
Preston, K.R., Woollard, K.C., and Cameron, K.H. External cavity controlled single longitudinal mode laser transmitter module 931
Prokhorov, A.M., Andreev, A.T., Grundinin, A.B., Dianov, E.M., Guryanov, A.N., Devjatykh, G.G., Ignatjev, S.V., and Hopin, V.F. see Andreev, A.T.
Puech, C., Kayoun, P., Papuchon, M., and Arditty, H.J. see Kayoun, P.

Q

Quarmby, D.J., and Abdel Gadir, O.M. see Abdel Gadir, O.M.
Quitmann, A., and Malkomes, M. see Malkomes, M.

R

Radmanovich, M.Dj., and Rakovich, D.D. see Rakovich, D.D.
Rafat, H.A., and Mavor, J. Experimental validation of exact design of switched-capacitor ladder filters 275
Raghav, V.S., and Sharma, Y.K. see Sharma, Y.K.
Rahman, F., Shafai, L., and Bridges, E. Radiation characteristics of array of crescent slots fed through radial waveguide 314
Raju, V.R., and Fleming, J.W. see Fleming, J.W.

Rakovich, D.D., and Radmanovich, M.Dj. Least-squares magnitude filters with self-equalised delay characteristic 833
Ramsdale, P.A. Efficiency of loaded conical log-spiral antenna 735
Rao, S.N., and Borgaonkar, S.R. see Borgaonkar, S.R.
Rashleigh, S.C., and Taylor, H.F. Beamforming fibre optic sensor 138
Rashvand, H.F. Effective minimum free distance for convolutional codes 463
Rashvand, H.F., Borelli, W.C., and Farrell, P.G. see Borelli, W.C.
Rathore, T.S., and Singhi, B.M. Voltage transfer function shift theorem 175
Ratkovic, Z., Kajfez, D., and Smith, C.E. see Kaifez, D.
Razeghi, M., Hirtz, J.P., Hirtz, P., Larivain, J.P., Bondeau, R., De Cremoux, B., and Duchemin, J.P. Room temperature CW operation of GaInAsP/InP double-heterostructure diode lasers emitting at 1.23 μm grown by low-pressure metalorganic chemical vapour deposition 597
Razeghi, M., Hirtz, P., Larivain, J.P., Blondeau, R., de Cremoux, B., and Duchemin, J.P. 1.5 μm room-temperature pulsed operation of GaInAsP/InP double heterostructure grown by LP MOCVD 643
Razeghi, M., Hirtz, J.P., Larivain, J.P., Hersee, S., and Duchemin, J.P. see Hirtz, J.P.
Razzak, M.A., Liau, T.F., and Cuthbert, L.G. see Liau, T.F.
Readdie, J., Teng, T.C., Shiau, Y., De Ornellas, S., Wong, E., Chang, G., Ko, S., and Skinner, C. see Teng, T.C.
Redwood, M., Milson, R.F., Murray, R.J., and Flinn, I. see Milson, R.F.
Reekie, H.M., Mavor, J., and Denyer, P.B. Realisation of a switched-capacitor voltage wave pseudobandpass filter 795
Rees, H.D., and Beard, S.J. see Beard, S.J.
Rees, H.D., Brewitt-Taylor, C.R., and Gunton, D.J. see Brewitt-Taylor, C.R.
Rees, H.D., and Mazzone, A.M. see Mazzone, A.M.
Reeve, M.H., and Hornung, S. see Hornung, S.
Reif, R., and Knott, J.E. Low-temperature process to increase the grain size in polysilicon films 586
Rentschler, J.A., Furuya, K., Coldren, L.A., and Miller, B.I. see Furuya, K.
Reynolds, C.L., and Gaw, C.A. see Gaw, C.A.
Reynolds, L., Ayasli, Y., Vorhaus, J.L., and Mozzi, R. see Ayasli, Y.
Richards, W.F., and Lo, Y.T. see Lo, Y.T.
Ristić, Lj. Dj., Stojadinović, N.D., and Vidanović, B.V. see Stojadinović, N.D.
Ritger, A.J., Lin, C., Liu, P.L., Lee, T.P., Burrus, C.A., and Stone, F.T. see Lin, C.
Rizzoli, V., and Someda, C.G. Mutual influence among imperfect joints in multimode-fibre link 906
Roba, G., and Modone, E. see Modone, E.
Robson, P.N., Benson, T.M., Murotani, T., and Houston, P.A. see Benson, T.M.
Robson, P.N., Chand, N., and Houston, P.A. see Chand, N.
Rocchi, M., and Boccon-Gibod, D. GaAs binary frequency dividers for high speed applications up to 10 GHz 168
Rockett, P.I., and Peaker, A.R. Temperature dependence of peak heights in deep-level transient spectroscopy 838
Rodriguez-Vazquez, A., and Huertas, J.L. Novel active-compensated weighted summer e211
Rogers, D.A., D'Assunçao, A.G., and Giarola, A.J. see D'Assunçao, A.G.
Rokos, G.H.S. Voltage amplification in switched-capacitor networks (Comment and reply) 501
Rosen, A., Wu, C.P., Caulton, M., Gombar, A., and Stabile, P. Method of fabricating high-Q silicon varactor diodes 707
Rosiewicz, A., and Gannon, J.R. Effects of γ-irradiation on mid-IR transmitting glass 184
Ross, J.N. Measurement of magnetic field by polarisation optical time-domain reflectometry 596
Rossi, U., Calzavara, M., and Di Vita, P. see Calzavara, M.
Roulston, D.J., and Eltoukhy, A.A. see Eltoukhy, A.A.
Rouzeyre, M., Attal, J., Truong-Quang, N., Cambon, G., and Saurel, J.M. see Attal, J.
Roytman, L.M., Brown, J.L., Delansky, J., Plotkin, E., and Swamy, M.N.S. see Brown, J.L.
Roza, E., Van De Grijp, A., Koopman, J.C., Meuleman, L.J., Nicia, A.J.A., and Van Heuven, J.H.C. see Van De Grijp, A.
Runovc, F. Continuous model for gate-induced charge in short-channel MOSFETS 636
Rusch, W.V.T. Modified ring currents to treat axial caustics and slope diffraction in edge-diffraction analysis 801

S

Sabine, P.V.H., Irving, D.H., and Donaghy, F.A. see Irving, D.H.
Saguet, P., and Pic, E. Le maillage rectangulaire et le changement de maille dans la methode TLM en deux dimensions 277
Saillard, J., and Chassay, G. Determination of viewing aspect window of RCS diagram for recognition of isotropic linear target 173
Saillard, J., and Chassay, G. Recognition of isotropic plane target from RCS diagram 397
Saini, S.P.S., and Maclean, T.S.M. see Maclean, T.S.M.
Saini, S.P.S., Maclean, T.S.M., and Barboza, Z. see Maclean, T.S.M.
Saito, S., and Yamamoto, Y. Direct observation of Lorentzian lineshape of semiconductor laser and linewidth reduction with external grating feedback 325
Saito, S., Nilsson, O., and Yamamoto, Y. see Nilsson, O.
Saito, S., Yamamoto, Y., and Mukai, T. see Yamamoto, Y.
Saitto, A., de Vincenti, P., and Doro, G. see de Vincenti, P.
Sakaguchi, H., Seki, N., and Yamamoto, S. Power coupling from laser diodes into single-mode fibres with quadrangular pyramid-shaped hemiellipsoidal ends 425
Sakaguchi, S., Kimura, T., and Nakahara, M. New primary coating method for optical fibres 800
Sakaguchi, S., Kawachi, M., Tomaru, S., Yasu, M., Horiguchi, M., and Kimura, T. see Kawachi, M.
Sakai, J., Machida, S., and Kimura, T. see Machida, S.
Sakai, K., Noda, Y., and Matsushima, Y. see Noda, Y.
Sakai, K., Utaka, K., Akiba, S., and Matsushima, Y. see Utaka, K.
Sakai, S., and Tateno, H. Static characteristic of a new quasiparticle injected superconducting weak link device 501
Sakaki, H., Fujii, Y., Misawa, M., and Hidaka, H. New optical heterodyne detector with integrated diffraction grating 727
Salama, C.A.T., and Choi D.H. see Choi D.H.
Salehi, S.V. Algorithm for sampled data signal flow graphs (Comment) 710
Saluja, K.K., and Lidgey, F.J. Fault detection in combinational circuits using Gunn effect logic devices 222
Sammut, R.A., and Pask, C. Simplified numerical analysis of optical fibres and planar waveguides 105
Sanada, T., Oikawa, M., and Iga, K. see Oikawa, M.
Sanchez-Sinencio, E., Silva-Martinez, J., and Alba-Flores, R. Effects of finite operational amplifier gain-bandwidth product on a switched-capacitor amplifier 509
Sannomiya, T., Kushibiki, J., and Chubachi, N. see Kushibiki, J.
Sansonetti, P., Alard, F., and Jeunhomme, L. see Alard, F.
Sasaki, H., and Mikoshiba, N. Normalised power transmission in single mode optical branching waveguides 136
Sasaki, H., Nakamura, K., and Shimizu, H. see Nakamura, K.
Sasaki, I., and Payne, D.N. Simple visual inspection technique for optical fibre preforms 805
Sasaki, I., Francois, P.L., and Adams, M.J. see Francois, P.L.
Sasaki, Y., Ohmori, Y., Kawachi, M., and Edahiro, T. CW single-pass Raman generation in optical fibres 315
Sasaki, Y., Hosaka, T., Okamoto, K., and Edahiro, T. see Hosaka, T.
Sasaki, Y., Hosaka, T., Okamoto, K., Miya, T., and Edahiro, T. see Hosaka, T.
Sasaki, Y., and Ohmori, Y. see Ohmori, Y.
Sasaki, Y., Ohmori, Y., and Edahiro, T. see Ohmori, Y.
Sasaki, Y., Ohmori, Y., Kawachi, M., and Edahiro, T. see Ohmori, Y.
Sasaki, Y., Uesugi, N., and Ikeda, M. see Uesugi, N.
Satake, T., Nagasawa, S., and Murata, H. Low-loss multifibre connectors with plug-guide-grooved silicon 828
Satyam, M., and Nagaraj, K. see Nagaraj, K.
Saunders, A.G., and Macdonald, B.M. see Macdonald, B.M.
Saurel, J.M., Lassale, J., Shahab, G., Cambon, G., and Attal, J. Temperature-stable surface-acoustic-wave delay lines on gallium arsenide: second-order effects and sensitivities 344
Saurel, J.M., Attal, J., Truong-Quang, N., Cambon, G., and Rouzeyre, M. see Attal, J.
Sautereau, J.F., Loriou, B., and Guena, J. see Loriou, B.
Schieblich, C., and Braas, M. see Braas, M.
Schimpe, R., and Boeck, J. Modulation characteristic and intensity noise of CW superluminescent diodes 715
Schlaak, H.F., Von Helmolt, C.H., and Kersten, R.T. see Von Helmolt, C.H.
Schleher, D.C. MTI detection loss in clutter 82
Schlesak, J.J., Hendry, A., Antar, Y.M.M., and Olsen, R.L. see Hendry, A.
Schmitt, D., and Dorda, G. Interface states in MOSFETs due to hot-electron injection determined by the charge pumping technique 761
Schweer, R., Herbst, D., Hosticka, B.J., Höfflinger, B., Kleine, U., and Nientiedt, W. see Herbst, D.
Schweer, R., Kleine, U., Herbst, D., Hoeflinger, B., and Hosticka, B.J. see Kleine, U.
Scifres, D.R., Burnham, R.D., and Streifer, W. see Burnham, R.D.
Scifres, D.R., Streifer, W., and Burnham, R.D. see Streifer, W.
Scott, P.D., and Nikias, C.L. Forward covariance least-squares algorithm: a new method in AR spectral estimation 111
Scott, R.I.H., and Underhill, M.J. see Underhill, M.J.
Scovell, P.D. Pulsed thermal annealing of arsenic-implanted silicon 403
Scrivener, G., Stewart, C., and Stewart, W.J. see Stewart, C.
Sealy, B.J., Gill, S.S., Topham, P.J., Barrett, N.J., and Stephens, K.G. see Gill, S.S.
Seeds, A.J., and Forrest, J.R. Reduction of FM noise in impatt oscillators by optical illumination 865
Seidler, P. Mismatched filtering for coded aperture imaging with minimum sidelobes 96
Seifert, F.J., Kowatsch, M., Lafferl, J., and Ungersbäck, F. see Kowatsch, M.
Seikai, S., Kitayama, K., and Uchida, N. see Kitayama, K.
Seikai, S., Shibata, N., Katsuyama, Y., and Tateda, M. see Shibata, N.
Seikai, S., Shibata, N., Tateda, M., and Uchida, N. see Shibata, N.
Seki, K., Yanai, H., and Kamiya, T. Structure dependent axial mode stability in GaAlAs/GaAs injection lasers 288
Seki, N., Sakaguchi, H., and Yamamoto, S. see Sakaguchi, H.
Seki, S., and Hasegawa, H. Cross-tie slow-wave coplanar waveguide on semi-insulating GaAs substrates 940

Sekine, H., Goto, H., Yamada, T., and Suzuki, N. see Goto, H.
Setzer, C.S., and Mattauch, R.J. High-performance millimetrewave GaAs Schottky-barrier flip-chip diode 555
Severi, M., Calzolari, P.U., Masetti, G., and Turchetti, C. see Calzolari, P.U.
Shafai, L., Rahman, F., and Bridges, E. see Rahman, F.
Shahab, G., Saurel, J.M., Lassale, J., Cambon, G., and Attal, J. see Saurel, J.M.
Shamash, Y. Truncation method of reduction: a viable alternative 97
Shang, H-T. Chromatic dispersion measurement by white-light interferometry on metre-length single-mode optical fibres 603
Shankarnarayan, L., Bhattacharyya, A.B., and Kapur, N. see Bhattacharyya, A.B.
Shannon, J.M., and Gill, A. High current gain in monolithic hot-electron transistors 620
Sharma, Y.K., and Raghav, V.S. Exact J/V characteristic of an insulator diode with thermal free carriers in nonconstant mobility regime 355
Shaw, D.I., Anderson, A.P., and Bennett, J.C. Pseudostereoscopic holographic imaging system: a possible approach to high resolution underwater mapping 841
Shenderey, S.V., Grekhov, I.V., Kardo-Sysoev, A.F., and Kostina, L.S. see Grekhov, I.V.
Shiau, Y., Teng, T.C., De Ornellas, S., Readdie, J., Wong, E., Chang, G., Ko, S., and Skinner, C. see Teng, T.C.
Shibata, K., Yanagisawa, H., Torimura, Y., and Hatori, K. Method for improving microstrip coupler directivity 732
Shibata, N., Katsuyama, Y., Tateda, M., and Seikai, S. Thermal characteristic measurement in jacketed and unjacketed fibres by a spatial technique 345
Shibata, N., Shibata, S., and Edahiro, T. Refractive index dispersion of lightguide glasses at high temperature 310
Shibata, N., Tateda, M., Seikai, S., and Uchida, N. Wavelength dependence of polarisation mode dispersion in elliptical-core single-mode fibres 564
Shibata, S., Horiguchi, M., Jinguji, K., Mitachi, S., Kanamori, T., and Manabe, T. Prediction of loss minima in infra-red optical fibres 775
Shibata, S., Mitachi, S., and Manabe, T. see Mitachi, S.
Shibata, S., Shibata, N., and Edahiro, T. see Shibata, N.
Shim, Y., and Kim, J. Improved conditional runlength codes based on two composite states 748
Shimizu, H., Nakamura, K., and Sasaki, H. see Nakamura, K.
Shimokoriyama, M., Yoneyama, T., and Nishida, S. see Yoneyama, T.
Shino, T., Yanagawa, S., Yamada, Y., Arai, K., Kamei, K., Chigira, T., and Nakanisi, T. GaAs power MESFETs prepared by metalorganic chemical vapour deposition 738
Shirafuji, J., Jeong, M.U., Inuishi, Y., Yakushiji, H., Harada, K., and Oka, H. see Jeong, M.U.
Shirai, T., Osaka, F., Yamasaki, S., Nakajima, K., and Kaneda, T. 1.3 μm InP/InGaAsP planar avalanche photodiodes 826
Shorrocks, N.M., Whatmore, R.W., O'Hara, C., Ainger, F.W., and Young, I.M. see Whatmore, R.W.
Shurmer, H.V., and Ugwuagu, G.N.O. see Ugwuagu, G.N.O.
Sicuranza, G.L. 2-D digital filters using logarithmic number systems 854
Silva-Martinez, J., Sanchez-Sinencio, E., and Alba-Flores, R. see Sanchez-Sinencio, E.
Sinclair, W., Conradi, J., Maciejko, R., Straus, J., Few, I., Duck, G., Springthorpe, A.J., and Dyment, J.C. see Conradi, J.
Singh, V. Active *RC* single-resistance-controlled lossless floating inductance simulation using single grounded capacitor 920
Singh, V.K. Lossless inductor simulation: novel configurations using DVCCS (Comment and reply) 549
Singhi, B.M., and Rathore, T.S. see Rathore, T.S.
Sinha, N.K., and Lastman, G.J. Transformation algorithm for identification of continuous-time multivariable systems from discrete data 779
Sion, A. New method for direct G/T measurement using satellite signals 883
Skalicky, P. Coupling coefficient between dielectric resonator and microstrip line 99
Skinner, C., Teng, T.C., Shiau, Y., De Ornellas, S., Readdie, J., Wong, E., Chang, G., and Ko, S. see Teng, T.C.
Smith, C.E., Kajfez, D., and Ratkovic, Z. see Kaifez, D.
Smith, C.R., Irven, J., and Harrison, A.P. see Irven, J.
Smith, D.C., and Brambley, D.R. see Brambley, D.R.
Smith, J.G., Abbasi, S.A., Takleh, O., and Brunnschweiler, A. see Abbasi, S.A.
Smith, M.S., and De Prunele, G. Crosspolarisation for monopole antennas on limited ground planes 653
Smith, M.S., and Guo, Y.C. see Guo, Y.C.
Smith, R.G., Forrest, S.R., Williams, G.F., and Kim, O.K. see Forrest, S.R.
Sobhy, M.I., and Hosny, E.A. Generalised analysis of microwave networks including lumped elements 181
Soerensen, O.H., and Finnegan, T.F. see Finnegan, T.F.
Soliman, A.M. Novel phase compensated 3-port VCVS without matched operational amplifiers 68
Somayajulu Sarma, G.S., and Padmanabhan, K. see Padmanabhan, K.
Someda, C.G., and Rizzoli, V. see Rizzoli, V.
Somekh, M.G., Lazarus, M.J., Novak, S., and Pantoja, F.R. see Lazarus, M.J.
Somekh, M.G., Lazarus, M.J., and Pantoja, F.R. see Lazarus, M.J.
Somekh, M.G., Lazarus, M.J., Pantoja, F.R., and Novak, S. see Lazarus, M.J.
Sowers, J.J., Janis, B.A., Crowley, J.D., and Fank, F.B. InP Gunn oscillators in V-band 708
Spence, R., and Ilumoka, A. see Ilumoka, A.
Spillett, R.E., Devlin, W.J., Walling, R.H., Fiddyment, P.J., Hobbs, R.E., Murrell, D., and Steventon, A.G. see Devlin, W.J.
Springthorpe, A.J., Conradi, J., Maciejko, R., Straus, J., Few, I., Duck, G., Sinclair, W., and Dyment, J.C. see Conradi, J.
Stabile, P., Rosen, A., Wu, C.P., Caulton, M., and Gombar, A. see Rosen, A.
Stanley, C.R., and Park, R.M. see Park, R.M.
Stearn, A.E., and Wills, L.J. see Wills, L.J.
Stephens, K.G., Gill, S.S., Sealy, B.J., Topham, P.J., and Barrett, N.J. see Gill, S.S.
Steventon, A.G., Devlin, W.J., Walling, R.H., Fiddyment, P.J., Hobbs, R.E., Murrell, D., and Spillett, R.E. see Devlin, W.J.
Stewart, C., Stewart, W.J., and Scrivener, G. 500 MHz bandwidth guided wave L-band Bragg cell 971
Stewart, W.J., Stewart, C., and Scrivener, G. see Stewart, C.
Stojadinović, N.D., Ristić, Lj. Dj., and Vidanović, B.V. New technique for fabrication of low voltage Si zener diodes 130
Stolen, R.H., Wagner, R.E., and Pleibel, W. see Wagner, R.E.
Stone, F.T., Lin, C., Liu, P.L., Lee, T.P., Burrus, C.A., and Ritger, A.J. see Lin, C.
Stradling, R.A., Fung, S., Nicholas, R.J., and Davison, A.M. see Fung, S.
Straus, J., Conradi, J., Maciejko, R., Few, I., Duck, G., Sinclair, W., Springthorpe, A.J., and Dyment, J.C. see Conradi, J.
Streetman, B.G., Drummond, T.J., Keever, M., Kopp, W., Morkoç, H., Hess, K., and Cho, A.Y. see Drummond, T.J.
Streetman, B.G., Keever, M., Drummond, T., Hess, K., and Morkoc, H. see Keever, M.
Strege, K.E., Chandra, P., and Coldren, L.A. see Chandra, P.
Streifer, W., Scifres, D.R., and Burnham, R.D. Spontaneous emission factor of narrow-stripe gain-guided diode lasers 933
Streifer, W., Burnham, R.D., and Scifres, D.R. see Burnham, R.D.
Stromsmoe, K.A., and Filanovsky, I.M. see Filanovsky, I.M.
Stuart, R.A., Childs, P.A., and Eccleston, W. see Childs, P.A.
Stulz, L.W., Kaminow, I.P., Nahory, R.E., and Dewinter, J.C. see Kaminow, I.P.
Su, L.M., and Beneking, H. see Beneking, H.
Su, S.L., Drummond, T.J., Morkoc, H., Fischer, R., and Cho, A.Y. see Drummond, T.J.
Suematsu, Y., Abe, Y., Kishino, K., and Arai, S. see Abe, Y.
Suematsu, Y., Asada, M., Itoh, K., and Arai, S. see Asada, M.
Suematsu, Y., Kobayashi, K., Utaka, K., and Abe, Y. see Kobayashi, K.
Suematsu, Y., Koyama, F., Arai, A., and Kishino, K. see Koyama, F.
Suematsu, Y., Tanbun-ek, T., Arai, S., Koyama, F., Kishino, K., Yoshizawa, S., and Watanabe, T. see Tanbun-ek, T.
Suematsu, Y., Utaka, K., Kobayashi, K., Koyama, F., and Abe, Y. see Utaka, K.
Suganuma, T., Katsuyama, T., and Matsumura, H. see Katsuyama, T.
Sugawara, Y., Ishihara, K., Uchida, N., Ishida, Y., and Higashimoto, M. see Ishihara, K.
Sugawara, Y., Tanaka, M., Kobayashi, T., Inada, K., Tanaka, C., Katsuyama, Y., and Ishida, Y. see Tanaka, M.
Sugiura, T., Honjo, K., and Itoh, H. see Honjo, K.
Sugiyama, Y., Ito, K., Umeda, Y., Nakajima, K., Oshima, K., and Nunoshita, M. see Ito, K.
Sumi, M., and Imoto, K. see Imoto, K.
Sun, C.Y., Hwang, H.L., Lin, W.J., and Chang, H.J. see Hwang, H.L.
Sundara Murthy, K.M., and Cattermole, K.W. Power spectra of *M*-ary variable index CPFSK 888
Susa, N., Ando, H., and Kanbe, H. see Ando, H.
Susaki, W., Oomura, E., Higuchi, H., Hirano, R., Namizaki, H., and Murotani, T. see Oomura, E.
Sutcliffe, H., and Wong, C.Y. Operational amplifier with compensation pole as basis for active networks 529
Suzuki, F., Tomizawa, K., Hashizume, N., and Matsumoto, K. see Tomizawa, K.
Suzuki, M., and Koshiba, M. see Koshiba, M.
Suzuki, M., Koshiba, M., and Morita, H. see Koshiba, M.
Suzuki, M., Koshiba, M., and Okada, M. see Koshiba, M.
Suzuki, N., Goto, H., Sekine, H., and Yamada, T. see Goto, H.
Suzuki, Y., Nakano, Y., Takahei, K., Noguchi, Y., Nagai, H., and Nawata, K. see Nakano, Y.
Swamy, M.N.S., Brown, J.L., Delansky, J., Plotkin, E., and Roytman, L.M. see Brown, J.L.
Szajnowski, W.J. Estimation of time-varying co-ordinates of ion beams 489
Szulakiewicz, P. Influence of two-path propagation on MSK systems 893

T

Tachikawa, Y., Ohnishi, K., Fujii, Y., and Nagata, Y. Digital transmission experiment using LED and PIN-PD arrays 650
Tachikura, M. Fusion mass-splicing for optical fibres by discharge heating 694
Taira, K., Kasahara, J., Kato, Y., Dohsen, M., and Watanabe, N. see Kasahara, J.
Taira, K., Kato, Y., Dohsen, M., Kasahara, J., and Watanabe, N. see Kato, Y.
Takada, A., Kanda, Y., and Aoshima, R. see Kanda, Y.

Takada, T., Yokoyama, K., and Hirayama, M. GaAs MESFET circuit simulation model including negative differential mobility 132

Takahei, K., Matsuoka, T., Noguchi, Y., and Nagai, H. see Matsuoka, T.

Takahei, K., Nakano, Y., Noguchi, Y., Nagai, H., Nawata, K., and Tokunaga, M. see Nakano, Y.

Takahei, K., Nakano, Y., Noguchi, Y., Suzuki, Y., Nagai, H., and Nawata, K. see Nakano, Y.

Takahei, K., Tokunaga, M., Nakano, Y., Noguchi, Y., Nagai, H., and Nawata, K. see Tokunaga, M.

Takanohashi, T., Akita, K., Yamaguchi, A., and Nakajima, K. see Akita, K.

Takeda, Y., Littlejohn, M.A., and Hauser, J.R. Electron hall mobility calculations and alloy scattering in $Ga_{0.47}In_{0.53}As$ 377

Takeda, Y., Littlejohn, M.A., Hutchby, J.A., and Trew, R.J. Electron concentration and alloy composition dependence of Hall factor in $Ga_xIn_{1-x}As_yP_{1-y}$ 686

Takeda, Y., and Pearsall, T.P. Failure of Matthiessen's rule in the calculation of carrier mobility and alloy scattering effects in $Ga_{0.47}In_{0.53}As$ 573

Takleh, O., Abbasi, S.A., Brunnschweiler, A., and Smith, J.G. see Abbasi, S.A.

Takusagawa, M., Imai, H., Ishikawa, H., and Tanahashi, T. see Imai, H.

Takusagawa, M., Ishikawa, H., Imai, H., Tanahashi, T., and Nishitani, Y. see Ishikawa, H.

Tan, M., Auld, B.A., Ayter, S., and Hauden, D. see Auld, B.A.

Tanahashi, T., Imai, H., Ishikawa, H., and Takusagawa, M. see Imai, H.

Tanahashi, T., Ishikawa, H., Imai, H., Nishitani, Y., and Takusagawa, M. see Ishikawa, H.

Tanaka, C., Tanaka, M., Kobayashi, T., Sugawara, Y., Inada, K., Katsuyama, Y., and Ishida, Y. see Tanaka, M.

Tanaka, M., Kobayashi, T., Sugawara, Y., Inada, K., Tanaka, C., Katsuyama, Y., and Ishida, Y. Optical-cable properties under frozen water in a conduit and a suitable method for prevention of degradation 796

Tanaka, S., Miyajima, Y., Ishihara, K., Kakii, T., and Toda, Y. see Miyajima, Y.

Tanbun-ek, T., Arai, S., Koyama, F., Kishino, K., Yoshizawa, S., Watanabe, T., and Suematsu, Y. Low threshold current CW operation of GaInAsP/InP buried heterostructure distributed Bragg-reflector integrated-twin-guide laser emitting at 1.5-1.6 μm 967

Tang, H.S., and Hang, C.C. Practical deficiency of adaptive control design based on the characteristic variable 238

Tarbox, E.J., Conduit, A.J., Hartog, A.H., Hadley, M.R., Payne, D.N., Gold, M.P., and Mansfield, R.J. see Conduit, A.J.

Tateda, M., Shibata, N., Katsuyama, Y., and Seikai, S. see Shibata, N.

Tateda, M., Shibata, N., Seikai, S., and Uchida, N. see Shibata, N.

Tatekura, K., Namihira, Y., and Mochizuki, K. see Namihira, Y.

Tateno, H., and Sakai, S. see Sakai, S.

Tatham, H.L., and Adams, A.R. see Adams, A.R.

Tatham, H.L., Hayes, J.R., Adams, A.R., and Greene, P.D. see Hayes, J.R.

Taylor, D.J., Turner, B., Barr, W.P., and Cooper, D.P. see Turner, B.

Taylor, F., and Marshall, J. see Marshall, J.

Taylor, H.F., Goldberg, L., and Weller, J.F. see Goldberg, L.

Taylor, H.F., and Rashleigh, S.C. see Rashleigh, S.C.

Tell, R., Andersson, T., and Eng, S.T. 10 Gbit/s and gate using dual-gate GaAs MESFET 201

Temes, G.C., and Müller, G. see Müller, G.

Temkin, H., Chin, A.K., and Digiuseppe, M.A. $In_{0.53}Ga_{0.47}As$ contact layer for 1.3 μm light-emitting diodes 703

Teng, T.C., Shiau, Y., De Ornellas, S., Readdie, J., Wong, E., Chang, G., Ko, S., and Skinner, C. Improved performance of 4K SRAM by means of CW laser annealing 627

Teo, T.M., and Harris, D.J. see Harris, D.J.

Terui, H., Kobayashi, M., and Kasai, T. Total reflection optical waveguide switch 77

Thoma, K.A., and Bennett, R.J. see Bennett, R.J.

Thompson, G.H.B., and Brosson, P. see Brosson, P.

Thomson, D.J., Matiowsky, M.A., and Card, H.C. Stability of aluminium-polysilicon photovoltaic junctions 382

Thornton, R.L. Schottky-barrier elevation by ion implantation and implant segregation 485

Tiusanen, T., Lehto, A., Jaarinen, J., Jokinen, M., and Luukkala, M. see Lehto, A.

Tiusanen, T., Lehto, A., Jokinen, M., Jaarinen, J., and Luukkala, M. see Lehto, A.

Toda, Y., Miyajima, Y., Ishihara, K., Kakii, T., and Tanaka, S. see Miyajima, Y.

Toda, Y., Miyauchi, M., Matsumoto, M., Matsuno, K., and Tokumuru, Y. see Miyauchi, M.

Tokuda, M., Nakazawa, M., Horiguchi, T., and Uchida, N. see Nakazawa, M.

Tokuda, M., Nakazawa, M., Washio, K., and Morishige, Y. see Nakazawa, M.

Tokumuru, Y., Miyauchi, M., Matsumoto, M., Toda, Y., and Matsuno, K. see Miyauchi, M.

Tokunaga, M., Nakano, Y., Takahei, K., Noguchi, Y., Nagai, H., and Nawata, K. Effect of cavity length on 1.55 μm buried-heterostructure DH laser characteristics 234

Tokunaga, M., Nakano, Y., Takahei, K., Noguchi, Y., Nagai, H., and Nawata, K. see Nakano, Y.

Tomaru, S., Yasu, M., Kawachi, M., and Edahiro, T. VAD single mode fibre with 0.2 dB/km loss 92

Tomaru, S., Kawachi, M., Yasu, M., Horiguchi, M., Sakaguchi, S., and Kimura, T. see Kawachi, M.

Tomaru, T., Kawachi, M., Yasu, M., Miya, T., and Edahiro, T. VAD single-mode fibres with high Δn values 731

Tomassetti, G., Weinreb, S., and Wellington, K. Low-noise 10.7 GHz cooled GaAs FET amplifier 949

Tomimuro, H., and Kawano, K. see Kawano, K.

Tomizawa, K., Hashizume, N., Matsumoto, K., and Suzuki, F. Speed-power property of GaAs Schottky-barrier coupled Schottky-barrier gate FET logic 821 e936

Tomizawa, K., Hashizume, N., and Yamada, H. see Hashizume, N.

Tomizawa, K., Hashizume, N., Yamada, H., Kojima, T., and Matsumoto, K. see Hashizume, N.

Topham, P.J., Gill, S.S., Sealy, B.J., Barrett, N.J., and Stephens, K.G. see Gill, S.S.

Torimura, Y., Shibata, K., Yanagisawa, H., and Hatori, K. see Shibata, K.

Tortoli, P., Manes, G.F., Gerli, D., and Atzeni, C. see Manes, G.F.

Tozer, T.C., and Makarios, A. see Makarios, A.

Tran, D.C., and Koo, K.P. Stabilising single mode fibre couplers by using gel glass 187

Trew, R.J., Takeda, Y., Littlejohn, M.A., and Hutchby, J.A. see Takeda, Y.

Truong-Quang, N., Attal, J., Cambon, G., Saurel, J.M., and Rouzeyre, M. see Attal, J.

Trusty, G.L., Leslie, D.H., Dandridge, A., and Giallorenzi, T.G. see Leslie, D.H.

Tserng, H.Q., and Nelson, S.R. 5-18 GHz, 3 dB hybrid coupler 258

Tsibukis, T.D., and Kriezis, E.E. VVMOS power transistors: upper and lower bounds of the on-resistance 353

Tsironis, C. 12 GHz receiver with self-oscillating dual-gate MESFET mixer 617

Tsironis, C., and Meierer, R. Equivalent circuit of GaAs dual gate MESFETs 477

Tsividis, Y. Self-tuned filters 406 e512

Tsividis, Y.P. Method for signal processing with transfer function coefficients dependent only on timing (Comment) 147

Tsoi, A.C. Inverse Jury-Blanchard table and its applications to the inverse stability problem 830

Tsuji, T., Furutsuka, T., Katano, F., Higashisaka, A., and Kurumada, K. see Furutsuka, T.

Tsutsui, K., Matsumura, M., and Naruke, Y. see Matsumura, M.

Tubridy, G. S-band trapatt oscillator with reduced frequency-temperature dependence 579

Tuck, B., Brozel, M.R., and Foulkes, E.J. see Brozel, M.R.

Turchetti, C., Calzolari, P.U., Masetti, G., and Severi, M. see Calzolari, P.U.

Turley, S.E.H., Henshall, G.D., Greene, P.D., Knight, V.P., Moule, D.M., and Wheeler, S.A. Properties of inverted rib-waveguide lasers operating at 1.3 μm wavelength 868

Turner, B., Barr, W.P., Cooper, D.P., and Taylor, D.J. GaAs microwave power FET with polyimide overlay interconnection 185

Turski, Z., and Wahi, P.K. see Wahi, P.K.

Tveten, A.B., and Dandridge, A. see Dandridge, A.

Tveten, A.B., Dandridge, A., and Giallorenzi, T.G. see Dandridge, A.

Tzeng, C.F., Wrick, V.L., and Choyke, W.J. see Wrick, V.L.

U

Uchida, M., Moriki, K., Iga, K., Wakao, K., and Kunikane, T. see Moriki, K.

Uchida, N., Ishihara, K., Ishida, Y., Sugawara, Y., and Higashimoto, M. see Ishihara, K.

Uchida, N., Kitayama, K., and Seikai, S. see Kitayama, K.

Uchida, N., Nakazawa, M., Horiguchi, T., and Tokuda, M. see Nakazawa, M.

Uchida, N., Shibata, N., Tateda, M., and Seikai, S. see Shibata, N.

Uematsu, Y., and Kinoshita, J. see Kinoshita, J.

Ueno, F., and Inoue, T. see Inoue, T.

Uesugi, N., Ikeda, M., and Sasaki, Y. Maximum single frequency input power in a long optical fibre determined by stimulated Brillouin scattering 379

Ugwuagu, G.N.O., and Shurmer, H.V. Pin diodes in meander-line filters for multiplexing applications 702

Ulrich, R., Böhm, K., Marten, P., Petermann, K., and Weidel, E. see Böhm, K.

Umeda, Y., Ito, K., Sugiyama, Y., Nakajima, K., Oshima, K., and Nunoshita, M. see Ito, K.

Underhill, M.J., and Scott, R.I.H. Simple switching technique for fast PLL frequency synthesisers 405

Ungersbäck, F., Kowatsch, M., Lafferl, J., and Seifert, F.J. see Kowatsch, M.

Upton, S.A.J., Evans, B.G., and Holt, A.R. see Evans, B.G.

Ury, I., Bar-Chaim, N., Katz, J., and Yariv, A. see Bar-Chaim, N.

Utaka, K., Akiba, S., Sakai, K., and Matsushima, Y. Room-temperature CW operation of distributed-feedback buried-heterostructure InGaAsP/InP lasers emitting at 1.57 μm 961

Utaka, K., Kobayashi, K., Koyama, F., Abe, Y., and Suematsu, Y. Single-wavelength operation of 1.53 μm GaInAsP/InP buried-heterostructure integrated twin-guide laser with distributed Bragg reflector under direct modulation up to 1 GHz 368

Utaka, K., Kobayashi, K., Abe, Y., and Suematsu, Y. see Kobayashi, K.

V

Vaitiekunas, F., and Vyshniauskas, J. Differences of plasma formation and extraction in P^+NN^+ and N^+PP^+ silicon trapatt structures 822

Van Bladel, J. Radar echoes near a dielectric resonance 699

Van De Grijp, A., Koopman, J.C., Meuleman, L.J., Nicia, A.J.A., Roza, E., and Van Heuven, J.H.C. Novel electro-optical feedback technique for noise and distortion reduction in high-quality analogue optical transmission video signals 361

van de Vaart, H., Nelson, A.R., and McMahon, D.H. see Nelson, A.R.

Van de Velde, J.C., Mamouni, A., and Leroy, Y. see Mamouni, A.

van den Bosch, P.P.J., and Kuijk, L.A.M. Improved accuracy in calculating the characteristic polynomial 33

Van Gelder, I.A., Declerck, G.J., and Copeland, M.A. Programmable transversal filter 605

Van Heuven, J.H.C., Van De Grijp, A., Koopman, J.C., Meuleman, L.J., Nicia, A.J.A., and Roza, E. see Van De Grijp, A.

Vanhove, L. Simple algorithm to improve LPC vocoder speech with noisy input 149

Varanasi, P., and Dutta Roy, S.C. Some arithmetically symmetrical bandpass filters 26

Varga, A. Numerically stable algorithm for standard controllability form determination 74

Veelenturf, C.J., and Huijsing, J.H. see Huijsing, J.H.

Venger, C., Berth, M., and Martin, G.M. see Berth, M.

Verdú, S., and Herranze, J. Reduction of symbolic sparse matrices 1

Verlangieri, P.A., and D'Angelo, R. see D'Angelo, R.

Vidanović, B.V., Stojadinović, N.D., and Ristić, Lj. Dj. see Stojadinović, N.D.

Vilamajo, E., Castaner, L., Llaberia, J., and Garrido, J. see Castaner, L.

Vilar, E., Moulsley, T.J., Haddon, J., and Lo, P. see Moulsley, T.J.

Villarruel, C.A., and Moeller, R.P. Fused single mode fibre access couplers 243

Vittoz, E., Krummenacher, F., and Degrauwe, M. see Krummenacher, F.

Vogt, H., Zimmer, G., Fielder, H., Hoefflinger, B., and Neubert, E. see Zimmer, G.

Vollenweider, W., Von Grünigen, D., Brugger, U.W., and Moschytz, G.S. see Von Grünigen, D.

von Grünigen, D., Brugger, U.W., and Moschytz, G.S. Simple switched-capacitor decimation circuit 30

Von Grünigen, D., Brugger, U.W., Moschytz, G.S., and Vollenweider, W. Combined switched-capacitor FIR N-path filter using only grounded capacitors 788 e987

Von Helmolt, C.H. SAWDIF: Surface-acoustic-wave-driven interferometer 447

Von Helmolt, C.H., Schlaak, H.F., and Kersten, R.T. SAWDIC: Surface-acoustic-wave-driven directional coupler 446

Vorhaus, J.L., Ayasli, Y., Mozzi, R., and Reynolds, L. see Ayasli, Y.

Voshchenkov, A.M., and Herrmann, H. Submicron resolution deep UV photolithography 61

Vucetić, B. Evaluation of the Gallager adaptive convolutional codes on real channels 519

Vyshniauskas, J., and Vaitiekunas, F. see Vaitiekunas, F.

W

Wagner, R.E., Stolen, R.H., and Pleibel, W. Polarisation preservation in multimode fibres 177

Wahi, P.K., and Turski, Z. Dispersion in microstrip lines comprising layered dielectric media 785

Wakabayashi, H., Mochizuki, K., and Mamihira, Y. see Mochizuki, K.

Wakabayashi, H., Mochizuki, K., and Namihira, Y. see Mochizuki, K.

Wakao, K., Moriki, K., Iga, K., Uchida, M., and Kunikane, T. see Moriki, K.

Walf, G., Albrecht, W., Baack, C., Elze, G., Enning, B., Heydt, G., Peters, K., and Wenke, G. see Albrecht, W.

Walf, G., Baack, C., Elze, G., Enning, B., Heydt, G., and Wenke, G. see Baack, C.

Walling, R.H., Devlin, W.J., Fiddyment, P.J., Hobbs, R.E., Murrell, D., Spillett, R.E., and Steventon, A.G. see Devlin, W.J.

Walpita, L.M., Neuman, V., and Pitt, C.W. see Neuman, V.

Wang, M.-T., Young, J.H., and Brezovich, I.A. see Young, J.H.

Wang, W.I., Wood, C.E.C., and Eastman, L.F. Extremely high electron mobilities in modulation-doped GaAs -Al_x Ga_{1-x} As heterojunction superlattices 36

Ward, C.J. Delay reduction techniques in phase-locked loop amplifiers 253

Ward, K.D. Compound representation of high resolution sea clutter 561 e862

Ward, R.B. Precise delay/phase measurement using surface-acoustic waves and microprocessing 417

Warden, M., Jack, M.A., McKee, D., and Milne, A.D. see Jack, M.A.

Washio, K., Nakazawa, M., Tokuda, M., and Morishige, Y. see Nakazawa, M.

Washio, M., Nomura, Y., Morimitsu, T., and Kitazawa, I. see Nomura, Y.

Watanabe, N., Kasahara, J., Taira, K., Kato, Y., and Dohsen, M. see Kasahara, J.

Watanabe, N., Kato, Y., Dohsen, M., Kasahara, J., and Taira, K. see Kato, Y.

Watanabe, R., and Nosu, K. New 2-channel multiplexer using polarisation 133

Watanabe, T., Tanbun-ek, T., Arai, S., Koyama, F., Kishino, K., Yoshizawa, S., and Suematsu, Y. see Tanbun-ek, T.

Wedding, B., and Jager, D. Phase-matched second harmonic generation and parametric mixing on nonlinear transmission lines 76

Weeks, D.W., King, G.D.H., Bone, M.C., and Weiss, B.L. see King, G.D.H.

Wei, C.J., Klein, H.-J., and Beneking, H. Symmetrical MOTT barrier as a fast photodetector 688

Weidel, E., Böhm, K., Marten, P., Petermann, K., and Ulrich, R. see Böhm, K.

Weidlich, H.P., Archer, J.A., and Petz, F.A. see Archer, J.A.

Weinreb, S., Tomassetti, G., and Wellington, K. see Tomassetti, G.

Weiss, B.L., King, G.D.H., Bone, M.C., and Weeks, D.W. see King, G.D.H.

Welch, B.M., Lee, C.P., and Fleming, W.P. see Lee, C.P.

Weller, J.F., Goldberg, L., Dandridge, A., Miles, R.O., and Giallorenzi, T.G. see Goldberg, L.

Weller, J.F., Goldberg, L., and Taylor, H.F. see Goldberg, L.

Wellington, K., Tomassetti, G., and Weinreb, S. see Tomassetti, G.

Welter, R., Berger, H.P., Dill, A., Guekos, G., and Melchior, H. see Berger, H.P.

Wenke, G., Albrecht, W., Baack, C., Elze, G., Enning, B., Heydt, G., Peters, K., and Walf, G. see Albrecht, W.

Wenke, G., Baack, C., Elze, G., Enning, B., Heydt, G., and Walf, G. see Baack, C.

Wessels, B.W., and Inuishi, M. see Inuishi, M.

Westbrook, L.D., Nelson, A.W., and Hatch, C.B. Low threshold 1.55 μm InGaAsP lasers double clad with InGaAsP confining layers 952

Westphal, L.C., and Craig, P.C. see Craig, P.C.

Whatmore, R.W., Shorrocks, N.M., O'Hara, C., Ainger, F.W., and Young, I.M. Lithium tetraborate: a new temperature-compensated SAW substrate material 11

Wheeler, S.A., Turley, S.E.H., Henshall, G.D., Greene, P.D., Knight, V.P., and Moule, D.M. see Turley, S.E.H.

White, I.H., Aspin, G.J., Carroll, J.E., and Plumb, R.G. Picosecond pulse generation by lateral mode switching of (GaAl)As-heterostructure stripe lasers 541

Williams, D.F., and Cho, F.Y. Temperature variation of SAW power flow angle 164

Williams, G.E., Akiba, S., and Haus, H.A. see Akiba, S.

Williams, G.F., Forrest, S.R., Kim, O.K., and Smith, R.G. see Forrest, S.R.

Williams, N., and Birand, M.T. see Birand, M.T.

Williams, N., Birand, M.T., and Wright, P. see Birand, M.T.

Williams, N., and Inggs, M.R. see Inggs, M.R.

Williams, N., Inggs, M.R., and Birand, M.T. see Inggs, M.R.

Williamson, A.G. Equivalent circuit for radial-line/coaxial-line junction 300

Wills, L.J., and Stearn, A.E. Remote arbitrating of a resource 415

Wilson, B. Low distortion feedback voltage-current conversion technique 157

Wilson, B. Low-distortion high-output class B current convertor using error feedforward 461 e580 e722

Wilson, G., and Papamichael, M. Phase invariant delay approximations 294

Wilson, M.G.F., and Chung, P.S. see Chung, P.S.

Wilson, M.G.F., and Culshaw, B. see Culshaw, B.

Wilson, M.G.F., De Oliveira, A.D., and Parriaux, O. see De Oliveira, A.D.

Winch, R.G. Very broadband bipolar VCO 871

Winch, R.G., and Matson, J.L. Ku-band MIC bipolar VCO 296

Wiss, C. Predictive identification and control applied to zone melting process 629

Withers, M.J., and Davies, D.E.N. see Davies, D.E.N.

Witkowski, L.C., Drummond, T.J., Barnett, S.A., Morkoc, H., Cho, A.Y., and Greene, J.E. High mobility GaAs-Al_x Ga_{1-x} As single period modulation-doped heterojunctions 126

Wojnar, A. Interference of correlated radio signals with Rayleigh fading 608

Wong, C.Y., and Sutcliffe, H. see Sutcliffe, H.

Wong, E., Teng, T.C., Shiau, Y., De Ornellas, S., Readdie, J., Chang, G., Ko, S., and Skinner, C. see Teng, T.C.

Wood, C.E.C., Wang, W.I., and Eastman, L.F. see Wang, W.I.

Woollard, K.C., Preston, K.R., and Cameron, K.H. see Preston, K.R.

Wrick, V.L., Choyke, W.J., and Tzeng, C.F. Amorphisation and low temperature recrystallisation of InP 752

Wright, P., Birand, M.T., and Williams, N. see Birand, M.T.

Wu, C.P., Rosen, A., Caulton, M., Gombar, A., and Stabile, P. see Rosen, A.

Wu, J-L., and Pei, S-C. see Pei, S-C.

Y

Yakushiji, H., Jeong, M.U., Shirafuji, J., Inuishi, Y., Harada, K., and Oka, H. see Jeong, M.U.

Yamada, H., Hashizume, N., Kojima, T., Matsumoto, K., and Tomizawa, K. see Hashizume, N.

Yamada, H., Hashizume, N., and Tomizawa, K. see Hashizume, N.

Yamada, J.I., Machida, S., and Kimura, T. 2 Gbit/s optical transmission experiments at 1.3 μm with 44km single-mode fibre 479

Yamada, K., and Daikoku, K. Error performance of frequency-hopped DPSK system e673

Yamada, M., and Furuta, O. see Furuta, O.

Yamada, S., Minakata, M., and Noda, J. High speed 2-bit analogue-digital convertor using $LiNbO_3$ waveguide modulators 259

Yamada, T., Goto, H., Sekine, H., and Suzuki, N. see Goto, H.

Yamada, Y., Shino, T., Yanagawa, S., Arai, K., Kamei, K., Chigira, T., and Nakanisi, T. see Shino, T.
Yamaguchi, A., Akita, K., Nakajima, K., and Takanohashi, T. see Akita, K.
Yamaguchi, M., Hashimoto, K.Y., and Kogo, H. Effects of surface metallisation on SSBW and BGW propagation in quartz 602
Yamamoto, R., and Higashisaka, A. High speed GaAs digital integrated circuit with clock frequency of 4.1 GHz 291
Yamamoto, S., Sakaguchi, H., and Seki, N. see Sakaguchi, H.
Yamamoto, Y., and Fujisawa, K. Dielectric measurements in the X-band of mamma tissue from cattle 690
Yamamoto, Y., Mukai, T., and Saito, S. Quantum phase noise and linewidth of a semiconductor laser 327
Yamamoto, Y., Kobayashi, S., and Kimura, T. see Kobayashi, S.
Yamamoto, Y., and Mukai, T. see Mukai, T.
Yamamoto, Y., Nilsson, O., and Saito, S. see Nilsson, O.
Yamamoto, Y., and Saito, S. see Saito, S.
Yamanaka, K., and Enomoto, Y. Fringe pattern around surface crack observed with scanning acoustic microscope 638
Yamani, A., and Bennett, J.C. see Bennett, J.C.
Yamanouchi, K. Shear-wave transducer using ferroelectric medium with distributed polarisation 956
Yamasaki, S., Shirai, T., Osaka, F., Nakajima, K., and Kaneda, T. see Shirai, T.
Yamauchi, J., and Nakano, H. Axial ratio of balanced helical antenna and ellipticity measurement of incident wave 365
Yamazaki, H., Honda, T., and Miyazawa, S. Low-dose Si ion implantation into semi-insulating LEC GaAs 817
Yanagawa, S., Shino, T., Yamada, Y., Arai, K., Kamei, K., Chigira, T., and Nakanisi, T. see Shino, T.
Yanagisawa, H., Shibata, K., Torimura, Y., and Hatori, K. see Shibata, K.
Yanai, H., Seki, K., and Kamiya, T. see Seki, K.
Yang, J.J.J., Coleman, J.J., and Dapkus, P.D. see Coleman, J.J.
Yao, H.H., and Yip, G.L. see Yip, G.L.
Yariv, A., Bar-Chaim, N., Katz, J., and Ury, I. see Bar-Chaim, N.
Yariv, A., Yu, K.L., Koren, U., Chen, T.R., and Chen, P.C. see Yu, K.L.
Yassin, G., and Laine, D.C. Elliptical oscillation in molecular beam maser with disk resonator 156
Yasu, M., Kawachi, M., Tomaru, S., Horiguchi, M., Sakaguchi, S., and Kimura, T. see Kawachi, M.
Yasu, M., Tomaru, S., Kawachi, M., and Edahiro, T. see Tomaru, S.
Yasu, M., Tomaru, T., Kawachi, M., Miya, T., and Edahiro, T. see Tomaru, T.
Yata, A., and Ikuno, H. Cutoff frequencies of W-type fibre with polynomial profile core 9 e432
Yata, A., and Ikuno, H. Guides modes of a parabolic-core slab waveguide 115
Yeung, K.S. Application of Routh's criterion to test for positive real functions 375
Yeung, K.S. Stability of reduced model obtained by truncation 374
Ying, R.S., Chang, K., Kung, J.K., Asher, P.G., and Hayashibara, G.M. see Chang, K.
Yip, G.L., and Yao, H.H. Numerical study of inhomogeneous optical waveguide problems using predictor-corrector method 229
Yokoyama, K., Takada, T., and Hirayama, M. see Takada, T.
Yoneyama, T., and Nishida, S. Approximate solution for step discontinuity in dielectric slab waveguide 151
Yoneyama, T., Shimokoriyama, M., and Nishida, S. Lens design for surface wave applications 210
Yoneyama, T., Gomi, J., and Nishida, S. see Gomi, J.
Yoshimi, M., Kamei, K., Kawasaki, H., Chigira, T., Nakanisi, T., and Kawabuchi, K. see Kamei, K.
Yoshizawa, S., Tanbun-ek, T., Arai, S., Koyama, F., Kishino, K., Watanabe, T., and Suematsu, Y. see Tanbun-ek, T.
Yoshizawa, T., Kurokawa, T., Nara, S., and Katayama, Y. see Kurokawa, T.
Young, I.M., Whatmore, R.W., Shorrocks, N.M., O'Hara, C., and Ainger, F.W. see Whatmore, R.W.
Young, J.H., Wang, M.-T., and Brezovich, I.A. Frequency/depth-penetration considerations in hyperthermia by magnetically induced currents e674
Young, W.C., and Curtis, L. Cascaded multipole switches for single-mode and multimode optical fibres 571
Yu, K.L., Koren, U., Chen, T.R., Chen, P.C., and Yariv, A. Groove GaInAsP laser on semi-insulating InP 790 e936
Yu, P.W., Oliver, J.R., Fairman, R.D., and Chen, R.T. see Oliver, J.R.
Yuan, H.T., Lam, H.W., Pinizzotto, R.F., and Bellavance, D.W. see Lam, H.W.

Z

Zi-Hua, W., and Hung-Chia, H. see Hung-Chia, H.
Zimmer, G., Fielder, H., Hoefflinger, B., Neubert, E., and Vogt, H. Performance of a scaled Si gate n-well CMOS technology 666
Zschauer, K.H., Lengyel, G., Meissner, P., and Patzak, E. see Lengyel, G.

Subject index

ACOUSTO-OPTICS

500 MHz bandwidth guided wave L-band Bragg cell. C.Stewart, W.J.Stewart and G.Scrivener 971
Acoustic properties of evaporated chalcogenide glass films. J.Kushibiki, H.Maehara and N.Chubachi 322 e482
Fibre-optic spectrophone. D.H.Leslie, G.L.Trusty, A.Dandridge and T.G.Giallorenzi 581
Filter detection of phase-modulated laser probe signals. B.A.Auld, S.Ayter, M.Tan and D.Hauden 661
Fringe pattern around surface crack observed with scanning acoustic microscope. K.Yamanaka and Y.Enomoto 638
Linearly focused acoustic beams for acoustic microscopy. J.Kushibiki, A.Ohkubo and N.Chubachi 520
Magnitude and phase in thermal wave imaging. A.Lehto, J.Jaarinen, T.Tiusanen, M.Jokinen and M.Luukkala 364
Marked extension of diagnosis length in optical time domain reflectometry using 1.32 μm YAG laser. M.Nakazawa, M.Tokuda, K.Washio and Y.Morishige 783
New SSBW mode in GaAs. J.Henaff, M.Feldmann, M.Carel and R.Dubois 427
Photo-displacement imaging. S.Ameri, E.A.Ash, V.Neuman and C.R.Petts 337

ANTENNAS

Arrays of concentric rings as frequency selective surfaces. E.A.Parker, S.M.A.Hamdy and R.J.Langley 880
Axial ratio of balanced helical antenna and ellipticity measurement of incident wave. J.Yamauchi and H.Nakano 365
Bird-proof feed-horn windows for microwave radio system antennas. W.S.Davies, G.W.Lipback and P.R.Copeland 777
Cross-spectral densities of array elements for folded dipole and loop antennas. T.S.M.Maclean, S.P.S.Saini and Z.Barboza 749
Crosspolarisation for monopole antennas on limited ground planes. M.S.Smith and G.De Prunele 653
Dipoles of finite length above stratified planar structures. V.Hansen 982
Effect of field amplitude taper on measured antenna gain and sidelobes. R.C.Hansen 260
Efficiency and signal/noise ratio of short linear dipoles. T.S.M.Maclean and S.P.S.Saini 492
Efficiency of loaded conical log-spiral antenna. P.A.Ramsdale 735
Experimental millimetric array using dielectric radiators fed by means of dielectric waveguide. M.T.Birand and R.V.Gelsthorpe 633
Flat short-circuited strip of one wavelength width and acting at quarter-wave resonance. G.Dubost 891
Investigation of crosspolarisation in offset Cassegrain antennas. T.S.Bird 585
Microstrip circular-segment antenna. M.Malkomes and A.Quitmann 198
Modified ring currents to treat axial caustics and slope diffraction in edge-diffraction analysis. W.V.T.Rusch 801
New approach to compact measurements on reflector antennas. D.E.N.Davies and M.J.Withers 960
New technique to improve antenna measurements in the presence of site reflections. D.R.Hill 257 e334
Nulling performance of null-steering arrays with digital phase-only weights. F.Ananasso 255
Optimum directivity of elliptic loop antennas. D.K.Cheng and C.H.Liang 736
Perturbation approach to design of circularly polarised microstrip antennas. Y.T.Lo and W.F.Richards 383
Phase weighting for linear antenna arrays. Y.C.Guo and M.S.Smith 121
Planar antennas on a dielectric surface. C.R.Brewitt-Taylor, D.J.Gunton and H.D.Rees 729
Quarterwave microstrip antenna on a ferrimagnetic substrate. N.Das and J.S.Chatterjee 441
Radiation characteristics of array of crescent slots fed through radial waveguide. F.Rahman, L.Shafai and E.Bridges 314
Reconstruction of bidimensional electromagnetic field by unidimensional sampling technique. P.de Vincenti, G.Doro and A.Saitto 324
Short- or open-circuited dipole parallel to perfect reflector plane and embedded in substrate and acting at resonance. G.Dubost 914

BIOMEDICAL ELECTRONICS

Blood compatibility of components and materials in silicon integrated circuits. Y.Kanda, R.Aoshima and A.Takada 558
Dielectric measurements in the X-band of mamma tissue from cattle. Y.Yamamoto and K.Fujisawa 690
Dielectric properties of blood plasma. S.C.Kashyap 713

CIRCUIT THEORY AND DESIGN

A pauper's algorithm for switched-capacitor circuit analysis. G.Müller and G.C.Temes 942
Accurate submicroampere controlled current source. A.Nedungadi 320
Active compensation of op-amp inverting amplifier using NIC. N.Boutin 978
Active *RC* single-resistance-controlled lossless floating inductance simulation using single grounded capacitor. V.Singh 920
Algorithm for finding the common spanning trees of two graphs. J.B.Grimbleby 470
Broadbanding the quarter-wave transformer using two parallel stubs. A.Podcameni and L.F.Conrado 372
Class AB CMOS amplifier for micropower SC filters. F.Krummenacher, E.Vittoz and M.Degrauwe 433
Combined switched-capacitor FIR N-path filter using only grounded capacitors. D.Von Grünigen, U.W.Brugger, G.S.Moschytz and W.Vollenweider 788 e987
Convertor of optimal capacitance for nonsinusoidal systems compensation to DC voltage. L.S.Czarnecki 426
Coupling of an optical fibre to a substrate entry photodiode. B.M.Macdonald and A.G.Saunders 832
Current-voltage conveyor. I.M.Filanovsky and K.A.Stromsmoe 129 e316
Design of twin-T single amplifier building block with prescribed values of capacitors and minimum gain-sensitivity product. M.Biey 249 e358
Design technique for low-current generators. R.W.J.Barker and B.L.Hart 271
Economic choice of component tolerances. A.Ilumoka and R.Spence 979
Effect of direct current on spuriously generated third harmonics. H.S.Ahluwalia and E.J.P.May 851
Effect of length of each transmission line in Roy transformer on wideband matching. H.R.Mgombelo 402
Effects of finite operational amplifier gain-bandwidth product on a switched-capacitor amplifier. E.Sanchez-Sinencio, J.Silva-Martinez and R.Alba-Flores 509
Experimental validation of exact design of switched-capacitor ladder filters. H.A.Rafat and J.Mavor 275
Generalised analysis of microwave networks including lumped elements. M.I.Sobhy and E.A.Hosny 181
High voltage gain CMOS OTA for micropower SC filters. F.Krummenacher 160
Lossless inductor simulation: novel configurations using DVCCS (Comment and reply). V.K.Singh 549
Low distortion feedback voltage-current conversion technique. B.Wilson 157
Low-distortion high-output class B current convertor using error feedforward. B.Wilson 461 e580 e722
Method for signal processing with transfer function coefficients dependent only on timing (Comment). Y.P.Tsividis 147
Monolithic GaAs travelling-wave amplifier. Y.Ayasli, J.L.Vorhaus, R.Mozzi and L.Reynolds 413
New inductance and capacitor floatation schemes using current conveyors. K.Pal 807 e936
New switched capacitor ladder filter with reduced number of amplifiers. T.Inoue and F.Ueno 209
Nonperiodic sampling and identifiability. M.De La Sen and S.Dormido 922
Novel active-compensated weighted summer. A.Rodriguez-Vazquez and J.L.Huertas e211
Novel floating inductance using current conveyors. K.Pal 638
Novel phase compensated 3-port VCVS without matched operational amplifiers. A.M.Soliman 68
Numerical simulation of solar cell open circuit voltage decay. I..Castaner, J.Llaberia, J.Garrido and E.Vilamajo 745
Offset voltage, CMRR and PSRR of a long-tailed pair: an integrated approach. B.L.Hart 537
Operational amplifier with compensation pole as basis for active networks. H.Sutcliffe and C.Y.Wong 529
Parasitic compensated switched capacitor circuits. P.E.Fleischer, A.Ganesan and K.R.Laker 929
Performance of Ruthroff transformer with reactive loads. R.T.Irish 913
Positive impedance convertor suitable for high-frequency application. P.Horn 474
Pseudoactive bridge for separation of R and C in a practical capacitive/conductive transducer. K.Padmanabhan and G.S.Somayajulu Sarma 705
Real-time programmable unit-element SC filter for LPC synthesis. U.Kleine, D.Herbst, B.Hoefflinger, B.J.Hosticka and R.Schweer 600
Reduction of symbolic sparse matrices. S.Verdú and J.Herranze 1
Reverse ladder linear predictor. G.Martinelli 985
Schmitt trigger circuit with picosecond risetimes. L.Bickers 695
Sensitivity evaluation for multiple feedback active filters. V.B.Mišić 240
Simple switched-capacitor decimation circuit. D.von Grünigen, U.W.Brugger and G.S.Moschytz 30
Simplified analysis of switched capacitor networks. G.S.Moschytz 975
Strays-insensitive switched capacitor biquads with reduced number of capacitors. P.Gillingham 171 e246
Symbolic analysis of circuits containing active elements. J.B.Grimbleby 754

Synthesis of single-amplifier switched-capacitor networks. J.J.Mulawka 510
Very broadband bipolar VCO. R.G.Winch 871
VIS-SC filters for higher clock frequency applications. J.Pandel and D.Herbst 504
Voltage amplification in switched-capacitor networks. I.Cederbaum 194
Voltage amplification in switched-capacitor networks (Comment and reply). G.H.S.Rokos 501
Voltage transfer function shift theorem. T.S.Rathore and B.M.Singhi 175
Voltage transfer function shift theorem (Comment). R.Palomera-Garcia 721

CODES AND CODING

Convolutional codes for multi-level modems. W.C.Borelli, H.F.Rashvand and P.G.Farrell 331
Effective minimum free distance for convolutional codes. H.F.Rashvand 463
Encoding of analogue signals using surface-acoustic-wave chirp filters. M.Kowatsch, J.Lafferl, F.Ungersbäck and F.J.Seifert 475
Evaluation of the Gallager adaptive convolutional codes on real channels. B.Vučetić 519
Impact of entropic coding on the time delays associated with time-encoded speech (TES) systems. R.A.King and J.Holbeche 394
Improved conditional runlength codes based on two composite states. Y.Shim and J.Kim 748
Multilevel double error correcting codes. V.C.Da Rocha 45
Optical orthogonal pulse compression codes by hopping. P.Healey 970

COMPUTER-AIDED DESIGN

Computer-aided design of the Gray-Markel filter. J.Marshall and F.Taylor 662
Design of two-dimensional recursive digital filters to a specified stability margin. G.Crebbin and J.Attikiouzel 765
Mismatch losses in multiply tapped SAW convolvers. E.L.Adler 866
Reduction of symbolic sparse matrices. S.Verdú and J.Herranze 1

COMPUTERS

Encryption with keyed random permutations. F.Ayoub 583 e771
Fault detection in combinational circuits using Gunn effect logic devices. K.K.Saluja and F.J.Lidgey 222
Improved performance of 4K SRAM by means of CW laser annealing. T.C.Teng, Y.Shiau, S.De Ornellas, J.Readdie, E.Wong, G.Chang, S.Ko and C.Skinner 627
Method for direct multiway branching in microprogram control. C.A.Papachristou 709
Remote arbitrating of a resource. L.J.Wills and A.E.Stearn 415
Self-checking multiprocessor module for train control applications. W.G.Marshall and W.Forsythe 408

CONTROL THEORY

Algorithm for sampled data signal flow graphs (Comment). S.V.Salehi 710
Degree of controllability due to individual inputs. K.V.Fernando and H.Nicholson 330
Design of error-actuated controllers for unknown multivariable plants. B.Porter 106
Improved accuracy in calculating the characteristic polynomial. P.P.J.van den Bosch and L.A.M.Kuijk 33
Inverse Jury-Blanchard table and its applications to the inverse stability problem. A.C.Tsoi 830
Minimum trajectory sensitivity of a linear system. V.Guruprasada Rau 563
Numerically stable algorithm for standard controllability form determination. A.Varga 74
Observer design for differential difference systems. R.K.Chhotaray and A.K.Mohanty 19
Optimisation of a graded-index fibre over a wavelength range. J.Arnaud and A.M.Desage 339
Practical deficiency of adaptive control design based on the characteristic variable. H.S.Tang and C.C.Hang 238
Predictive identification and control applied to zone melting process. C.Wiss 629
Simple derivation of discrete minimal-order optimal estimator. J.O'Reilly and M.M.Fahmy 908
Simple switching technique for fast PLL frequency synthesisers. M.J.Underhill and R.I.H.Scott 405
Solution of Lyapunov equation for the state matrix. K.V.Fernando and H.Nicholson 204
Truncation method of reduction: a viable alternative. Y.Shamash 97

DATA TRANSMISSION

Binary data transmission through TV channels by equivalent luminance signal. J.Isailović 233
Extraction of decision level for envelope-detected amplitude-shift keying. W.Hodgkiss 881
Lower bound on one shot error probability. D.B.Hoang and G.C.Goodwin 261
TSRMA-A communication protocol for data transmission by radio channels. A.Abramovitz and Y.Bar-Ness 526

DIELECTRICS AND DIELECTRIC DEVICES

Dielectric measurements in the X-band of mamma tissue from cattle. Y.Yamamoto and K.Fujisawa 690
Dielectric properties of blood plasma. S.C.Kashyap 713
Dispersion in microstrip lines comprising layered dielectric media. P.K.Wahi and Z.Turski 785
Planar antennas on a dielectric surface. C.R.Brewitt-Taylor, D.J.Gunton and H.D.Rees 729
Reducing radiation loss of tilts in dielectric optical waveguides. E.-G.Neumann 369
Thermo-optic effect in $LiNbO_3$ for light deflection and switching. M.Haruna and J.Koyama 842
Unloaded quality factor measurement for MIC dielectric resonator applications. A.Podcameni, L.F.M.Conrado and M.M.Mosso 656

DIGITAL CIRCUITS

10 Gbit/s and gate using dual-gate GaAs MESFET. R.Tell, T.Andersson and S.T.Eng 201
Digital frequency substractor and/or adder based on hybrid PLL. P.M.Djurdje 28
GaAs binary frequency dividers for high speed applications up to 10 GHz. M.Rocchi and D.Boccon-Gibod 168
Reduction of crosstalk interference in local digital transmission. P.G.Potter 423
SSB-FDM using complementary comb filters. Y.Hirata 614

ELECTROMAGNETIC WAVES

Arrays of concentric rings as frequency selective surfaces. E.A.Parker, S.M.A.Hamdy and R.J.Langley 880
Dipoles of finite length above stratified planar structures. V.Hansen 982
Measurement of mutual scattering between spheres by use of microwave open resonator. B.Mahmid and L.J.Auchterlonie 977
Modified ring currents to treat axial caustics and slope diffraction in edge-diffraction analysis. W.V.T.Rusch 801
Probability distribution of amplitude scintillations on a line-of-sight link at 36 GHz and 55 GHz. F.C.Medeiros Filho, D.A.R.Jayasuriya and R.S.Cole 393
Rings as elements for frequency selective surfaces. E.A.Parker and S.M.A.Hamdy 612
Thermal noise emission of a lossy material for a TEM propagation. J.J.Fabre and Y.Leroy 376

ELECTRON DEVICES

Efficient fundamental frequency oscillation from millimetre-wave indium phosphide n^+-n-n^+ transferred electron oscillators. I.G.Eddison, I.Davies, P.L.Giles and D.M.Brookbanks 758
Harmonic operation of GaAs millimetre wave transferred electron oscillators. W.H.Haydl 825
High current gain in monolithic hot-electron transistors. J.M.Shannon and A.Gill 620
Hot electron effects in Schottky barrier mixers at high frequencies. S.J.Beard and H.D.Rees 811
Low-noise two-dimensional electron gas FET. M.Laviron, D.Delagebeaudeuf, P.Delescluse, J.Chaplart and N.T.Linh 536
Reduction of shot noise by the influence of space charge. A.H.W.Beck 769
Transferred-electron oscillators at very high frequencies. A.M.Mazzone and H.D.Rees 539
Wideband tunable mm-wave Gunn oscillator design. M.J.Lazarus, F.R.Pantoja, S.Novak and M.G.Somekh 739

ERRORS

Error performance of frequency-hopped DPSK system. K.Yamada and K.Daikoku e673

FILTERS

2-D digital filters using logarithmic number systems. G.L.Sicuranza 854

Analysis of noise, sensitivity and dynamic range in digital filters using multiplier extraction approach. P.M.Hughes and B.M.G.Cheetham 286
Anomalous nonlinearity of quartz crystal filters. D.Gordon-Smith and D.P.Almond 207
Class AB CMOS amplifier for micropower SC filters. F.Krummenacher, E.Vittoz and M.Degrauwe 433
Combined switched-capacitor FIR N-path filter using only grounded capacitors. D.Von Grünigen, U.W.Brugger, G.S.Moschytz and W.Vollenweider 788 e987
Design of two-dimensional recursive digital filters to a specified stability margin. G.Crebbin and J.Attikiouzel 765
Efficient real-time interpolation for D/A conversion. J.de Carvalho and J.V.Hanson 733
Encoding of analogue signals using surface-acoustic-wave chirp filters. M.Kowatsch, J.Lafferl, F.Ungersbäck and F.J.Seifert 475
Fast biased polynomial transforms for two-dimensional convolutions. S-C.Pei and J-L.Wu 547
Ladder-simulation switched-capacitor filters with inductor loops. R.Gregorian and S-C.Fan 786
Least-squares magnitude filters with self-equalised delay characteristic. D.D.Rakovich and M.Dj.Radmanovich 833
Low-noise state-space realisation of bandpass active filter. E.J.P.May and H.H.Mehdi 615
Measurement of refractive-index profile of optical-fibre preform by means of spatial filtering. D.Peri and P.L.Chu 371
Method for reducing coefficient sensitivity in lowpass CCD transversal filters. N.Kapur and S.C.Dutta Roy 435
Mismatched filtering for coded aperture imaging with minimum sidelobes. P.Seidler 96
MOS switched capacitor integrator eliminating operational amplifiers. H.Jamal and F.E.Holmes 925
New inverting integrator with improved high-frequency response. M.V.Popovich and O.Katič 641
Performance of an area variable MOS varicap weighted programmable CCD transversal filter. A.B.Bhattacharyya, L.Shankarnarayan and N.Kapur 467
Phase constraints on FIR digital filters. T.F.Liau, M.A.Razzak and L.G.Cuthbert 910
Programmable transversal filter. I.A.Van Gelder, G.J.Declerck and M.A.Copeland 605
Real-time programmable unit-element SC filter for LPC synthesis. U.Kleine, D.Herbst, B.Hoefflinger, B.J.Hosticka and R.Schweer 600
Realisable 100% raised cosine filters. L.F.Lind and T.Labarre 197
Realisation of a switched-capacitor voltage wave pseudobandpass filter. H.M.Reekie, J.Mavor and P.B.Denyer 795
Self-tuned filters. Y.Tsividis 406 e512
Sensitivities of impedance scaled SC filters. P.Lutz 24
Some arithmetically symmetrical bandpass filters. P.Varanasi and S.C.Dutta Roy 26
SSB-FDM using complementary comb filters. Y.Hirata 614
Stability test for multidimensional digital filters. J.L.Brown, J.Delansky, E.Plotkin, L.M.Roytman and M.N.S.Swamy 717
Stability test for two-dimensional recursive digital filters using inner determinants. A.H.Kayran and R.A.King 67
Switched capacitor analogue delays comprising unity gain buffer. J.J.Mulawka 276
Three-layer low frequency hybrid electrothermal filter. J.M.Opuchlik 329
Two-stage stability test for two-dimensional recursive digital filters. P.C.Craig and L.C.Westphal 919
Very low sensitivity recursive digital filter structures. L.Bhuyan and B.N.Chatterji 348
Voltage-controlled SAW filter on berlinite. J.Henaff, M.Feldmann and M.Carel 86

IMAGE PROCESSING

CCD linear image sensor with buried overflow drain structure. H.Goto, H.Sekine, T.Yamada and N.Suzuki 904
Depth of field improvements in long wavelength imaging systems. J.C.Bennett and A.Yamani 860
DFT processing of variable length sequences. B.Arambepola 109
Histogram equalisation with S and π functions in detecting X-ray edges. S.K.Pal and R.A.King 302
Mismatched filtering for coded aperture imaging with minimum sidelobes. P.Seidler 96
New fast discrete sine transform with offset. E.J.K.Bisherurwa and F.P.Coakley 803
Pseudostereoscopic holographic imaging system: a possible approach to high resolution underwater mapping. D.I.Shaw, A.P.Anderson and J.C.Bennett 841
Resolution enhancement in time domain reflectometry systems. B.Chambers 154
Truncation error in 2-D block mode filtering. M.R.Azimi Sadjadi and R.A.King 217

INTEGRATED CIRCUITS

5-18 GHz, 3 dB hybrid coupler. H.Q.Tserng and S.R.Nelson 258
Accurate submicroampere controlled current source. A.Nedungadi 320
Cross-tie slow-wave coplanar waveguide on semi-insulating GaAs substrates. S.Seki and H.Hasegawa 940
E-type circulator for fin lines. M.Braas and C.Schieblich 701
GaAs digital integrated circuits for very high-speed frequency division. M.Gloanec, J.Jarry and G.Nuzillat 763
High-speed frequency dividers with quasi-normally-off GaAs MESFETs. F.Damay-Kavala, G.Nuzillat and C.Arnodo 968
High speed GaAs digital integrated circuit with clock frequency of 4.1 GHz. R.Yamamoto and A.Higashisaka 291
High speed normally-off GaAs MESFET integrated circuit. F.Katano, T.Furutsuka and A.Higashisaka 236
Integrated CMOS SC filter with 170 kHz cutoff frequency. D.Herbst, B.J.Hosticka, B.Höfflinger, U.Kleine, W.Nientiedt and R.Schweer 205
Integrated NMOS output stage with low output impedance. P.U.Calzolari, G.Masetti, C.Turchetti and M.Severi 218
Ion-implanted E/D-type GaAs IC technology. T.Furutsuka, T.Tsuji, F.Katano, A.Higashisaka and K.Kurumada 944
Monolithic class AB operational mirrored amplifier. J.H.Huijsing and C.J.Veelenturf 119
Novel active *RC* building block with optimal sensitivity. J.C.Berka and M.Herpy 887
Performance of integrated dynamic MOS amplifiers. B.J.Hosticka, B.Hoefflinger and D.Herbst 298
Programmable transversal filter. I.A.Van Gelder, G.J.Declerck and M.A.Copeland 605

INTEGRATED OPTICS

Buried heterostructure AlGaAs lasers on semi-insulating substrates. N.Bar-Chaim, J.Katz, I.Ury and A.Yariv 108
Crystallographic facets chemically etched in GaInAsP/InP for integrated optics. K.Furuya, L.A.Coldren, B.I.Miller and J.A.Rentschler 582
CW operation of 1.5 - 1.6 μm wavelength GaInAsP/InP buried-heterostructure integrated twin-guide laser with distributed Bragg reflector. K.Kobayashi, K.Utaka, Y.Abe and Y.Suematsu 366
Guided-wave holographic grating beam expander - fabrication and performance. V.Neuman, C.W.Pitt and L.M.Walpita 165
High speed 2-bit analogue-digital convertor using $LiNbO_3$ waveguide modulators. S.Yamada, M.Minakata and J.Noda 259
Ion implanted optical waveguides in $LiNbO_3$. G.D.H.King, M.C.Bone, B.L.Weiss and D.W.Weeks 897
Low threshold current CW operation of GaInAsP/InP buried heterostructure distributed Bragg-reflector integrated-twin-guide laser emitting at 1.5-1.6 μm. T.Tanbun-ek, S.Arai, F.Koyama, K.Kishino, S.Yoshizawa, T.Watanabe and Y.Suematsu 967
Photoelastic optical directional couplers in epitaxial GaAs layers. T.M.Benson, T.Murotani, P.A.Houston and P.N.Robson 237
SAWDIC: Surface-acoustic-wave-driven directional coupler. C.H.Von Helmolt, H.F.Schlaak and R.T.Kersten 446
Single-mode optical Y-branching circuit using deposited silica guides (DS guides). Y.Murakami and M.Ikeda 411
Single-wavelength operation of 1.53 μm GaInAsP/InP buried-heterostructure integrated twin-guide laser with distributed Bragg reflector under direct modulation up to 1 GHz. K.Utaka, K.Kobayashi, F.Koyama, Y.Abe and Y.Suematsu 368

LASERS AND LASER APPLICATIONS

1.3 μm-wavelength mode controlled GaInAsP/InP etched laser. K.Moriki, K.Iga, M.Uchida, K.Wakao and T.Kunikane 559
1.5 μm region InP/GaInAsP buried heterostructure lasers on semi-insulating substrates. T.Matsuoka, K.Takahei, Y.Noguchi and H.Nagai 12
1.5 μm room-temperature pulsed operation of GaInAsP/InP double heterostructure grown by LP MOCVD. M.Razeghi, P.Hirtz, J.P.Larivain, R.Blondeau, B.de Cremoux and J.P.Duchemin 643
Achievement of 1 MHz frequency stability of semiconductor lasers by double-loop AFC scheme. K.Kikuchi, T.Okoshi and S.Kawanishi 515
Alternating beam method (ABM) in photothermal microscopy (PTM) and photoacoustic microscopy (PAM). A.Lehto, M.Jokinen, J.Jaarinen, T.Tiusanen and M.Luukkala 540
Bistable operation in semiconductor lasers with inhomogeneous excitation. H.Kawaguchi and G.Iwane 167
Bistable operation of semiconductor lasers by optical injection. H.Kawaguchi 741
Buried heterostructure AlGaAs lasers on semi-insulating substrates. N.Bar-Chaim, J.Katz, I.Ury and A.Yariv 108
Calculation of lateral current spreading and series resistance effects in oxide stripe geometry GaAs-GaAlAs DH lasers. G.Lengyel, P.Meissner, E.Patzak and K.H.Zschauer 174
Carrier-induced index change in AlGaAs double-heterostructure lasers. J.S.Manning and R.Olshansky 506
Cavity length dependence of differential quantum efficiency of GaInAsP/InP lasers. M.Asada, K.Itoh, Y.Suematsu and S.Arai 486
Conditions for operation of semiconductor laser with negative light/current characteristic. S.J.Chua 848

Current dependence of temperature rise in CW operated GaInAsP/InP DH laser diodes. P.Brosson and G.H.B.Thompson 957
Current drifting behaviour in InP MISFET with thermally oxidised InP/InP interface. M.Okamura and T.Kobayashi 941
CW operation of 1.5 - 1.6 μm wavelength GaInAsP/InP buried-heterostructure integrated twin-guide laser with distributed Bragg reflector. K.Kobayashi, K.Utaka, Y.Abe and Y.Suematsu 366
CW single-pass Raman generation in optical fibres. Y.Sasaki, Y.Ohmori, M.Kawachi and T.Edahiro 315
Direct observation of Lorentzian lineshape of semiconductor laser and linewidth reduction with external grating feedback. S.Saito and Y.Yamamoto 325
Dynamic spectral width of rapidly modulated 1.58 μm GAINAsP/InP buried-heterostructure distributed-Bragg-reflector integrated-twin-guide lasers. F.Koyama, A.Arai, Y.Suematsu and K.Kishino 938
Effect of cavity length on 1.55 μm buried-heterostructure DH laser characteristics. M.Tokunaga, Y.Nakano, K.Takahei, Y.Noguchi, H.Nagai and K.Nawata 234
Electronic phase noise suppression in diode lasers. A.Dandridge and A.B.Tveten 937
External cavity controlled single longitudinal mode laser transmitter module. K.R.Preston, K.C.Woollard and K.H.Cameron 931
GaInAsP/InP integrated laser with butt-jointed built-in distributed-Bragg-reflection waveguide. Y.Abe, K.Kishino, Y.Suematsu and S.Arai 945
Groove GaInAsP laser on semi-insulating InP. K.L.Yu, U.Koren, T.R.Chen, P.C.Chen and A.Yariv 790 e936
High power output InGaAsP/InP buried heterostructure lasers. Y.Nakano, K.Takahei, Y.Noguchi, Y.Suzuki, H.Nagai and K.Nawata 782
High rate pulse generation from InGaAsP laser in selfoc lens external resonator. S.Akiba, G.E.Williams and H.A.Haus 527
High temperature CW operation of 1.5 μm InGaAsP/InP buffer-layer loaded planoconvex waveguide lasers. Y.Noda, K.Sakai and Y.Matsushima 226
Improved coupling between laser diode and single-mode fibre tipped with a chemically etched self-centred diffracting element. P.Kayoun, C.Puech, M.Papuchon and H.J.Arditty 400
InGaAsP/InP BH lasers on p-type InP substrates. Y.Nakano, K.Takahei, Y.Noguchi, H.Nagai, K.Nawata and M.Tokunaga 645
InGaAsP/InP separated multiclad layer stripe geometry lasers emitting at 1.5 μm. H.Imai, H.Ishikawa, T.Tanahashi and M.Takusagawa 17
Laser diode switch. M.Ikeda 899
Leaky-mode channel-guide injection lasers. D.E.Ackley 766
Low threshold 1.55 μm InGaAsP lasers double clad with InGaAsP confining layers. L.D.Westbrook, A.W.Nelson and C.B.Hatch 952
Low threshold channelled-substrate buried crescent InGaAsP lasers emitting at 1.54 μm. W.J.Devlin, R.H.Walling, P.J.Fiddyment, R.E.Hobbs, D.Murrell, R.E.Spillett and A.G.Steventon 651
Low threshold current CW operation of GaInAsP/InP buried heterostructure distributed Bragg-reflector integrated-twin-guide laser emitting at 1.5-1.6 μm. T.Tanbun-ek, S.Arai, F.Koyama, K.Kishino, S.Yoshizawa, T.Watanabe and Y.Suematsu 967
Low threshold GaInAsP/InP lasers with good temperature dependence grown by low pressure MOVPE. J.P.Hirtz, M.Razeghi, J.P.Larivain, S.Hersee and J.P.Duchemin 113
Low-threshold stripe geometry lasers by metalorganic chemical vapour deposition (MO-CVD). R.D.Burnham, D.R.Scifres and W.Streifer 714
LPE growth of 1.3 μm InGaAsP CW lasers on (110) InP substrates. F.Z.Hawrylo 282
Marked extension of diagnosis length in optical time domain reflectometry using 1.32 μm YAG laser. M.Nakazawa, M.Tokuda, K.Washio and Y.Morishige 783
Modulation frequency characteristics of directly optical frequency modulated AlGaAs semiconductor laser. S.Kobayashi, Y.Yamamoto and T.Kimura 350
Noise characteristics in line-narrowed semiconductor lasers with optical feedback. L.Goldberg, A.Dandridge, R.O.Miles, T.G.Giallorenzi and J.F.Weller 677
Noise characteristics of semiconductor laser amplifiers. T.Mukai and Y.Yamamoto 31
Optical FM signal amplification and FM noise reduction in an injection locked AlGaAs semiconductor laser. S.Kobayashi, Y.Yamamoto and T.Kimura 849
Oscillation frequency, linewidth reduction and frequency modulation characteristics for a diode laser with external grating feedback. O.Nilsson, S.Saito and Y.Yamamoto 589
Performance of an improved InGaAsP ridge waveguide laser at 1.3 μm. I.P.Kaminow, R.E.Nahory, L.W.Stulz and J.C.Dewinter 318
Photo-displacement imaging. S.Ameri, E.A.Ash, V.Neuman and C.R.Petts 337
Picosecond pulse generation by lateral mode switching of (GaAl)As-heterostructure stripe lasers. I.H.White, G.J.Aspin, J.E.Carroll and R.G.Plumb 541
Power coupling from laser diodes into single-mode fibres with quadrangular pyramid-shaped hemiellipsoidal ends. H.Sakaguchi, N.Seki and S.Yamamoto 425
Properties of inverted rib-waveguide lasers operating at 1.3 μm wavelength. S.E.H.Turley, G.D.Henshall, P.D.Greene, V.P.Knight, D.M.Moule and S.A.Wheeler 868
Quantum phase noise and linewidth of a semiconductor laser. Y.Yamamoto, T.Mukai and S.Saito 327
Room-temperature CW operation of distributed-feedback buried-heterostructure InGaAsP/InP lasers emitting at 1.57 μm. K.Utaka, S.Akiba, K.Sakai and Y.Matsushima 961
Room temperature CW operation of GaInAsP/InP double-heterostructure diode lasers emitting at 1.23 μm grown by low-pressure metalorganic chemical vapour deposition. M.Razeghi, J.P.Hirtz, P.Hirtz, J.P.Larivain, R.Bondeau, B.De Cremoux and J.P.Duchemin 597
Self-Q-switched picosecond optical pulse generation with tandem-type AlGaAs TJS laser. H.Ito, N.Onodera, K.Gen-ei and H.Inaba 15
Sensitivity of single mode buried heterostructure lasers to reflected power at 274 Mbit/s. V.J.Mazurczyk 143
Short-cavity single-mode 1.3 μm InGaAsP lasers with evaporated high-reflectivity mirrors. C.A.Burrus, T.P.Lee and A.G.Dentai 954
Single-pass Raman generation pumped by a mode-locked laser. Y.Ohmori, Y.Sasaki, M.Kawachi and T.Edahiro 594
Single-wavelength operation of 1.53 μm GaInAsP/InP buried-heterostructure integrated twin-guide laser with distributed Bragg reflector under direct modulation up to 1 GHz. K.Utaka, K.Kobayashi, F.Koyama, Y.Abe and Y.Suematsu 368
Spectral characteristics of semiconductor laser diodes coupled to optical fibres. A.Dandridge and R.O.Miles 273
Spontaneous emission factor of narrow-stripe gain-guided diode lasers. W.Streifer, D.R.Scifres and R.D.Burnham 933
Structure dependent axial mode stability in GaAlAs/GaAs injection lasers. K.Seki, H.Yanai and T.Kamiya 288
Sum-frequency light generation in optical fibres pumped by a Q-switched laser. Y.Ohmori and Y.Sasaki 781
Time dependence of current at high electric fields in $Al_xGa_{1-x}As$-GaAs heterojunction layers. M.Keever, T.Drummond, K.Hess, H.Morkoc and B.G.Streetman 93
Time-dependent thermal effects in current-modulated semiconductor lasers. L.Goldberg, H.F.Taylor and J.F.Weller 497
Tradeoffs between noise, distortion and fibre length for multichannel analogue TV transmission over graded-index fibres at 0.83 μm. H.P.Berger, R.Welter, A.Dill, G.Guekos and H.Melchior 844
Transverse mode control in InGaAsP/InP buried crescent diode lasers. E.Oomura, H.Higuchi, R.Hirano, H.Namizaki, T.Murotani and W.Susaki 83
V-grooved substrate buried heterostructure InGaAsP/InP laser. H.Ishikawa, H.Imai, T.Tanahashi, Y.Nishitani and M.Takusagawa 465

LIGHT-EMITTING DIODES

$In_{0.53}Ga_{0.47}As$ contact layer for 1.3 μm light-emitting diodes. H.Temkin, A.K.Chin and M.A.Digiuseppe 703
Modulation characteristic and intensity noise of CW superluminescent diodes. R.Schimpe and J.Boeck 715
System experiments using 1.3 μm LEDs. K.Ogawa, E.L.Chinnock, D.Gloge, P.Kaiser, S.R.Nagel and S.J.Jang 71
Wavelength division multiplexing experiment employing dual-wavelength LEDs and photodetectors. K.Ogawa, T.P.Lee, C.A.Burrus, J.C.Campbell and A.G.Dentai 857

LOGIC AND LOGIC DESIGN

Fault detection in combinational circuits using Gunn effect logic devices. K.K.Saluja and F.J.Lidgey 222
GaAs digital integrated circuits for very high-speed frequency division. M.Gloanec, J.Jarry and G.Nuzillat 763
High-speed frequency dividers with quasi-normally-off GaAs MESFETs. F.Damay-Kavala, G.Nuzillat and C.Arnodo 968
Low-power gigabit logic by GaAs SSFL. N.Hashizume, H.Yamada, T.Kojima, K.Matsumoto and K.Tomizawa 553
Low voltage high performance E/D MOS logic. Choi D.H. and C.A.T.Salama 879

MAGNETISM

Frequency/depth-penetration considerations in hyperthermia by magnetically induced currents. J.H.Young, M.-T.Wang and I.A.Brezovich e674

MEASUREMENT

Dispersion measurements in single-mode fibres using sum-frequency mixing as a picosecond optical shutter. K.Mochizuki, Y.Mamihira and H.Wakabayashi 646
Effect of field amplitude taper on measured antenna gain and sidelobes. R.C.Hansen 260
Elliptical oscillation in molecular beam maser with disk resonator. G.Yassin and D.C.Laine 156

Formulation of electric-field integral equation without use of differential operator. C.J.O'Neill, T.Downs and P.J.Khan 598
Measurement of magnetic field by polarisation optical time-domain reflectometry. J.N.Ross 596
Measuring high-bandwidth fibres in the 1.3 μm region with picosecond InGaAsP injection lasers and ultrafast InGaAs detectors. C.Lin, P.L.Liu, T.P.Lee, C.A.Burrus, F.T.Stone and A.J.Ritger 438
Microheater and microbolometer using microbridge of SiO_2 film on silicon. M.Kimura 80
Precise delay/phase measurement using surface-acoustic waves and microprocessing. R.B.Ward 417

MEMORIES

Distributed mailbox arrangement which facilitates task communication in a multimicroprocessor system. N.Jayaram and P.L.Evans 648 e862
Improved performance of 4K SRAM by means of CW laser annealing. T.C.Teng, Y.Shiau, S.De Ornellas, J.Readdie, E.Wong, G.Chang, S.Ko and C.Skinner 627
Low-cost multiprocessor system. A.Gago and J.Biscarri 924
Method for direct multiway branching in microprogram control. C.A.Papachristou 709

MICROPROCESSORS AND MICROPROCESSOR APPLICATIONS

Distributed mailbox arrangement which facilitates task communication in a multimicroprocessor system. N.Jayaram and P.L.Evans 648 e862
Low-cost multiprocessor system. A.Gago and J.Biscarri 924
Microprocessor-based real time system for eye motion analysis. O.M.Abdel Gadir and D.J.Quarmby 196

MICROWAVE CIRCUITS AND SYSTEMS

10 Gbit/s and gate using dual-gate GaAs MESFET. R.Tell, T.Andersson and S.T.Eng 201
5-18 GHz, 3 dB hybrid coupler. H.Q.Tserng and S.R.Nelson 258
70 MHz to 6 GHz FET up-convertor. P.Bura 437
Accurate model for open end effect of microstrip lines. M.Kirschning, R.H.Jansen and N.H.L.Koster 123
Adjustable microstrip transformer for use with Josephson devices in mm-wave ICs. T.F.Finnegan and O.H.Soerensen 79
Analysis and design of DC blocks. S.R.Borgaonkar and S.N.Rao 101
Coupling coefficient between dielectric resonator and microstrip line. P.Skalicky 99
Directional harmonics in Doppler effect. M.J.Lazarus, M.G.Somekh, S.Novak and F.R.Pantoja 94
Experimental 30 GHz printed array with low loss insular guide feeder. M.R.Inggs, M.T.Birand and N.Williams 146
Experimental evaluation of bend radiation losses in millimetric dielectric waveguide. M.R.Inggs and N.Williams 75
Generalised analysis of microwave networks including lumped elements. M.I.Sobhy and E.A.Hosny 181
High efficiency InP transferred electron device for high peak power, high mean power pulsed sources in J-band. D.R.Brambley and D.C.Smith 307
Influence of diode capacitance on performance of balanced microwave mixers. E.Korolkiewicz and B.L.J.Kulesza 144
Ku-band MIC bipolar VCO. R.G.Winch and J.L.Matson 296
Phase-matched second harmonic generation and parametric mixing on nonlinear transmission lines. B.Wedding and D.Jager 76
Rigorous analysis of planar MIS transmission lines. P.Kennis and L.Faucon 454
Stabilised FET oscillator with input dielectric resonator: large signal design. A.Podcameni and L.A.Bermudez 44

MICROWAVE DEVICES AND COMPONENTS

Approximate determination of effective radius and effective dielectric constant of microstrip disc resonators. J.Helszajn and R.W.Lyon 46
Characteristics of broadside-coupled microstrip lines with iso/anisotropic substrates. A.G.D'Assunçao, A.J.Giarola and D.A.Rogers 264
Cross-tie slow-wave coplanar waveguide on semi-insulating GaAs substrates. S.Seki and H.Hasegawa 940
Dispersion in microstrip lines comprising layered dielectric media. P.K.Wahi and Z.Turski 785
E-type circulator for fin lines. M.Braas and C.Schieblich 701
Even mode analysis of symmetric coupled microstrip. D.Kajfez 183
Groove-guide microwave detector for 100 GHz operation. D.J.Harris and S.Mak 516
High frequency microstrip branch-line coupler design with T-junction discontinuity compensation. M.Cuhaci and G.J.P.Lo 87 e334
Low noise single-ended mixer for 230 GHz. J.W.Archer and R.J.Mattauch 180
Method for improving microstrip coupler directivity. K.Shibata, H.Yanagisawa, Y.Torimura and K.Hatori 732
MIC impatt diode oscillator stabilised by temperature compensated dielectric resonator. G.B.Morgan and G.O.Obe 72
New correlation radiometer for microwave thermography. A.Mamouni, J.C.Van de Velde and Y.Leroy 554
Operating modes of millimetre wave transferred electron oscillators. I.G.Eddison and D.M.Brookbanks 112
Parallel-coupled microstrip lines on pyrolytic boron nitride. A.G.D'Assunlao and A.J.Giarola 947
Power dissipation on edges of coupled microstrip. D.Kaifez, Z.Ratkovic and C.E.Smith 984
Radiation suppressed high-Q dielectric resonators for MIC applications. E.Hagihara, M.Akaike and N.Imai 213
Simple design of X-junction microstrip circulators. A.-M.Khilla 681

MODELLING

Algorithms for sampled data signal flow graphs. M.Dias and F.J.Evans 341
Application of Routh's criterion to test for positive real functions. K.S.Yeung 375
Cauer continued fraction methods for model reduction. R.Parthasarathy and S.John 792
Computation of impulse response autocorrelation sequence of an AR model. G.A.Mian and A.P.Nainer 347
Continuous model for gate-induced charge in short-channel MOSFETS. F.Runovc 636
Discrete time MRAS with reduced implementation complexity. A.A.A.Karim, R.Nagarajan and K.B.Mirza 809
Economic choice of component tolerances. A.Ilumoka and R.Spence 979
Estimation of parameter drift rate for detection and prediction of faults. L.Kazovsky and A.Cohen 306
Measurement and modelling of the probability density function of amplitude scintillations of an X-band satellite down-link. T.J.Moulsley, J.Haddon, P.Lo and E.Vilar 625
Simulation of FM/FDM blocks for interference and intermodulation calculations. B.G.Evans and H.Ganem 963
Stability of reduced model obtained by truncation. K.S.Yeung 374
Transformation algorithm for identification of continuous-time multivariable systems from discrete data. N.K.Sinha and G.J.Lastman 779
Truncation method of reduction: a viable alternative. Y.Shamash 97

MODULATION

Cochannel interference immunity of high capacity QAM. V.K.Prabhu 680
Influence of two-path propagation on MSK systems. P.Szulakiewicz 893
Magnitude and phase in thermal wave imaging. A.Lehto, J.Jaarinen, T.Tiusanen, M.Jokinen and M.Luukkala 364
Realisation of a decoder for two MFM codes. J.Isailović 117
Single-wavelength operation of 1.53 μm GaInAsP/InP buried-heterostructure integrated twin-guide laser with distributed Bragg reflector under direct modulation up to 1 GHz. K.Utaka, K.Kobayashi, F.Koyama, Y.Abe and Y.Suematsu 368
SSB versus FM at VHF for mobile radio telephony. A.J.Motley 852
Subjective performance of amplitude companding in SSB mobile radio systems. J.P.McGeehan and A.Bateman 859
Tradeoffs between noise, distortion and fibre length for multichannel analogue TV transmission over graded-index fibres at 0.83 μm. H.P.Berger, R.Welter, A.Dill, G.Guekos and H.Melchior 844

OPTICAL COMMUNICATION

1.3 μm, 400 Mbit/s undersea optical repeater sea trial. Y.Nomura, T.Morimitsu, I.Kitazawa and M.Washio 889
Achievement of 1 MHz frequency stability of semiconductor lasers by double-loop AFC scheme. K.Kikuchi, T.Okoshi and S.Kawanishi 515
Bidirectional fibre optic loop-structured network. K.Ito, Y.Umeda, Y.Sugiyama, K.Nakajima, K.Oshima and M.Nunoshita 84
Birefringence measurement in twisted single-mode fibres. M.Monerie and P.Lamouler 252 e334
Coupling of an optical fibre to a substrate entry photodiode. B.M.Macdonald and A.G.Saunders 832
Digital transmission experiment using LED and PIN-PD arrays. Y.Tachikawa, K.Ohnishi, Y.Fujii and Y.Nagata 650
Direct observation of Lorentzian lineshape of semiconductor laser and linewidth reduction with external grating feedback. S.Saito and Y.Yamamoto 325
Double crucible optical fibre for data link applications. K.J.Beales, P.W.France and S.Partington 846
Laser based WDM multichannel video transmission system. J.Conradi, R.Maciejko, J.Straus, I.Few, G.Duck, W.Sinclair, A.J.Springthorpe and J.C.Dyment 91

Modulation characteristic and intensity noise of CW superluminescent diodes. R.Schimpe and J.Boeck 715
Noise characteristics in line-narrowed semiconductor lasers with optical feedback. L.Goldberg, A.Dandridge, R.O.Miles, T.G.Giallorenzi and J.F.Weller 677
OH reduction in preforms by isotope exchange. E.Modone and G.Roba 815
Optical fibre connectors using a fused and drawn multi-class-rod arrangement. S.Nagasawa and H.Murata 268
Optical mode conversion using chirped gratings. P.S.Chung and M.G.F.Wilson 14
Optical tee coupler for data bus system with single multimode fibres. T.Matsui and M.Nunoshita 304
Optical transmission of 16 digitised TV channels over 21 km fibre at a bit rate of 1.12 Gbit/s. C.Baack, G.Elze, B.Enning, G.Heydt, G.Walf and G.Wenke 517
Reliability of a new method for measurements of modal power distribution in optical fibres with application to mode scrambler testing. M.Calzavara, P.Di Vita and U.Rossi 543
Sensitivity of single mode buried heterostructure lasers to reflected power at 274 Mbit/s. V.J.Mazurczyk 143
Structure dependent axial mode stability in GaAlAs/GaAs injection lasers. K.Seki, H.Yanai and T.Kamiya 288
System experiments using 1.3 μm LEDs. K.Ogawa, E.L.Chinnock, D.Gloge, P.Kaiser, S.R.Nagel and S.J.Jang 71
Total reflection optical waveguide switch. H.Terui, M.Kobayashi and T.Kasai 77

OPTICAL FIBRES

100 km single mode VAD fibres. M.Kawachi, S.Tomaru, M.Yasu, M.Horiguchi, S.Sakaguchi and T.Kimura 57
2 Gbit/s optical transmission experiments at 1.3 μm with 44km single-mode fibre. J.I.Yamada, S.Machida and T.Kimura 479
Analysis of multimode optical fibres with profile perturbations. A.Ankiewicz and C.Pask 551
Analytical approach to prediction of dispersion properties of step-index single mode optical fibres. H.Hung-Chia and W.Zi-Hua 202
Application of focusing method of index profiling to transition region of optical fibre preform. P.L.Chu and D.Peri 64
Asymptotic eigenvalues of vector wave equation for guided modes in graded-index fibre. H.Ikuno 8
Backscattering measurement of bending-induced birefringence in single mode fibres. B.Y.Kim and S.S.Choi 193
Backscattering signatures from graded-index fibres with diameter variations. M.Eriksrud, A.R.Mickelson and T.Andersen-Gott 200
Bandwidth formulas for chromatic limitation in optical fibres. R.W.H.Engelmann 333
Beamforming fibre optic sensor. S.C.Rashleigh and H.F.Taylor 138
Cascaded multipole switches for single-mode and multimode optical fibres. W.C.Young and L.Curtis 571
Ceramic components for optical-fibre systems. P.Mossman 451
Characteristics of phase-matched sum-frequency light in optical fibres. Y.Ohmori and Y.Sasaki 678
Chromatic dispersion measurement by white-light interferometry on metre-length single-mode optical fibres. H-T.Shang 603
Coupling of an optical fibre to a substrate entry photodiode. B.M.Macdonald and A.G.Saunders 832
Cutoff frequencies of vector wave modes in cladded inhomogeneous optical fibre (Comment). M.Hashimoto 17
Cutoff frequencies of W-type fibre with polynomial profile core. A.Yata and H.Ikuno 9 e432
CW single-pass Raman generation in optical fibres. Y.Sasaki, Y.Ohmori, M.Kawachi and T.Edahiro 315
Direct method of determining equivalent-step-index profiles for monomode fibres. C.A.Millar 458
Dispersion measurements in single-mode fibres using sum-frequency mixing as a picosecond optical shutter. K.Mochizuki, Y.Mamihira and H.Wakabayashi 646
Double crucible optical fibre for data link applications. K.J.Beales, P.W.France and S.Partington 846
Effects of γ irradiation on mid-IR transmitting glass. A.Rosiewicz and J.R.Gannon 184
Effects of thermal stress on group delay in jacketed single mode fibres. Y.Namihira, K.Mochizuki and K.Tatekura 813
Experimental study of single-mode W-type optical fibre. A.T.Andreev, A.B.Grundinin, E.M.Dianov, A.M.Prokhorov, A.N.Guryanov, G.G.Devjatykh, S.V.Ignatjev and V.F.Hopin 416
Far-field profiling of multimode optical fibres. W.Freude 385
Fibre-length dependence of critical power for stimulated Raman scattering. Y.Ohmori, Y.Sasaki and T.Edahiro 593
Fibre light acceptance for modified near field technique. D.H.Irving, F.A.Donaghy and P.V.H.Sabine 250
Fluoride-glass-cladded optical fibres for mid-infra-red ray transmission. S.Mitachi, T.Miyashita and T.Kanamori 591, 672
Fluoride glasses for infra-red optical fibres. H.Poignant, J.Le Mellot and J.F.Bayon 295
Frequency mixing in fibre-optic interferometer systems. K.P.Koo and E.F.Carome 380
Fundamental mode spot-size measurement in single-mode optical fibres. F.Alard, L.Jeunhomme and P.Sansonetti 958
Fused single mode fibre access couplers. C.A.Villarruel and R.P.Moeller 243
Fusion mass-splicing for optical fibres by discharge heating. M.Tachikura 694
Generation of harmonic distortion at fibre connectors. H.Kuwahara and M.Goto 626
High-resolution measurement of diameter variations in optical fibres by the backscatter method. A.J.Conduit, A.H.Hartog, M.R.Hadley, D.N.Payne, M.P.Gold, R.J.Mansfield and E.J.Tarbox 742
Hybrid modes of graded-index optical fibres. M.Hashimoto 659 e987
Improved coupling between laser diode and single-mode fibre tipped with a chemically etched self-centred diffracting element. P.Kayoun, C.Puech, M.Papuchon and H.J.Arditty 400
Interferometric current sensors using optical fibres. A.Dandridge, A.B.Tveten and T.G.Giallorenzi 523
Interferometric measurement of dispersion of a single-mode optical fibre. W.D.Bomberger and J.J.Burke 495
Long-length fibre containing high-strength splices. Y.Miyajima, K.Ishihara, T.Kakii, Y.Toda and S.Tanaka 670
Long wavelength performance of optical fibres co-doped with fluorine. J.Irven, A.P.Harrison and C.R.Smith 3
Long wavelength performance of $SiO_2/GeO_2/P_2O_5$ core fibres with different P_2O_5 levels. J.Irven 2
Low-drift fibre gyro using a superluminescent diode. K.Böhm, P.Marten, K.Petermann, E.Weidel and R.Ulrich 352
Low loss high-density optical cable with nylon-extruded fibre units. K.Ishihara, N.Uchida, Y.Ishida, Y.Sugawara and M.Higashimoto 69
Low-loss multifibre connectors with plug-guide-grooved silicon. T.Satake, S.Nagasawa and H.Murata 828
Low-loss single-mode fibres prepared by plasma-enhanced MCVD. J.W.Fleming and V.R.Raju 867
Low-loss single-polarisation fibres. T.Katsuyama, H.Matsumura and T.Suganuma 473
Low-loss single polarisation fibres with asymmetrical strain birefringence. T.Hosaka, K.Okamoto, T.Miya, Y.Sasaki and T.Edahiro 530
Marked extension of diagnosis length in optical time domain reflectometry using 1.32 μm YAG laser. M.Nakazawa, M.Tokuda, K.Washio and Y.Morishige 783
Materials dispersion zero in glass mixtures. K.Nassau 768
Maximum single frequency input power in a long optical fibre determined by stimulated Brillouin scattering. N.Uesugi, M.Ikeda and Y.Sasaki 379
Measurement of backscatter factor in single-mode fibres. M.P.Gold and A.H.Hartog 965
Measurement of magnetic field by polarisation optical time-domain reflectometry. J.N.Ross 596
Measurement of refractive-index profile of optical-fibre preform by means of spatial filtering. D.Peri and P.L.Chu 371
Modal distribution of backscattered light in a step-index multimode fibre. R.Payne 568
Modal noise in single-mode fibres operated slightly above cutoff. S.Heckmann 499
Mode power distribution in optical fibres with fluctuation in physical parameters and application to backscattering signal analysis. P.Di Vita 874
Modified VAD method for optical-fibre fabrication. K.Imoto and M.Sumi 525
Multichannel photon-counting backscatter measurements on monomode fibre. P.Healey 751
Mutual influence among imperfect joints in multimode-fibre link. V.Rizzoli and C.G.Someda 906
New primary coating method for optical fibres. S.Sakaguchi, T.Kimura and M.Nakahara 800
New reinforcement for arc-fusion spliced fibre. M.Miyauchi, M.Matsumoto, Y.Toda, K.Matsuno and Y.Tokumuru 907
OH reduction in preforms by isotope exchange. E.Modone and G.Roba 815
Optical fibre diameter variations and their effect on backscatter loss measurements. A.J.Conduit, D.N.Payne, A.H.Hartog and M.P.Gold 308
Optimisation of a graded-index fibre over a wavelength range. J.Arnaud and A.M.Desage 339
Optimum optical pulse width for high bandwidth single-mode fibre transmission. C.Lin and D.Marcuse 54
Polarisation beat length measurement in a single-mode optical fibre by backward Rayleigh scattering. M.Nakazawa, T.Horiguchi, M.Tokuda and N.Uchida 513
Polarisation behaviour fluctuations of a single-mode fibre. G.Garlichs 894
Polarisation conservation in single-mode fibres. S.Machida, J.Sakai and T.Kimura 494
Polarisation-maintaining single-mode fibre with azimuthally inhomogeneous index profile. K.Kitayama, S.Seikai and N.Uchida 419
Polarisation maintenance in circularly birefringent fibres. A.J.Barlow and D.N.Payne 388
Polarisation mode dispersion measurements in long single mode fibres. K.Mochizuki, Y.Namihira and H.Wakabayashi 153
Polarisation preservation in multimode fibres. R.E.Wagner, R.H.Stolen and W.Pleibel 177
Power coupling from laser diodes into single-mode fibres with quadrangular pyramid-shaped hemiellipsoidal ends. H.Sakaguchi, N.Seki and S.Yamamoto 425

Precision moulded fibre connector using an electroformed cavity. T.Kurokawa, T.Yoshizawa, S.Nara and Y.Katayama 667
Prediction of loss minima in infra-red optical fibres. S.Shibata, M.Horiguchi, K.Jinguji, S.Mitachi, T.Kanamori and T.Manabe 775
Production of single-mode fibres with negligible intrinsic birefringence and polarisation mode dispersion. A.J.Barlow, D.N.Payne, M.R.Hadley and R.J.Mansfield 725
Refractive index dispersion of lightguide glasses at high temperature. N.Shibata, S.Shibata and T.Edahiro 310
Reliability assurance for long-length optical fibre based on proof testing. Y.Mitsunaga, Y.Katsuyama and Y.Ishida 567
Reliability of a new method for measurements of modal power distribution in optical fibres with application to mode scrambler testing. M.Calzavara, P.Di Vita and U.Rossi 543
Role of modal distribution in determining power backscattered from fibres with diameter perturbations. A.R.Mickelson and M.Eriksud 658
Self-aligning optical-fibre connector with magnetic-alloy-clad fibres. Y.Ando and I.Nishi 793
Simple visual inspection technique for optical fibre preforms. I.Sasaki and D.N.Payne 805
Simplified numerical analysis of optical fibres and planar waveguides. R.A.Sammut and C.Pask 105
Single-mode-fibre design for 4 μm band operation. L.Jeunhomme 560
Single-mode fibres in a few moments. C.D.Hussey and C.Pask 644
Single mode fibres with asymmetrical refractive index pits on both sides of core. T.Hosaka, K.Okamoto, Y.Sasaki and T.Edahiro 191
Single-mode optical fibre microbending loss in a loose tube coating. S.Hornung and M.H.Reeve 774
Single-pass Raman generation pumped by a mode-locked laser. Y.Ohmori, Y.Sasaki, M.Kawachi and T.Edahiro 594
Solution of wave equation in graded-index optical fibres by means of multiparabolic approximation. G.Coppa and P.Di Vita 896
Spectral characteristics of semiconductor laser diodes coupled to optical fibres. A.Dandridge and R.O.Miles 273
Stabilising single mode fibre couplers by using gel glass. D.C.Tran and K.P.Koo 187
Strength of fusion splices for fibre lightguides. J.T.Krause, C.R.Kurkjian and U.C.Paek 232
Stripe waveguide Y-intersection as efficient coupler for multimode optical communication systems. A.D.De Oliveira, M.G.F.Wilson and O.Parriaux 100
Sum-frequency light generation in optical fibres pumped by a Q-switched laser. Y.Ohmori and Y.Sasaki 781
Teflon FEP-clad fluoride glass fibre. S.Mitachi, S.Shibata and T.Manabe 128
Thermal characteristic measurement in jacketed and unjacketed fibres by a spatial technique. N.Shibata, Y.Katsuyama, M.Tateda and S.Seikai 345
Three-dimensional fibre preform profiling. P.L.Francois, I.Sasaki and M.J.Adams 876
VAD single mode fibre with 0.2 dB/km loss. S.Tomaru, M.Yasu, M.Kawachi and T.Edahiro 92
VAD single-mode fibres with high Δn values. T.Tomaru, M.Kawachi, M.Yasu, T.Miya and T.Edahiro 731
Vortex shedding fluid flowmeter using optical fibre sensor. J.H.Lyle and C.W.Pitt 244
Wavelength dependence of polarisation mode dispersion in elliptical-core single-mode fibres. N.Shibata, M.Tateda, S.Seikai and N.Uchida 564

OPTICS

Cylindrical concave diffraction grating utilising thin silicon chip. Y.Fujii and J.Minowa 934
Dispersive and scattering properties of a ZrF_4 based glass. H.Poignant 973
Distributed-index planar microlens array prepared from deep electromigration. M.Oikawa, K.Iga and T.Sanada 452
Improved coupling between laser diode and single-mode fibre tipped with a chemically etched self-centred diffracting element. P.Kayoun, C.Puech, M.Papuchon and H.J.Arditty 400
Integrated optic frequency shifter modulator. B.Culshaw and M.G.F.Wilson 135
Marked extension of diagnosis length in optical time domain reflectometry using 1.32 μm YAG laser. M.Nakazawa, M.Tokuda, K.Washio and Y.Morishige 783
Material dispersion evaluation in a fluoride glass. L.Jeunhomme, H.Poignant and M.Monerie 808
Maximum single frequency input power in a long optical fibre determined by stimulated Brillouin scattering. N.Uesugi, M.Ikeda and Y.Sasaki 379
New 2-channel multiplexer using polarisation. R.Watanabe and K.Nosu 133
New optical heterodyne detector with integrated diffraction grating. H.Sakaki, Y.Fujii, M.Misawa and H.Hidaka 727
Normalised power transmission in single mode optical branching waveguides. H.Sasaki and N.Mikoshiba 136
Numerical study of inhomogeneous optical waveguide problems using predictor-corrector method. G.L.Yip and H.H.Yao 229
Optoelectronic matrix switch using heterojunction switching photodiodes. E.H.Hara, S.Machida, M.Ikeda, H.Kanbe and T.Kimura 150
Photoelastic optical directional couplers in epitaxial GaAs layers. T.M.Benson, T.Murotani, P.A.Houston and P.N.Robson 237
Remote optical measurement of temperature using luminescent materials. J.S.McCormack 630
Strength of fusion splices for fibre lightguides. J.T.Krause, C.R.Kurkjian and U.C.Paek 232
Tensile strengths > 4 GPa for lightguide fusion splices. J.T.Krause, C.R.Kurkjian and U.C.Paek 812
Wavelength dependence of polarisation mode dispersion in elliptical-core single-mode fibres. N.Shibata, M.Tateda, S.Seikai and N.Uchida 564
Wavelength division multiplexing experiment employing dual-wavelength LEDs and photodetectors. K.Ogawa, T.P.Lee, C.A.Burrus, J.C.Campbell and A.G.Dentai 857

OPTOELECTRONICS

2.24 Gbit/s optical transmission system at 0.85 μm wavelength. W.Albrecht, C.Baack, G.Elze, B.Enning, G.Heydt, K.Peters, G.Walf and G.Wenke 664
CCD linear image sensor with buried overflow drain structure. H.Goto, H.Sekine, T.Yamada and N.Suzuki 904
Fast photoconductive optoelectronic broadband switch with low control voltage. R.I.MacDonald, E.H.Hara and R.H.Hum 611
Novel electro-optical feedback technique for noise and distortion reduction in high-quality analogue optical transmission video signals. A.Van De Grijp, J.C.Koopman, L.J.Meuleman, A.J.A.Nicia, E.Roza and J.H.C.Van Heuven 361
Observation of higher-order diffraction components in degenerate four-wave mixing experiments in $Bi_{12}GeO_{20}$ crystals. Y.H.Ja 488
Optical-cable properties under frozen water in a conduit and a suitable method for prevention of degradation. M.Tanaka, T.Kobayashi, Y.Sugawara, K.Inada, C.Tanaka, Y.Katsuyama and Y.Ishida 796
Planar InP avalanche photodiode with Zn-diffused guard ring. H.Ando, N.Susa and H.Kanbe 292

PHOTOELECTRIC DEVICES

New detector for thermal imaging systems. C.T.Elliott 312
Planar InP avalanche photodiode with Zn-diffused guard ring. H.Ando, N.Susa and H.Kanbe 292
Symmetrical MOTT barrier as a fast photodetector. C.J.Wei, H.-J.Klein and H.Beneking 688
Very-high speed back-illuminated InGaAs/InP PIN punch-through photodiodes. T.P.Lee, C.A.Burrus, K.Ogawa and A.G.Dentai 431

PIEZOELECTRIC DEVICES AND MATERIALS

Lithium tetraborate: a new temperature-compensated SAW substrate material. R.W.Whatmore, N.M.Shorrocks, C.O'Hara, F.W.Ainger and I.M.Young 11
Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method. M.Koshiba, M.Okada and M.Suzuki 609
Temperature variation of SAW power flow angle. D.F.Williams and F.Y.Cho 164
Ultra low bulk orientations of lithium niobate for SAW TV filters. R.F.Milson, R.J.Murray, I.Flinn and M.Redwood 89
ZnO/SiO_2-diaphragm composite resonator on a silicon wafer. K.Nakamura, H.Sasaki and H.Shimizu 507

RADAR

Compound representation of high resolution sea clutter. K.D.Ward 561 e862
Determination of viewing aspect window of RCS diagram for recognition of isotropic linear target. J.Saillard and G.Chassay 173
Directional harmonics in Doppler effect. M.J.Lazarus, M.G.Somekh, S.Novak and F.R.Pantoja 94
MTI detection loss in clutter. D.C.Schleher 82
New commutated Doppler radar system. F.R.Connor 533
New moving target simulators for Doppler radar. M.J.Lazarus, F.R.Pantoja and M.G.Somekh 48
Parameter estimation of an SSR amplitude comparison monopulse extractor. G.Jacovitti 632
Radar echoes near a dielectric resonance. J.Van Bladel 699
Rapid interference suppression using Kalman filter approach. K.Krucker 65
Recognition of isotropic plane target from RCS diagram. J.Saillard and G.Chassay 397
Resolution enhancement in time domain reflectometry systems. B.Chambers 154

RADIO LINKS

Interference on microwave digital radio links due to transhorizon propagation. J.E.Doble 399

SSB versus FM at VHF for mobile radio telephony. A.J.Motley 852

RADIOWAVE PROPAGATION

Analysis of 11 GHz slant path fade duration and fade slope. F.Dintelmann 267

Attenuation statistics at 11.6 GHz from satellite SIRIO after three years' activity in Italy. M.Mauri and A.Paraboni 440

Duration of rain-induced fades of signal from Sirio at 11.6 GHz. E.Matricciani 29

Effect of raindrop shape on crosspolarisation/attenuation relationships. B.G.Evans, S.A.J.Upton and A.R.Holt 22

Effective canting angle of distorted raindrops along earth-space propagation path. O.Furuta and M.Yamada 170

Extinction cross-section measurements on single falling water drops at 100 GHz. D.J.Harris and T.M.Teo 7

Interference of correlated radio signals with Rayleigh fading. A.Wojnar 608

Melting layer attenuation at 28.6 GHz from simultaneous comstar beacon and polarisation diversity radar data. A.Hendry, Y.M.M.Antar, J.J.Schlesak and R.L.Olsen 190

Microwave thermal emission of rain. A.Mawira 162

Modified Lin's empirical formula for calculation rain attenuation on a terrestrial path. J.A.Garcia-Lopez and V.Casares-Giner 34

Rate of change of signal attenuation from Sirio at 11.6 GHz. E.Matricciani 139

Spectral density of amplitude scintillations on a 55 GHz line of sight link. F.C.Medeiros Filho, D.A.R.Jayasuriya and R.S.Cole 25

Variability of atmospheric noise temperature in 11-14 GHz band due to water vapour and clouds. G.Brussaard 20

SEMICONDUCTOR DEVICES AND MATERIALS

1.3 μm InP/InGaAsP planar avalanche photodiodes. T.Shirai, F.Osaka, S.Yamasaki, K.Nakajima and T.Kaneda 826

4 GBIT/s pseudo-noise generator using GaAs MESFETs. M.Henry and J.L.Baron 928

60 GHz high-efficiency InP pulsed TEO. I.G.Eddison, I.Davies, A.M.Howard and D.M.Brookbanks 948

Acoustionjection transistor - A new type of electrically controlled transducer. Yu.V.Gulyaev, G.D.Mansfeld and G.A.Orlova 396

Alloy scattering effects and calculated mobility in n-type $Ga_{0.47}In_{0.53}As$. T.P.Pearsall 169

Alternative mechanism for substrate minority carrier injection in MOS devices operating in low level avalanche. P.A.Childs, W.Eccleston and R.A.Stuart 281

Amorphisation and low temperature recrystallisation of InP. V.L.Wrick, W.J.Choyke and C.F.Tzeng 752

Analysis for optimum threshold voltage and load current of E-D-type GaAs DCFL circuits. M.Ino, M.Hirayama and M.Ohmori 522

Annealing of Si_3N_4-capped ion-implanted InP. S.S.Gill, B.J.Sealy, P.J.Topham, N.J.Barrett and K.G.Stephens 623

Application of feedback techniques to the realisation of hybrid and monolithic broadband low-noise-and-power GaAs FET amplifiers. R.S.Pengelly 798

Carrier-induced index change in AlGaAs double-heterostructure lasers. J.S.Manning and R.Olshansky 506

Cavity length dependence of differential quantum efficiency of GaInAsP/InP lasers. M.Asada, K.Itoh, Y.Suematsu and S.Arai 486

Characterisation of a deep electron trap in molecular-beam epitaxial InP. R.M.Park and C.R.Stanley 669

Characteristics of field-effect transistor using fluorinated amorphous-silicon (a-Si:F). H.Matsumura, M.Kanamori and S.Furukawa 457

Characteristics of MOSFETS fabricated in silicon-on-insulator material formed by high-dose oxygen ion implantation. H.W.Lam, R.F.Pinizzotto, H.T.Yuan and D.W.Bellavance 356

Chromium contamination in VPE InP from photoconductivity spectra. S.Fung, R.J.Nicholas, A.M.Davison and R.A.Stradling 188

Deep hole traps in VPE p-type InP. M.Inuishi and B.W.Wessels 685

Deep level spectroscopy in InP:Fe. G.Bremond, A.Nouailhat, G.Guillot and B.Cockayne 55

Determination of an initial mesh for computer simulation of H-abrupt devices. R.J.Bennett and K.A.Thoma 747

Differences of plasma formation and extraction in P^+NN^+ and N^+PP^+ silicon trapatt structures. F.Vaitiekunas and J.Vyshniauskas 822

Diffusion of transition elements in GaAs and InP. M.R.Brozel, B.Tuck and E.J.Foulkes 532

Effect of energy relaxation on injected current pulse in high-frequency impatt diodes. D.Lippens and E.Constant 878

Effect of illumination and gate bias on flat-band voltage in plasma CVD Si-N on n-Si MIS structure. M.U.Jeong, J.Shirafuji, Y.Inuishi, H.Yakushiji, K.Harada and H.Oka 444 e862

Effect of masking geometry on gain of bipolar transistors. S.A.Abbasi and A.Brunnschweiler 270

Effect of substrate orientation on electrical properties of LPE-grown InP. K.Akita, A.Yamaguchi, K.Nakajima and T.Takanohashi 921

Effect of vacuum annealing cleaning on electrical characteristics of $GaAs_{1-x}P_x$-Mo Schottky diodes. E.Calleja and J.Piqueras 37

Effects of heat treatment on noise spectrum in Au-InP Schottky barriers. J.M.Peransin, M.Mesbah and E.Groubert 757

Efficient fundamental frequency oscillation from millimetre-wave indium phosphide n^+-n-n^+ transferred electron oscillators. I.G.Eddison, I.Davies, P.L.Giles and D.M.Brookbanks 758

Efficient P-type Si impatt diodes for V-band frequencies. D.Leistner 635

Electron concentration and alloy composition dependence of Hall factor in $Ga_xIn_{1-x}As_yP_{1-y}$. Y.Takeda, M.A.Littlejohn, J.A.Hutchby and R.J.Trew 686

Electron hall mobility calculations and alloy scattering in $Ga_{0.47}In_{0.53}As$. Y.Takeda, M.A.Littlejohn and J.R.Hauser 377

Electron scattering profiles in SOS films measured by temperature-dependent Hall effect. J-H.Lee 566

Enhanced mobility in inverted $Al_xGa_{1-x}As$/GaAs heterojunctions: binary on top of ternary. T.J.Drummond, H.Morkoc, S.L.Su, R.Fischer and A.Y.Cho 870

Equivalent circuit of GaAs dual gate MESFETs. C.Tsironis and R.Meierer 477

Etched profiles of SiO_2 layer. S-H Oh, Y-I Choi, Y-S Kwon and C-K Kim 227

Exact J/V characteristic of an insulator diode with thermal free carriers in nonconstant mobility regime. Y.K.Sharma and V.S.Raghav 355

Excess-noise and receiver sensitivity measurements of $In_{0.53}Ga_{0.47}As$/InP avalanche photodiodes. S.R.Forrest, G.F.Williams, O.K.Kim and R.G.Smith 917

Extremely high electron mobilities in modulation-doped GaAs -Al_xGa_{1-x} As heterojunction superlattices. W.I.Wang, C.E.C.Wood and L.F.Eastman 36

Extremely low-noise MESFETs fabricated by metal-organic chemical vapour deposition. K.Kamei, H.Kawasaki, T.Chigira, T.Nakanisi, K.Kawabuchi and M.Yoshimi 450

Failure of Matthiessen's rule in the calculation of carrier mobility and alloy scattering effects in $Ga_{0.47}In_{0.53}As$. Y.Takeda and T.P.Pearsall 573

Fast response InP/InGaAsP heterojunction phototransistors. D.Fritzsche, E.Kuphal and R.Aulbach 178

Field dependence of mobility in $Al_{0.2}Ga_{0.8}As$/GaAs heterojunctions at very low fields. T.J.Drummond, M.Keever, W.Kopp, H.Morkoç, K.Hess, B.G.Streetman and A.Y.Cho 545

Fully ion-implanted GaAs ICs using normally-off JFETs. J.Kasahara, K.Taira, Y.Kato, M.Dohsen and N.Watanabe 621

GaAlAs/GaAs heterojunction microwave bipolar transistor. H.Beneking and L.M.Su 301

GaAs FET distributed amplifier. J.A.Archer, F.A.Petz and H.P.Weidlich 433

GaAs MESFET circuit simulation model including negative differential mobility. T.Takada, K.Yokoyama and M.Hirayama 132

GaAs microwave power FET with polyimide overlay interconnection. B.Turner, W.P.Barr, D.P.Cooper and D.J.Taylor 185

GaAs power MESFETs prepared by metalorganic chemical vapour deposition. T.Shino, S.Yanagawa, Y.Yamada, K.Arai, K.Kamei, T.Chigira and T.Nakanisi 738

GaAs read-type impatt diode for 130 GHz CW operation. K.Chang, J.K.Kung, P.G.Asher, G.M.Hayashibara and R.S.Ying 471

High current gain in monolithic hot-electron transistors. J.M.Shannon and A.Gill 620

High efficiency InP transferred electron device for high peak power, high mean power pulsed sources in J-band. D.R.Brambley and D.C.Smith 307

High-efficiency millimetre-wave silicon impatt oscillators. H.S.Gokgor, I.Davies, A.M.Howard and D.M.Brookbanks 744

High mobility GaAs-Al_xGa_{1-x} As single period modulation-doped heterojunctions. L.C.Witkowski, T.J.Drummond, S.A.Barnett, H.Morkoc, A.Y.Cho and J.E.Greene 126

High-performance millimetrewave GaAs Schottky-barrier flip-chip diode. C.S.Setzer and R.J.Mattauch 555

High-speed frequency dividers with quasi-normally-off GaAs MESFETs. F.Damay-Kavala, G.Nuzillat and C.Arnodo 968

High-speed $Ga_{0.47}In_{0.53}As$ photoconductive detector for picosecond light pulses. H.J.Klein, R.Kaumanns and H.Beneking 421

High-voltage buried-channel MOS fabricated by oxygen implantation into silicon. M.Akiya, K.Ohwada and S.Nakashima 640

Hot electron effects in Schottky barrier mixers at high frequencies. S.J.Beard and H.D.Rees 811

Improved mobility in OM-VPE-grown $Ga_{1-x}In_xAs$. W.T.Dietze, M.J.Ludowise and C.B.Cooper 698

Improvement in surface morphology of InGaAsP-InP wafers by dummy layer technique. J.Kinoshita and Y.Uematsu 223

$In_{0.53}Ga_{0.47}As$ contact layer for 1.3 μm light-emitting diodes. H.Temkin, A.K.Chin and M.A.Digiuseppe 703

InGaAsP/InP BH lasers on p-type InP substrates. Y.Nakano, K.Takahei, Y.Noguchi, H.Nagai, K.Nawata and M.Tokunaga 645

InP Gunn oscillators in V-band. J.J.Sowers, B.A.Janis, J.D.Crowley and F.B.Fank 708

InP MESFET with $In_{0.53}Ga_{0.47}$ As/InP heterostructure contacts. T.Ishibashi 215
Interface states in MOSFETs due to hot-electron injection determined by the charge pumping technique. D.Schmitt and G.Dorda 761
Ion-implanted E/D-type GaAs IC technology. T.Furutsuka, T.Tsuji, F.Katano, A.Higashisaka and K.Kurumada 944
Low breakdown voltage Schottky diode as voltage regulator. R.S.Popović and D.A.Mladenović 214
Low-dose Si ion implantation into semi-insulating LEC GaAs. H.Yamazaki, T.Honda and S.Miyazawa 817
Low-frequency noise spectrum of GaAs FETs. J.Graffeuil 387
Low-noise 10.7 GHz cooled GaAs FET amplifier. G.Tomassetti, S. Weinreb and K.Wellington 949
Low-power gigabit logic by GaAs SSFL. N.Hashizume, H.Yamada, T.Kojima, K.Matsumoto and K.Tomizawa 553
Low-temperature process to increase the grain size in polysilicon films. R.Reif and J.E.Knott 586
LPE growth of 1.3 μm InGaAsP CW lasers on (110) InP substrates. F.Z.Hawrylo 282
Method of fabricating high-Q silicon varactor diodes. A.Rosen, C.P.Wu, M.Caulton, A.Gombar and P.Stabile 707
Microheater and microbolometer using microbridge of SiO_2 film on silicon. M.Kimura 80
Microstrip impatt-diode oscillator for 100 GHz. G.B.Morgan 570
Minority-carrier injection into diffused region of small N^+-P junction. A.A.Eltoukhy and D.J.Roulston 619
Mn as a p-type dopant in $In_{0.53}Ga_{0.47}As$ on InP substrates. N.Chand, P.A.Houston and P.N.Robson 726
Modelling of dual-gate MESFETS with second gate forward biased. P.C.Chao and W.H.Ku 574
Modulation frequency characteristics of directly optical frequency modulated AlGaAs semiconductor laser. S.Kobayashi, Y.Yamamoto and T.Kimura 350
Monolithic GaAs travelling-wave amplifier. Y.Ayasli, J.L.Vorhaus, R.Mozzi and L.Reynolds 413
New technique for determination of static emitter and collector series resistances of bipolar transistors. W.Filensky and H.Beneking 503
New technique for determination of static emitter and collector series resistances of bipolar transistors (Comment). R.J.Hawkins 735
New technique for fabrication of low voltage Si zener diodes. N.D.Stojadinović, Lj.Dj.Ristić and B.V.Vidanović 130
Noise characteristics in line-narrowed semiconductor lasers with optical feedback. L.Goldberg, A.Dandridge, R.O.Miles, T.G.Giallorenzi and J.F.Weller 677
Novel CMOS Schmitt trigger. K.Nagaraj and M.Satyam 693
Ohmic contacts on n-GaAs produced by spark alloying. R.D'Angelo and P.A.Verlangieri 290
Optical FM signal amplification and FM noise reduction in an injection locked AlGaAs semiconductor laser. S.Kobayashi, Y.Yamamoto and T.Kimura 849
Optically frequency modulated GaAs MESFET oscillator. B.Loriou, J.Guena and J.F.Sautereau 901
OTDR in monomode fibres at 1.3 μm using a semiconductor laser. P.Healey 62
Performance of a scaled Si gate n-well CMOS technology. G.Zimmer, H.Fielder, B.Hoefflinger, E.Neubert and H.Vogt 666
Pin diodes in meander-line filters for multiplexing applications. G.N.O.Ugwuagu and H.V.Shurmer 702
Planar normally-off GaAs JFET for high speed logic circuits. Y.Kato, M.Dohsen, J.Kasahara, K.Taira and N.Watanabe 951
Power limiting due to impact ionisation in GaAs MESFETS. P.H.Ladbrooke 338
Preparation of $CuInS_2$ on GaP grown by LPE. H.L.Hwang, W.J.Lin, H.J.Chang and C.Y.Sun 245
Pressure dependence of hole mobility in $In_{1-x}Ga_xAs_yP_{1-y}$ and its relation to alloy scattering. J.R.Hayes, H.L.Tatham, A.R.Adams and P.D.Greene 230
Pulsed thermal annealing of arsenic-implanted silicon. P.D.Scovell 403
Reduction of FM noise in impatt oscillators by optical illumination. A.J.Seeds and J.R.Forrest 865
Refractive index data from Ga_x $In_{1-x}As_y$ P_{1-y} films. P.Chandra, L.A.Coldren and K.E.Strege 6
Reliability of AuGe/Pt and AuGe/Ni ohmic contacts on GaAs. C.P.Lee, B.M.Welch and W.P.Fleming 407
Room temperature CW operation of GaInAsP/InP double-heterostructure diode lasers emitting at 1.23 μm grown by low-pressure metalorganic chemical vapour deposition. M.Razeghi, J.P.Hirtz, P.Hirtz, J.P.Larivain, R.Bondeau, B.De Cremoux and J.P.Duchemin 597
S-band trapatt oscillator with reduced frequency-temperature dependence. G.Tubridy 579
Schmitt trigger circuit with picosecond risetimes. L.Bickers 695
Schottky-barrier coupled Schottky-barrier gate GaAs FET logic. N.Hashizume, H.Yamada and K.Tomizawa 51
Schottky-barrier elevation by ion implantation and implant segregation. R.L.Thornton 485
Schottky drain microwave GaAs field effect transistors. D.Meignant and D.Boccon-Gibod 107
Selective carrier removal using oxygen implantation in GaAs. M.Berth, C.Venger and G.M.Martin 873
Self-aligned normally-off GaAs MESFET using Sn-doped SiO_2 glass. Y.Ishii and Y.Kawasaki 834
Sidewall effects in shallow emitter of small bipolar transistor. A.A.Eltoukhy and D.J.Roulston 845
Single-interface enhanced mobility structures by metalorganic chemical vapour deposition. J.J.Coleman, P.D.Dapkus and J.J.J.Yang 606
Speed-power property of GaAs Schottky-barrier coupled Schottky-barrier gate FET logic. K.Tomizawa, N.Hashizume, K.Matsumoto and F.Suzuki 821 e936
Stability of aluminium-polysilicon photovoltaic junctions. D.J.Thomson, M.A.Matiowsky and H.C.Card 382
Submicrometre lift-off line with T-shaped cross-sectional form. M.Matsumura, K.Tsutsui and Y.Naruke 429
Submicron resolution deep UV photolithography. A.M.Voshchenkov and H.Herrmann 61
Temperature dependence of peak heights in deep-level transient spectroscopy. P.I.Rockett and A.R.Peaker 838
Temperature dependence of the Gunn threshold in GaAs. A.R.Adams and H.L.Tatham 557
Temperature dependence of the transferred electron threshold current in $In_{1-x}Ga_xAs_yP_{1-y}$. K.C.Heasman, J.R.Hayes, A.R.Adams and P.D.Greene 756
Temperature effect on low threshold voltage ion-implanted GaAs MESFETs. S.J.Lee and C.P.Lee 760
Theory of switching in polysilicon-n-p^+ silicon structures. K.Board and M.Darwish 41
Three period (Al, Ga)As/GaAs heterostructures with extremely high mobilities. T.J.Drummond, W.Kopp and H.Morkoç 442
Threshold voltage of a narrow-width MOSFET. L.A.Akers 49
Time dependence of current at high electric fields in $Al_xGa_{1-x}As$-GaAs heterojunction layers. M.Keever, T.Drummond, K.Hess, H.Morkoc and B.G.Streetman 93
Time-dependent thermal effects in current-modulated semiconductor lasers. L.Goldberg, H.F.Taylor and J.F.Weller 497
Transferred-electron oscillators at very high frequencies. A.M.Mazzone and H.D.Rees 539
Transmission cathodoluminescence as a screening technique for rake lines in (Al, Ga)As DH laser material. C.A.Gaw and C.L.Reynolds 285
Transport properties in GaAs-$Al_xGa_{1-x}As$ heterostructures and MESFET application. P.Delescluse, M.Laviron, J.Chaplart, D.Delagebeaudeuf and N.T.Linh 342
Ultrabroadband GaAs monolithic amplifier. K.Honjo, T.Sugiura and H.Itoh 927
Undoped semi-insulating LEC GaAs: a model and a mechanism. J.R.Oliver, R.D.Fairman, R.T.Chen and P.W.Yu 839
V-grooved substrate buried heterostructure InGaAsP/InP laser. H.Ishikawa, H.Imai, T.Tanahashi, Y.Nishitani and M.Takusagawa 465
Variation of diffused boron concentration in the neighbourhood of an oxide-masked edge. S.A.Abbasi, O.Takleh, A.Brunnschweiler and J.G.Smith 578
Very-high speed back-illuminated InGaAs/InP PIN punch-through photodiodes. T.P.Lee, C.A.Burrus, K.Ogawa and A.G.Dentai 431
VVMOS power transistors: upper and lower bounds of the on-resistance. T.D.Tsibukis and E.E.Kriezis 353
Waveguide cavity FET oscillator. A.Materka and S.Mizushina 902

SIGNAL PROCESSING

Acoustionjection transistor - A new type of electrically controlled transducer. Yu.V.Gulyaev, G.D.Mansfeld and G.A.Orlova 396
Analysis of noise, sensitivity and dynamic range in digital filters using multiplier extraction approach. P.M.Hughes and B.M.G.Cheetham 286
Delay reduction techniques in phase-locked loop amplifiers. C.J.Ward 253
Differential encoding of composite SECAM colour TV signals. H.Gharavi 122
Discrimination of pulsed and CW signals using SAW power cepstrum analysis. M.A.Jack, D.McKee, A.D.Milne and M.Warden 39
Effect of threshold offsets in zero-crossing speech detector. M.R.L.Hodges 682
Efficient calculation of multimode CPFSK spectra. L.F.Lind and A.A.De Albuquerque 456
Encoding of analogue signals using surface-acoustic-wave chirp filters. M.Kowatsch, J.Lafferl, F.Ungersbäck and F.J.Seifert 475
Equivalent-time signal acquisition and processing. J.J.O'Reilly 911
Error performance of frequency-hopped DPSK system. K.Yamada and K.Daikoku e673
Estimation of time-varying co-ordinates of ion beams. W.J.Szajnowski 489
Extraction of decision level for envelope-detected amplitude-shift keying. W.Hodgkiss 881
False-lock avoidance scheme for Costas loops. A.Makarios and T.C.Tozer 490
Fast calculation of impulse responses without multiplications. J.Justesen 700
Forward covariance least-squares algorithm: a new method in AR spectral estimation. P.D.Scott and C.L.Nikias 111
General analysis of bilinear SAW convolvers. D.P.Morgan 265

Impact of entropic coding on the time delays associated with time-encoded speech (TES) systems. R.A.King and J.Holbeche 394
Influence of two-path propagation on MSK systems. P.Szulakiewicz 893
New method for direct G/T measurement using satellite signals. A.Sion 883
Phase invariant delay approximations. G.Wilson and M.Papamichael 294
Phase-lock-loop operating ranges measurement. R.C.Den Dulk and M.P.I.Huisman 691
Power spectra of M-ary variable index CPFSK. K.M.Sundara Murthy and K.W.Cattermole 888
Rapid interference suppression using Kalman filter approach. K.Krucker 65
Realisation of a decoder for two MFM codes. J.Isailović 117
Retiming 2.24 Gbit/s and demultiplexing 2.24 to 1.12 Gbit/s in an optical transmission system by means of a single-gate field-effect transistor. B.Enning 548
Simple algorithm to improve LPC vocoder speech with noisy input. L.Vanhove 149
Simple phase-locked loop with large pull-in range to noise bandwidth ratio. R.C.Halgren and I.R.Peterson 448
Some arithmetically symmetrical bandpass filters. P.Varanasi and S.C.Dutta Roy 26
Spectral calculation of partial response multi-h phase codes. L.F.Lind and A.A.de Albuquerque 711
Spectral distribution of a sampled 1st-order lowpass filtered white noise. C.A.Gobet 720
Truncation error in 2-D block mode filtering. M.R.Azimi Sadjadi and R.A.King 217
Use of error patterns in coded communication systems. W-H Ng 241

SOLAR CELLS

Flash technique for GaAs concentrator solar cell measurement. E.Fanetti 469
New method for maximum power consideration in solar cells with and without resistive losses. K.K.Govil and K.K.Aggarwal 5
Numerical simulation of solar cell open circuit voltage decay. L.Castaner, J.Llaberia, J.Garrido and E.Vilamajo 745
Theoretical advantages of pn^+-type Cu_2S-ZnO solar cell. M.Burgelman and H.J.Pauwels 224

SUPERCONDUCTING DEVICES

Phase-plane analysis of simple Josephson junction model. V.Dvorak 980
Static characteristic of a new quasiparticle injected superconducting weak link device. S.Sakai and H.Tateno 501

SURFACE ACOUSTIC WAVES

Adaptive noise cancellation with a SAW storage correlator. J.E.Bowers and G.S.Kino 460
Analogue buffer memory for high speed rate conversion. G.F.Manes, P.Tortoli, D.Gerli and C.Atzeni 58
Anisotropy detection in sapphire by acoustic microscope using line-focus beam. J.Kushibiki, A.Ohkubo and N.Chubachi 534
Discrimination of pulsed and CW signals using SAW power cepstrum analysis. M.A.Jack, D.McKee, A.D.Milne and M.Warden 39
Effects of surface metallisation on SSBW and BGW propagation in quartz. M.Yamaguchi, K.Y.Hashimoto and H.Kogo 602
Efficient three-wavelength-output SAW multistrip beam compressor for convolver applications. S.Ameri and D.J.Gunton 836 e900
Extension of time-bandwidth product in SAW spectrum analysers. P.A.Campbell, P.M.Grant and J.W.Arthur 576
High frequency acoustic plate mode device employing interdigital transducers. M.F.Lewis 819
High frequency ZnO-SiO_2-Si surface acoustic wave convolvers. M.R.Melloch, R.L.Gunshor and R.F.Pierret 827
Lithium tetraborate: a new temperature-compensated SAW substrate material. R.W.Whatmore, N.M.Shorrocks, C.O'Hara, F.W.Ainger and I.M.Young 11
Mismatch losses in multiply tapped SAW convolvers. E.L.Adler 866
Multiplexing system for fibre optic sensors using pulse compression techniques. A.R.Nelson, D.H.McMahon and H.van de Vaart 263
Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method. M.Koshiba, M.Okada and M.Suzuki 609
Precise delay/phase measurement using surface-acoustic waves and microprocessing. R.B.Ward 417
SAWDIC: Surface-acoustic-wave-driven directional coupler. C.H.Von Helmolt, H.F.Schlaak and R.T.Kersten 446
SAWDIF: Surface-acoustic-wave-driven interferometer. C.H.Von Helmolt 447
Shear surface elastic waves on large amplitude gratings. N.E.Glass and A.A.Maradudin 773
Temperature-stable surface-acoustic-wave delay lines on gallium arsenide: second-order effects and sensitivities. J.M.Saurel, J.Lassale, G.Shahab, G.Cambon and J.Attal 344
Temperature variation of SAW power flow angle. D.F.Williams and F.Y.Cho 164
Ultra low bulk orientations of lithium niobate for SAW TV filters. R.F.Milson, R.J.Murray, I.Flinn and M.Redwood 89
Voltage-controlled SAW filter on berlinite. J.Henaff, M.Feldmann and M.Carel 86

SWITCHING AND SWITCHING CIRCUITS

High-power subnanosecond switch. I.V.Grekhov, A.F.Kardo-Sysoev, L.S.Kostina and S.V.Shenderey 422
Multistage monostable multivibrator using load-coupled regenerative feedback. K.Nagaraj and M.Satyam 159
Simple switching technique for fast PLL frequency synthesisers. M.J.Underhill and R.I.H.Scott 405

TELECOMMUNICATION

12 GHz receiver with self-oscillating dual-gate MESFET mixer. C.Tsironis 617
Conditions for synchronisation and corresponding user capacities for spread-spectrum multiple-access systems. M.Beale 410 e862
SSB-FDM using complementary comb filters. Y.Hirata 614
Wide-sense nonblocking network made of square switches. V.E.Beneš and R.P.Kurshan 697

ULTRASONICS

Acoustic microscopy with noncoherent source. J.Attal, N.Truong-Quang, G.Cambon, J.M.Saurel and M.Rouzeyre 116
Broad bandwidth concave transducer for scanning acoustic microscope. J.Kushibiki, T.Sannomiya and N.Chubachi 42
Depth of field improvements in long wavelength imaging systems. J.C.Bennett and A.Yamani 860
Double-layer acoustic antireflection coating for sapphire/water interface. J.Kushibiki and N.Chubachi 59
Grating acoustic scanner using bulk acoustic waves. W.H.Chen and E.G.Lean 141
Shear-wave transducer using ferroelectric medium with distributed polarisation. K.Yamanouchi 956

WAVEGUIDES

Additional losses and time delay fluctuations of TE_{11} modes in curved circular waveguides-application to feeder antennas. C.Fray, I.Andritsos and A.Papiernik 362
Approximate solution for step discontinuity in dielectric slab waveguide. T.Yoneyama and S.Nishida 151
Calculation of lateral current spreading and series resistance effects in oxide stripe geometry GaAs-GaAlAs DH lasers. G.Lengyel, P.Meissner, E.Patzak and K.H.Zschauer 174
Cross-tie slow-wave coplanar waveguide on semi-insulating GaAs substrates. S.Seki and H.Hasegawa 940
Equivalent circuit for radial-line/coaxial-line junction. A.G.Williamson 300
Equivalent network analysis of dielectric thin-film waveguide with trapezoidal cross-section. M.Koshiba and M.Suzuki 283
Equivalent network analysis of dielectric thin-film waveguide with trapezoidal cross-section (Comment and reply). J.Buus 497
Experimental evaluation of bend radiation losses in millimetric dielectric waveguide. M.R.Inggs and N.Williams 75
Experimental millimetric array using dielectric radiators fed by means of dielectric waveguide. M.T.Birand and R.V.Gelsthorpe 633
Finite-element analysis of angularly dependent modes in a general RF periodic cavity. G.Y.Philippou, G.S.Gupta and J.B.Davies 588
Finite-element analysis of discontinuity problem of SH modes in an elastic plate waveguide. M.Koshiba, H.Morita and M.Suzuki 480
Finite-element analysis of topographic waveguides for acoustic surface waves using approximate analytical solutions. M.Koshiba, M.Okada and M.Suzuki 856
GaInAsP/InP integrated laser with butt-jointed built-in distributed-Bragg-reflection waveguide. Y.Abe, K.Kishino, Y.Suematsu and S.Arai 945
Guides modes of a parabolic-core slab waveguide. A.Yata and H.Ikuno 115
Input VSWR of profiled E-plane tapers. M.T.Birand and N.Williams 220
Ion implanted optical waveguides in $LiNbO_3$. G.D.H.King, M.C.Bone, B.L.Weiss and D.W.Weeks 897
Le maillage rectangulaire et le changement de maille dans la methode TLM en deux dimensions. P.Saguet and E.Pic 277
Lens design for surface wave applications. T.Yoneyama, M.Shimokoriyama and S.Nishida 210
Mode conversion in profiled E-plane tapers and horns. M.T.Birand, P.Wright and N.Williams 885

Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method. M.Koshiba, M.Okada and M.Suzuki 609
Original improvements of TLM method. M.Leroy 684
Picosecond pulse generation by lateral mode switching of (GaAl)As-heterostructure stripe lasers. I.H.White, G.J.Aspin, J.E.Carroll and R.G.Plumb 541
Reflection analysis of flanged circular waveguide radiating through small aperture into absorbing medium. C.Fray, K.Chandrasekhar and A.Papiernik 718
Simplified numerical analysis of optical fibres and planar waveguides. R.A.Sammut and C.Pask 105
Single-mode fibres in a few moments. C.D.Hussey and C.Pask 644
Single-mode optical Y-branching circuit using deposited silica guides (DS guides). Y.Murakami and M.Ikeda 411
Slot ring resonator and dispersion measurement on slot lines. K.Kawano and H.Tomimuro 916
Stripe waveguide Y-intersection as efficient coupler for multimode optical communication systems. A.D.De Oliveira, M.G.F.Wilson and O.Parriaux 100
Synthesis of surface reactances using grounded pin bed structure. R.J.King and K.S.Park 52
Theoretical comparison of crosspolar performance of dielectric and corrugated feeds. P.J.B.Clarricoats 317
Thermo-optic effect in $LiNbO_3$ for light deflection and switching. M.Haruna and J.Koyama 842
Tube-controlled slab waveguide for millimetre and submillimetre waves. J.Gomi, T.Yoneyama and S.Nishida 125
Waveguide cavity FET oscillator. A.Materka and S.Mizushina 902

PRINTED BY Unwin Brothers Limited
THE GRESHAM PRESS OLD WOKING SURREY ENGLAND